



DEFENSE INFORMATION SYSTEMS AGENCY

P. O. BOX 549
FORT MEADE, MARYLAND 20755-0549

IN REPLY
REFER TO: Joint Interoperability Test Command (JTE)

19 Jun 13

MEMORANDUM FOR DISTRIBUTION

SUBJECT: Extension of the Special Interoperability Test Certification of the Brocade ICX6000 Series Release 7.3.0d

References: (a) DoD Directive 4630.05, "Interoperability and Supportability of Information Technology (IT) and National Security Systems (NSS)," 5 May 2004
(b) CJCSI 6212.01E, "Interoperability and Supportability of Information Technology and National Security Systems," 15 December 2008
(c) through (f), see Enclosure

1. References (a) and (b) establish Defense Information Systems Agency (DISA), Joint Interoperability Test Command (JITC), as the responsible organization for interoperability test certification.

2. The Brocade ICX6610-24 and ICX6610-48P Release 7.3.0c are hereinafter referred to as the System Under Test (SUT). The SUT meets all of its critical interoperability requirements and is certified for joint use within the Defense Information System Network (DISN) as an Assured Services Local Area Network (ASLAN) Core and Distribution switch in a stacked configuration and as a Layer 2/Layer 3 Access switch in either a stacked or single component configuration. The SUT is certified as interoperable for joint use with other ASLAN components listed on the UC APL with the following interfaces: 100/1000Base SX/LX, 10GbaseX, and 10/100/1000BaseT. The other products, listed in Table 1 below, employ the same software and similar hardware as the SUT. JITC analysis determined these systems to be functionally identical to the SUT for interoperability certification purposes and therefore, they are also certified for joint use. The SUT meets the critical interoperability requirements set forth in Reference (c), using test procedures derived from Reference (d).

The SUT is certified to support Assured Services within an ASLAN. If a component meets the minimum requirements for deployment in an ASLAN, it also meets the lesser requirements for deployment in a non-ASLAN. Non-ASLANs are "commercial grade" and provide support to Command and Control (C2) (ROUTINE only calls) (C2(R)) or non-C2 voice subscribers. When deployed in a non-ASLAN, the SUT may also be used to receive all levels of precedence, but is limited to supporting calls that are originated at ROUTINE precedence only. Non-ASLANs do not meet the availability or redundancy requirements for C2 or Special C2 users and therefore are not authorized to support precedence calls originated above ROUTINE.

No other configurations, features, or functions, except those cited within this document, are certified by JITC. This certification expires upon changes that could affect interoperability, but

no later than three years from the date of the original Unified Capabilities (UC) Approved Product List (APL) memorandum (24 July 2012).

3. The extension of this certification is based upon Desktop Review (DTR) 2. The original certification is based on interoperability testing conducted by JITC, review of the vendor’s Letters of Compliance (LoC), DISA adjudication of open test discrepancy reports (TDRs), and DISA Certifying Authority (CA) Recommendation, and documented in Reference (e). Interoperability testing was conducted by JITC, Fort Huachuca, Arizona, from 12 March through 5 April 2012. Review of the vendor’s LoC was completed on 9 April 2012. DISA adjudication of outstanding TDRs was completed on 24 April 2012. The DISA CA provided a positive Recommendation on 13 July 2012 based on the security testing completed by DISA-led IA test teams and published in a separate report, Reference (f). This DTR was requested to update the part numbers for the ICX6450 series to include “-A” at the end of the model number. These products are identical to the ones tested, the “-A” is for Brocade’s internal tracking purposes. Table 1 denotes the updated part numbers next to the certified components numbers they are identical to. JITC determined through analysis that this DTR would not impact the interoperability certified features and functions of the SUT. Additionally, the DISA CA has approved this DTR to include the additional “-A” in the ICX6450 series without further testing. Therefore, the original IA approval applies to this DTR and JITC approves this DTR.

4. Table 1 provides a UC APL product summary. Table 2 provides the SUT interface interoperability status and Table 3 provides the Capability Requirements (CR) and Functional Requirements (FR) status. The threshold CR/FRs for ASLAN components are established by Section 5.3.a of Reference (c) and were used to evaluate the interoperability of the SUT.

Table 1. UC APL Product Summary

SUT (See notes 1 and 2.)	Release	Function	Sub-component	Description
Brocade ICX6430-24, ICX6430-24P, ICX6430-48, ICX6430-48P, ICX6450-24 (ICX6450-24-A), ICX6450-24P (ICX6450-24P-A), ICX6450-48 (ICX6450-48-A), ICX6450-48P (ICX6450-48P-A), ICX6610-24-E, ICX6610-24-PE, ICX6610-24-I, ICX6610-24-PI, ICX6610-24P-E, <u>ICX6610-24P-PE</u> , ICX6610-24P-I, ICX6610-24P-PI, ICX6610-24F-E, ICX6610-24F-PE, ICX6610-24F-I, ICX6610-24F-PI, ICX6610-48-E, ICX6610-48-PE, ICX6610-48-I, ICX6610-48-PI, ICX6610-48P-E, <u>ICX6610-48P-PE</u> , ICX6610-48P-I, ICX6610-48P-PI	7.3.0d (See note 3.)	Core, Distribution, Access	Not Applicable	One rack-unit high stackable switch

NOTES:

- Components bolded and underlined were tested by JITC. The other components in the family series were not tested; however, they utilize the same software and similar hardware and JITC analysis determined them to be functionally identical for interoperability certification purposes and they are also certified for joint use.
- This DTR was requested to update the part numbers for the ICX6450 family products to include “-A”. These products are identical to the ones tested; however, they have “-A” for internal tracking purposes.
- The SUT was updated from Release 7.3.0c to Release 7.3.0d with DTR 1.

LEGEND:

APL	Approved Products List	JITC	Joint Interoperability Test
DTR	Desktop Review	Command	
HPOE	High Power over Ethernet	UC	Unified Capabilities

Table 2. SUT Interface Interoperability Status

Interface	Applicability			UCR 2008, Change 3 Reference	Threshold CR/FR (See note 1.)	Status	Remarks
	Co	D	A				
Serial	C	C	C	5.3.1.3.9	1-4	Certified	The SUT met the CRs and FRs with the following standard: EIA-232.
10Base-X	C	C	C (See note 2.)	5.3.1.3.1	1-6	Certified	The SUT met CRs and FRs with the following IEEE standard: 802.3i (10BaseT).
100Base-X	R	R	C (See note 2.)	5.3.1.3.1	1-6	Certified	The SUT met CRs and FRs with the following IEEE standard: 802.3u (100BaseT).
1000Base-X	R	R	C (See note 2.)	5.3.1.3.1	1-6	Certified	The SUT met CR and FRs with the following IEEE standards: 802.3ab (1000BaseT), 802.3z (1000Base-SX, 1000Base-LX).
10000Base-X	C	C	C	5.3.1.3.1	1-6	Certified	The SUT met CRs and FRs with the following IEEE standard: 802.3ae (10GBase-SR, 10GBase-LR).
Wireless	C	C	C	5.3.1.3.1/5.3.1.7.2	1-6	Not Tested	See note 3.

NOTES:

- The SUT high-level CR and FR ID numbers depicted in the Threshold CRs/FRs column can be cross-referenced in Table 3. These high-level CR/FR requirements refer to a detailed list of requirements provided in Reference (e), Enclosure 3.
- Core and Distribution products must minimally support 100Base-X (802.3u) and 1000Base-X (802.3z). Access products must minimally support one of the following standards: 802.3i (10BaseT), 802.3j (10BaseF), 802.3u (100BaseT/F), 802.3z (1000BaseF), or 802.3ab (1000BaseT). Other rates and standards may be provided as conditional interfaces.
- The SUT does not support this interface. This interface is not required for a core, distribution, or access switch.

LEGEND:

802.3ab	1000BaseT Gbps Ethernet over twisted pair at 1 Gbps (125 Mbps)	EIA-232	Electronic Industries Alliance Standard for defining the mechanical and electrical characteristics for connecting Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) data communications devices
802.3ae	10 Gbps Ethernet		
802.3i	10BaseT Mbps over twisted pair		
802.3j	10 Mbps over fiber		
802.3u	Standard for carrier sense multiple access with collision detection at 100 Mbps	FR	Functional Requirement
802.3z	Gigabit Ethernet Standard	Gbps	Gigabits per second
A	Access	ID	Identification
C	Conditional	IEEE	Institute of Electrical and Electronics Engineers
Co	Core	Mbps	Megabits per second
CR	Capability Requirement	R	Required
D	Distribution	SUT	System Under Test
		UCR	Unified Capabilities Requirements

Table 3. SUT CRs and FR Status

CR/FR ID	Capability/Function	Applicability (See note 1.)	UCR Reference	Status
1	General Performance Parameters			
	Performance Parameters	Required	5.3.1.3	Met
	Port Interface Rates	Required	5.3.1.3.1	Met
	Port Parameter Requirements	Required	5.3.1.3.2	Met
	Class of Service Markings	Required	5.3.1.3.3	Met
	VLAN Capabilities	Required	5.3.1.3.4	Met
	Protocols	Required	5.3.1.3.5	Met
QoS Features	Required	5.3.1.3.6	Met	

Table 3. SUT CRs and FR Status

CR/FR ID	Capability/Function	Applicability (See note 1.)	UCR Reference	Status
2	General Performance Parameters (continued)			
	Network Monitoring	Required	5.3.1.3.7	Met
	Security	Required	5.3.1.3.8	Met
3	E2E Performance Requirements			
	Voice Services	Required	5.3.1.4.1	Met (See note 2.)
	Video services	Required	5.3.1.4.2	Met (See note 2.)
	Data services	Required	5.3.1.4.3	Met (See note 2.)
4	NM Requirements			
	Configuration Control	Required	5.3.1.6.1	Met
	Operational Changes	Required	5.3.1.6.2	Met
	Performance Monitoring	Required	5.3.1.6.3	Met
	Alarms	Required	5.3.1.6.4	Met
	Reporting	Required	5.3.1.6.5	Met
5	Engineering Requirements			
	Physical Media	Required	5.3.1.7.1	Met (See note 3.)
	Wireless	Conditional	5.3.1.7.2	Not Tested
	Traffic Engineering	Required	5.3.1.7.3	Met (See note 3.)
	Availability	Required	5.3.1.7.6	Met (See note 3.)
	Redundancy	Required	5.3.1.7.7	Met (See notes 3, 4.)
6	MPLS			
	MPLS Requirements	Conditional	5.3.1.8.4.1	Not Tested
	MPLS VPN Augmentation to VLANs	Conditional	5.3.1.8.4.2	Not Tested
7	IPv6 Requirements			
	Product Requirements	Required	5.3.5.4	Partially Met (See notes 5, 6, 7.)
<p>NOTES:</p> <ol style="list-style-type: none"> The annotation of 'required' refers to a high-level requirement category. The applicability of each sub-requirement is provided in Reference (e), Enclosure 3. The system under test does not need to provide conditional requirements. However, if a capability is provided, it must function according to the specified requirements in order to be certified for that capability. This requirement was verified and met using simulated voice, video, and data traffic in an operational emulated environment to meet E2E requirements. The SUT must be deployed in accordance with deployment guide and engineering guidelines provided in UCR Change 3, paragraph 5.3.1.4. This requirement was met with the following stipulations: It is the site's responsibility to configure the SUT in a manner which meets the engineering requirements listed in Reference (e), Enclosure 2, Section 11.2 d and that does not create a single point of failure which could impact more than 96 C2 users. The SUT operates in a stack configuration. In the stack, there is an element which is the Master and another which is the Standby. Remaining elements will be Members and may assume the role of standby upon failure of the Master. Upon failure of the Master element, the standby element becomes Master. However, IPv6 streams required up to 25 seconds before they were resumed. If a Member or Standby element of the stack failed, then IPv6 streams resumed within the required 5 seconds. DISA has accepted and approved the vendor's POA&M and adjudicated this discrepancy as having a minor operational impact. The SUT does not support the following IPv6 RFC: RFC 5340. DISA has accepted and approved the vendor's POA&M and adjudicated this discrepancy as having a minor operational impact. The SUT does not support the following IPv6 RFC: RFC 2711. DISA has accepted and approved the vendor's POA&M and adjudicated this discrepancy as having a minor operational impact. The SUT does not support the following IPv6 RFC: RFC 4302. DISA has accepted and approved the vendor's POA&M and adjudicated this discrepancy as having a minor operational impact. The SUT does not support the following IPv6 RFC: RFC 5340. DISA has accepted and approved the vendor's POA&M and adjudicated this discrepancy as having a minor operational impact. 				

Table 3. SUT CRs and FR Status (continued)

LEGEND:			
C2	Command and Control	NM	Network Management
CR	Capability Requirement	POA&M	Plan of Action and Milestones
DISA	Defense Information Systems Agency	QoS	Quality of Service
E2E	End-to-End	RFC	Request For Comment
FR	Functional Requirement	SUT	System Under Test
IPSec	Internet Protocol Security	UCR	Unified Capabilities Requirements
IPv6	Internet Protocol version 6	VLAN	Virtual Local Area Network
MPLS	Multiprotocol Label Switching	VPN	Virtual Private Network

5. No detailed test report was developed in accordance with the Program Manager's request. JITC distributes interoperability information via the JITC Electronic Report Distribution (ERD) system, which uses Unclassified-But-Sensitive Internet Protocol Router Network (NIPRNet) e-mail. More comprehensive interoperability status information is available via the JITC System Tracking Program (STP). STP is accessible by .mil/gov users on the NIPRNet at <https://stp.fhu.disa.mil>. Test reports, lessons learned, and related testing documents and references are on the JITC Joint Interoperability Tool (JIT) at <http://jit.fhu.disa.mil> (NIPRNet). Due to the sensitivity of the information, the Information Assurance Accreditation Package (IAAP) that contains the approved configuration and deployment guide must be requested directly through government civilian or uniformed military personnel from the Unified Capabilities Certification Office (UCCO), e-mail: disa.meade.ns.list.unified-capabilities-certification-office@mail.mil. All associated data is available on the DISA UCCO website located at [website located at http://www.disa.mil/Services/Network-Services/UCCO](http://www.disa.mil/Services/Network-Services/UCCO).

6. The JITC point of contact is Capt Jonathan Kim, DSN 879-5182, commercial (520) 538-5182, FAX DSN 879-4347, or e-mail to jonathan.s.kim.mil@mail.mil. JITC's mailing address is P.O. Box 12798, Fort Huachuca, AZ 85670-2798. The UCCO tracking number for the SUT is 1132702.

FOR THE COMMANDER:

Enclosure a/s


for RICHARD A. MEADOR
Chief
Battlespace Communications Portfolio

JITC Memo, JTE, Extension of the Special Interoperability Test Certification of the Brocade
ICX6000 Series Release 7.3.0d

Distribution (electronic mail):

DoD CIO

Joint Staff J-6, JCS

USD(AT&L)

ISG Secretariat, DISA, JTA

U.S. Strategic Command, J665

US Navy, OPNAV N2/N6FP12

US Army, DA-OSA, CIO/G-6 ASA(ALT), SAIS-IOQ

US Air Force, A3CNN/A6CNN

US Marine Corps, MARCORSSYSCOM, SIAT, A&CE Division

US Coast Guard, CG-64

DISA/TEMC

DIA, Office of the Acquisition Executive

NSG Interoperability Assessment Team

DOT&E, Netcentric Systems and Naval Warfare

Medical Health Systems, JMIS IV&V

HQUSAISEC, AMSEL-IE-IS

UCCO

ADDITIONAL REFERENCES

- (c) Office of the Assistant Secretary of Defense, "Department of Defense Unified Capabilities Requirements 2008, Change 3," September 2011
- (d) Joint Interoperability Test Command, "ASLAN Component Test Plan (UCTP)," November 2010
- (e) Joint Interoperability Test Command, Memo, JTE, "Special Interoperability Test Certification of the Brocade ICX6000 Series with Release 7.3.0c," 20 July 2012
- (f) Joint Interoperability Test Command, "Information Assurance (IA) Assessment of Brocade ICX Series Release (Rel.) 7.3.0c (Tracking Number 1132702)," 20 July 2012