



## DEFENSE INFORMATION SYSTEMS AGENCY

P. O. BOX 4502  
ARLINGTON, VIRGINIA 22204-4502

IN REPLY  
REFER TO: Joint Interoperability Test Command (JTE)

**6 May 10**

### MEMORANDUM FOR DISTRIBUTION

**SUBJECT:** Special Interoperability Test Certification of the Extreme Summit X350 Series with Release 12.3.1

References: (a) DoD Directive 4630.5, "Interoperability and Supportability of Information Technology (IT) and National Security Systems (NSS)," 5 May 2005  
(b) CJCSI 6212.01E, "Interoperability and Supportability of Information Technology and National Security Systems," 15 December 2008  
(c) through (d), see Enclosure 1

1. References (a) and (b) establish the Defense Information Systems Agency (DISA), Joint Interoperability Test Command (JITC), as the responsible organization for interoperability test certification.

2. The Extreme Summit X350-48T with Release 12.3.1 is hereinafter referred to as the system under test (SUT). The SUT met the interface and functional requirements for an Assured Services Local Area Network (ASLAN) Layer 2 access switch as described in Reference (c). The SUT is certified as interoperable for joint use with other ASLAN components listed on the Unified Capabilities (UC) Approved Products List (APL) with the following interfaces: 1000 Base SX/LX and 10/100/1000 BaseT. Testing was conducted using test procedures derived from Reference (d). The Extreme Summit X350-24t, X350-24t-TAA, and X350-48t-TAA employ the same software and similar hardware as the SUT. The JITC analysis determined these systems to be functionally identical to the SUT for interoperability certification purposes and they are also certified for joint use.

The SUT is certified to support DSN Assured Services over Internet Protocol. If a component meets the minimum requirements for deployment in an ASLAN, it also meets the lesser requirements for deployment in a non-ASLAN. Non-ASLANs are "commercial grade" and provide support to Command and Control (C2) (ROUTINE only calls) (C2(R)) or non-C2 voice subscribers. The SUT is certified for joint use deployment in a non-ASLAN for C2R and non-C2 traffic. When deployed in a non-ASLAN, the SUT may also be used to receive all levels of precedence, but is limited to supporting calls that are originated at ROUTINE precedence only. Non-ASLANs do not meet the availability or redundancy requirements for C2 or Special C2 users and therefore are not authorized to support precedence calls originated above ROUTINE.

Testing of the SUT did not include video services or data applications; however, simulated preferred data, best effort data, and video traffic was generated during testing to determine the SUT's ability to prioritize and properly queue voice media and signaling traffic. No other configurations, features, or functions, except those cited within this document, are certified by

the JITC. This certification expires upon changes that affect interoperability, but no later than three years from the date of Defense Information Assurance (IA)/Security Accreditation Working Group (DSAWG) accreditation.

3. This finding is based on interoperability testing conducted by JITC, review of the vendor's Letters of Compliance (LoC), and DSAWG accreditation. Interoperability testing was conducted by JITC at the Global Information Grid Network Test Facility, Fort Huachuca, Arizona, from 4 August through 4 December 2009. Review of the vendor's LoC was completed on 15 February 2010. DSAWG granted accreditation on 4 March 2010 based on the security testing completed by DISA-led IA test teams and published in a separate report, Reference (e).

4. Table 1 provides the SUT's interface status. The SUT capability and functional requirements are listed in Table 2.

**Table 1. SUT Interface Status**

Interface	Applicability	CRs/FRs (See note 1.)	Status
	Access		Access
<b>Network Management Interfaces for Layer 2 Access Switches</b>			
EIA/TIA (Serial) 232	R	EIA/TIA-232	Met
IEEE 802.3i (10BaseT UTP)	C	1, 6-15, 18-28, 31, 32-36, 49	Not Tested <sup>2</sup>
IEEE 802.3u (100BaseT UTP)	C	1, 6-15, 18-28, 31, 32-36, 49	Met
IEEE 802.3ab (1000BaseT UTP)	C	1, 6-15, 18-28, 31, 32-36, 49	Met
<b>Uplink Interfaces for Layer 2 Access Switches</b>			
IEEE 802.3u (100BaseT UTP)	R	1-15, 16, 18-24, 28-31, 40, 49	Met
IEEE 802.3u (100BaseFX)	C	1-6, 11, 16, 18-24, 28-31, 40-41, 49	Met
IEEE 802.3ab (1000BaseT UTP)	C	1-16, 18-24, 28-31, 40, 49	Met
IEEE 802.3z (1000BaseX Fiber)	C	1-5, 8-16, 18-24, 28-31, 40, 49	Met
IEEE 802.3ae (10GBaseX)	C	1-5, 8-16, 18, 19, 40-41, 49	Not Tested <sup>2</sup>
<b>Access Interfaces for Layer 2 Access Switches</b>			
IEEE 802.3i (10BaseT UTP)	R	1-15, 18-24, 28-41, 49	Met
IEEE 802.3u (100BaseT UTP)	R	1-15, 18-24, 28-41, 49	Met
IEEE 802.3u (100BaseFX)	C	1-6, 11, 18-24, 28-31, 49	Met
IEEE 802.3ab (1000BaseT UTP)	C	1-15, 18-24, 28-41, 49	Met
IEEE 802.3z (1000BaseX Fiber)	C	1-6, 11, 18-24, 28-31, 49	Met
<b>Generic Requirements for all Interfaces</b>			
Generic Requirements not associated with specific interfaces	R	30-32, 35, 36, 40, 69-71	Met
DoD IPv6 Profile Requirements	R	UCR Section 5.3.5.5 (See note 3.)	Met
Security	R	UCR Sections 5.3.1.3.8, 5.3.1.5, 5.3.1.6, and 5.4 (See note 4.)	Met
<b>NOTES:</b>			
1 The SUT's specific capability and functional requirement ID numbers depicted in the CRs/FRs column can be cross-referenced in Table 2. These requirements are for the following Extreme Summit switch models, which are certified in the Layer 2 access layer: <b><u>Summit X350-48T</u></b> , X350-24t, X350-24t-TAA, and X350-48t-TAA. The JITC tested the devices that are bolded and underlined. The other devices listed that are not bolded or underlined are in the same family series as the SUT were not tested; however, they utilize the same OS software and hardware and JITC analysis determined them to be functionally identical for interoperability certification purposes.			
2 This interface is not offered by the SUT, and is not a required interface.			
3 IPv6 requirements are met by both testing and a vendor letter of compliance.			
4 Security testing is accomplished via DISA-led Information Assurance test teams and published in a separate report, Reference (e).			

**Table 1. SUT Interface Status (continued)**

<b>LEGEND:</b>			
802.3ab	1000BaseT Gbps Ethernet over twisted pair at 1 Gbps (125 Mbps)	EIA-232	Standard for defining the mechanical and electrical characteristics for connecting Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) data communications devices
802.3ae	10 Gbps Ethernet		
802.3i	10BaseT Mbps over twisted pair		
802.3u	Standard for carrier sense multiple access with collision detection at 100 Mbps	FRs	Functional Requirements
802.3z	Gigabit Ethernet Standard	Gbps	Gigabits per second
1000BaseFX	1000 Mbps Ethernet over fiber	ID	Identification
1000BaseT	1000 Mbps (Baseband Operation, Twisted Pair) Ethernet	IEEE	Institute of Electrical and Electronics Engineers
ASLAN	Assured Services Local Area Network	IPv6	Internet Protocol version 6
C	Conditional	JITC	Joint Interoperability Test Command
CRs	Capability Requirements	Mbps	Megabits per second
DISA	Defense Information Systems Agency	OS	Operating System
EIA	Electronic Industries Alliance	R	Required
		SUT	System Under Test
		TIA	Telecommunications Industry Association
		UTP	Unshielded Twisted Pair

**Table 2. SUT Capability and Functional Requirements**

<b>ID</b>	<b>Requirement (See note.)</b>	<b>UCR Reference</b>
1	ASLAN components can have no single point of failure for >96 users for C2 and Special C2 users. Non-ASLAN components can have a single point of failure for C2(R) and non-C2 users. (R)	5.3.1.2.1, 5.3.1.7.7
2	Non-blocking of any voice or video traffic at 50%. (R)	5.3.1.3
3	Maximum of 1 ms of jitter for all ASLAN components. (R)	5.3.1.3
4	Maximum of 0.02% packet loss for core and distribution layer components and 0.01% for access layer components. (R)	5.3.1.3
5	Maximum of 2 ms latency for core and distribution layer components and 2 ms for access layer components. (R)	5.3.1.3
6	100 Mbps IAW IEEE 802.3u and 1 Gbps IAW IEEE 802.3z for core and distribution layer components and 10 Mbps IAW IEEE 802.3i and 100 Mbps IAW IEEE 802.3u for access layer components. (R)	5.3.1.3.1
7	Force mode and auto-negotiation IAW IEEE 802.3, filtering IAW RFC 1812, and flow control IAW IEEE 802.3x. (R)	5.3.1.3.2
8	Auto-negotiation IAW IEEE 802.3. (R)	5.3.1.3.2
9	Force mode IAW IEEE 802.3. (R)	
10	Flow control IAW IEEE 802.3x. (R)	
11	Filtering IAW RFC 1812. (R)	
12	Link Aggregation IAW IEEE 802.3ad (output/egress ports only). (R)	
13	Spanning Tree Protocol IAW IEEE 802.1D. (R)	
14	Multiple Spanning Tree IAW IEEE 802.1s. (R)	
15	Rapid Reconfiguration of Spanning Tree IAW IEEE 802.1w. (R)	
16	LACP link Failover and Link Aggregation IAW IEEE 802.3ad (uplink ports only). (R)	5.3.1.3.2, 5.3.1.7.7.1
17	Class of Service Marking: Layer 3 DSCPs IAW RFC 2474. (R) Layer 2 3-bit user priority field of the IEEE 802.1Q 2-byte TCI field. (C)	5.3.1.3.3
18	VLAN Capabilities IAW IEEE 802.1Q. (R)	5.3.1.3.4
19	Protocols IAW DISR profile (IPv4 and IPv6). IPv4 (R: LAN Switch, Layer 2 Switch): IPv6 (R: LAN Switch, C: Layer 2 Switch). Note: Layer 2 switch is required to support only RFC 2460, 5095, 2464, and be able to queue packets based on DSCPs in accordance with RFC 2474.	5.3.1.3.5

**Table 2. SUT Capability and Functional Requirements (continued)**

ID	Requirement (See note.)		UCR Reference
20	QoS Features	Shall support minimum of 4 queues. (R)	5.3.1.3.6
21		Must be able to assign VLAN tagged packets to a queue. (R)	
22		Support DSCP PHBs per RFCs 2474, 2494, 2597, 2598, and 3246. (R: LAN Switch). Note: Layer 2 switch is required to support RFC 2474 only.	
23		Support a minimum of one of the following: Weighted Fair Queuing (WFQ) IAW RFC 3662, Priority Queuing (PQ) IAW RFC 1046, or Class-Based WFQ IAW RFC 3366. (R)	
24		Must be able to assign a bandwidth or percent of traffic to any queue. (R)	
25	Network Monitoring	SNMP IAW RFC's 1157, 2206, 3410, 3411, 3412, 3413 and 3414. (R)	5.3.1.3.7
26		SNMP traps IAW RFC1215. (R)	
27		Remote monitoring IAW RFC1281 and Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model IAW RFC 3826. (R)	
28	Product Requirements Summary IAW UCR2008 Table 5.3.1-5. (R)		5.3.1.3.9
29	E2E Performance (Voice)	No more than 5 ms Latency over any 5-minute period measured under congestion (100% of link capacity). (R)	5.3.1.4.1
		No more than 3 ms Jitter over any 5-minute period measured under congestion. (R)	
		Packet loss not to exceed engineered (queuing) parameters over any 5-minute period under congestion. (R)	
30	E2E Performance (Video)	No more than 30 ms Latency over any 5-minute period measured under congestion. (R)	5.3.1.4.2
		No more than 30 ms Jitter over any 5-minute period measured under congestion. (R)	
		Packet loss not to exceed engineered (queuing) parameters over any 5-minute period under congestion. (R)	
31	E2E Performance (Data)	No more than 50 ms Latency over any 5-minute period measured under congestion. (R)	5.3.1.4.3
		Packet loss not to exceed engineered (queuing) parameters over any 5-minute period under congestion. (R)	
32	LAN Network Management	Configuration Control for ASLAN and Non-ASLAN. (R)	5.3.1.6.1
33		Operational Controls for ASLAN and Non-ASLAN. (R)	5.3.1.6.2
34		Performance Monitoring for ASLAN and Non-ASLAN. (R)	5.3.1.6.3
35		Alarms for ASLAN and Non-ASLAN. (R)	5.3.1.6.4
36		Reporting for ASLAN and Non-ASLAN. (R)	5.3.1.6.5
37	Redundancy	Redundant Power Supplies. (Required on standalone redundant products.)	5.3.1.7.7
38		Chassis Failover. (Required on standalone redundant products.)	
39		Switch Fabric Failover. (Required on standalone redundant products.)	
40		Non-LACP Link Failover.(R)	
41		Fiber Blade Failover. (R)	
42		Stack Failover. (C) (Required if the stack supports more than 96 users.)	
43		CPU (routing engine) blade Failover. (R)	
49	Support IPv6 packets over Ethernet IAW RFC2464. (R)		5.3.5.4
76	Site Requirements	Engineering Requirements: Physical Media for ASLAN and Non-ASLAN. (R) (Site requirement)	5.3.1.7.1
77		Battery Back up two hours for non-ASLAN components and eight hours for ASLAN components. (R) (Site requirement)	5.3.1.7.5
78		Availability of 99.999 percent (Special C2), and 99.997 percent (C2) for ASLAN (R), and 99.9 percent (non-C2 and C2(R) for non-ASLAN. (R) (Site requirement)	5.3.1.7.6
79	IA Security requirements	Port-Based Access Control IAW IEEE 802.1x (R)	5.3.1.3.2
80		Secure methods for network configuration. SSH2 instead of Telnet and support RFCs 4251-4254. Must use HTTPS instead of http, and support RFCs 2660 and 2818 for ASLAN and Non-ASLAN. (R)	5.3.1.6
81		Security (R)	5.3.1.3.8
82		Must meet IA requirements IAW UCR 2008 Section 5.4 for ASLAN and non-ASLAN. (R)	5.3.1.5
<b>NOTE:</b> All requirements are for core, distribution, and access layer components unless otherwise specified.			

**Table 2. SUT Capability and Functional Requirements (continued)**

<b>LEGEND:</b>					
ASLAN	Assured Services Local Area Network	HTTPS	Hyper Text Transfer Protocol, Secure	ms	millisecond
C	Conditional	IA	Information Assurance	PHB	Per Hop Behavior
C2	Command and Control	IAW	In Accordance with	QoS	Quality of Service
C2(R)	Command and Control ROUTINE only	ID	Identification	R	Required
CPU	Central Processing Unit	IEEE	Institute of Electrical and Electronics Engineers	RFC	Request for Comments
DISR	Department of Defense Information Technology Standards Registry	IPv4	Internet Protocol version 4	SNMP	Simple Network Management Protocol
DSCP	Differentiated Services Code Point	IPv6	Internet Protocol version 6	SSH2	Secure Shell Version 2
E2E	End-to-End	LACP	Link Aggregation Control Protocol	SUT	System Under Test
E2E	End-to-End	LAN	Local Area Network	TCI	Tag Control Information Requirements
Gbps	Gigabits per second	LAN	Local Area Network	UCR	Unified Capabilities Requirements
HTTP	Hypertext Transfer Protocol	Mbps	Megabits per second	VLAN	Virtual Local Area Network
		MPLS	Multiprotocol Label Switching		

5. No detailed test report was developed in accordance with the Program Manager’s request. JITC distributes interoperability information via the JITC Electronic Report Distribution (ERD) system, which uses Unclassified-But-Sensitive Internet Protocol Router Network (NIPRNet) e-mail. More comprehensive interoperability status information is available via the JITC System Tracking Program (STP). The STP is accessible by .mil/gov users on the NIPRNet at <https://stp.fhu.disa.mil>. Test reports, lessons learned, and related testing documents and references are on the JITC Joint Interoperability Tool (JIT) at <http://jit.fhu.disa.mil> (NIPRNet), or <http://199.208.204.125> (SIPRNet). Information related to DSN testing is on the Telecom Switched Services Interoperability (TSSI) website at <http://jitc.fhu.disa.mil/tssi>. Due to the sensitivity of the information, the Information Assurance Accreditation Package (IAAP) that contains the approved configuration and deployment guide must be requested directly through government civilian or uniformed military personnel from the Unified Capabilities Certification Office (UCCO), e-mail: [ucco@disa.mil](mailto:ucco@disa.mil).

6. The JITC point of contact is Mr. Edward Mellon, DSN 879-5159, commercial (520) 538-5159, FAX DSN 879-4347, or e-mail to [Edward.Mellon@disa.mil](mailto:Edward.Mellon@disa.mil). The JITC’s mailing address is P.O. Box 12798, Fort Huachuca, AZ 85670-2798. The Tracking Number for the SUT is 0904207.

FOR THE COMMANDER:

2 Enclosures a/s

  
 for RICHARD A. MEADOR  
 Chief  
 Battlespace Communications Portfolio

JITC Memo, JTE, Special Interoperability Test Certification of the Extreme Summit X350 Series with Release 12.3.1

Distribution (electronic mail):

Joint Staff J-6

Joint Interoperability Test Command, Liaison, TE3/JT1

Office of Chief of Naval Operations, CNO N6F2

Headquarters U.S. Air Force, Office of Warfighting Integration & CIO, AF/XCIN (A6N)

Department of the Army, Office of the Secretary of the Army, DA-OSA CIO/G-6 ASA (ALT), SAIS-IOQ

U.S. Marine Corps MARCORSSYSCOM, SIAT, MJI Division I

DOT&E, Net-Centric Systems and Naval Warfare

U.S. Coast Guard, CG-64

Defense Intelligence Agency

National Security Agency, DT

Defense Information Systems Agency, TEMC

Office of Assistant Secretary of Defense (NII)/DOD CIO

U.S. Joint Forces Command, Net-Centric Integration, Communication, and Capabilities Division, J68

Defense Information Systems Agency, GS23

## **ADDITIONAL REFERENCES**

- (c) Office of the Assistant Secretary of Defense, "Department of Defense Unified Capabilities Requirements 2008 Change 1," 22 January 2010
- (d) Joint Interoperability Test Command, "Defense Switched Network Generic Switch Test Plan (GSTP), Change 2," 2 October 2006
- (e) Joint Interoperability Test Command, "Information Assurance (IA) Assessment of Extreme's Summit X350-48T (Layer 2 Access only) (Tracking Number 0904207)," 4 March 2010

## CERTIFICATION TESTING SUMMARY

**1. SYSTEM TITLE.** Extreme Summit X350-48T with Release 12.3.1; hereinafter referred to as the system under test (SUT).


**2. PROPONENT.** Headquarters United States Army Information Systems Engineering Command (HQUSAISEC).

**3. PROGRAM MANAGER.** Gary Kitsmiller, AMSEL-IE-IS, Building 53301 Arizona Street, Fort Huachuca, Arizona, 85613-5300, e-mail: gary.kitsmiller@us.army.mil.

**4. TESTER.** Joint Interoperability Test Command (JITC), Fort Huachuca, Arizona.

**5. SYSTEM UNDER TEST DESCRIPTION.** The SUT is used to transport voice signaling and media as part of an overall Voice over Internet Protocol (VoIP) system. The SUT provides availability, security, and Quality of Service (QoS) to meet the operational requirements of the network and Assured Services for the warfighter. The SUT is certified as a layer 2 access switch and is interoperable for joint use with other Assured Services Local Area Network ASLAN components listed on the Unified Capabilities (UC) Approved Products List (APL) with the following interfaces: 1000 Base SX/LX and 10/100/1000 BaseT. The Extreme Summit Summit X350-48T was the system tested; however, the Extreme Summit X350-24t, X350-24t-TAA, and X350-48t-TAA employ the same software and similar hardware as the SUT. The JITC analysis determined these systems to be functionally identical to the SUT for interoperability certification purposes.

**6. OPERATIONAL ARCHITECTURE.** The Defense Switched Network (DSN) architecture is a two-level network hierarchy consisting of DSN backbone switches and Service/Agency installation switches. Service/Agency installation switches have been authorized to extend voice services over Internet Protocol (IP) infrastructures. The Unified Capabilities Requirements (UCR) operational DSN Architecture is depicted in Figure 2-1, which depicts the relationship of the ASLAN and non-ASLAN to the DSN switch types.



**LEGEND:**

- |       |                                     |         |   |
|-------|-------------------------------------|---------|---|
| 4W    | 4-Wire                              | NATO    | North Atlantic Treaty Organization          |
| ASLAN | Assured Services Local Area Network | PBX     | Private Branch Exchange                     |
| BRI   | Basic Rate Interface                | PBX 1   | Private Branch Exchange 1                   |
| CB    | Channel Bank                        | PBX 2   | Private Branch Exchange 2                   |
| COI   | Community of Interest               | PC      | Personal Computer                           |
| CSN   | Canadian Switch Network             | PSTN    | Public Switched Telephone Network           |
| DRSN  | Defense Red Switch Network          | RSU     | Remote Switching Unit                       |
| DSN   | Defense Switched Network            | SMEO    | Small End Office                            |
| DVX   | Deployable Voice Exchange           | SMU     | Switched Multiplex Unit                     |
| EMSS  | Enhanced Mobile Satellite System    | STEP    | Standardized Tactical Entry Point           |
| EO    | End Office                          | TDM/P   | Time Division Multiplex/Packetized          |
| IAS   | Integrated Access Switch            | Tri-Tac | Tri-Service Tactical Communications Program |
| IP    | Internet Protocol                   | TS      | Tandem Switch                               |
| ISDN  | Integrated Services Digital Network | VoIP    | Voice over Internet Protocol                |
| IST   | Interswitch Trunk                   | VTC     | Video Teleconferencing                      |
| MFS   | Multifunction Switch                | SUT     | System Under Test                           |

**Figure 2-1. DSN Architecture**

**7. REQUIRED SYSTEM INTERFACES.** The SUT capability and functional requirements are listed in Table 2-1. These requirements are derived from the UCR 2008, Change 1, and verified through JITC testing and review of the vendor’s Letters of Compliance (LoC).


**Table 2-1. SUT Capability and Functional Requirements**

ID	Requirement (See note.)		UCR Reference
1	ASLAN components can have no single point of failure for >96 users for C2 and Special C2 users. Non-ASLAN components can have a single point of failure for C2(R) and non-C2 users. (R)		5.3.1.2.1, 5.3.1.7.7
2	Non-blocking of any voice or video traffic at 50%. (R)		5.3.1.3
3	Maximum of 1 ms of jitter for all ASLAN components. (R)		5.3.1.3
4	Maximum of 0.02% packet loss for core and distribution layer components and 0.01% for access layer components. (R)		5.3.1.3
5	Maximum of 2 ms latency for core and distribution layer components and 2 ms for access layer components. (R)		5.3.1.3
6	100 Mbps IAW IEEE 802.3u and 1 Gbps IAW IEEE 802.3z for core and distribution Layer components and 10 Mbps IAW IEEE 802.3i and 100 Mbps IAW IEEE 802.3u for access layer components. (R)		5.3.1.3.1
7	Force mode and auto-negotiation IAW IEEE 802.3, filtering IAW RFC 1812, and flow control IAW IEEE 802.3x. (R)		5.3.1.3.2
8	Port Parameter Requirements	Auto-negotiation IAW IEEE 802.3. (R)	5.3.1.3.2
9		Force mode IAW IEEE 802.3. (R)	
10		Flow control IAW IEEE 802.3x. (R)	
11		Filtering IAW RFC 1812. (R)	
12		Link Aggregation IAW IEEE 802.3ad (output/egress ports only). (R)	
13		Spanning Tree Protocol IAW IEEE 802.1D. (R)	
14		Multiple Spanning Tree IAW IEEE 802.1s. (R)	
15	Rapid Reconfiguration of Spanning Tree IAW IEEE 802.1w. (R)		
16	LACP link Failover and Link Aggregation IAW IEEE 802.3ad uplink ports only). (R)		5.3.1.3.2, 5.3.1.7.7.1
17	Class of Service Marking: Layer 3 DSCPs IAW RFC 2474. (R) Layer 2 3-bit user priority field of the IEEE 802.1Q 2-byte TCI field. (C)		5.3.1.3.3
18	VLAN Capabilities IAW IEEE 802.1Q. (R)		5.3.1.3.4
19	Protocols IAW DISR profile (IPv4 and IPv6). IPv4 (R: LAN Switch, Layer 2 Switch): IPv6 (R: LAN Switch, C: Layer 2 Switch). Note: Layer 2 switch is required to support only RFC 2460, 5095, 2464, and be able to queue packets based on DSCPs in accordance with RFC 2474.		5.3.1.3.5
20	QoS Features	Shall support minimum of 4 queues. (R)	5.3.1.3.6
21		Must be able to assign VLAN tagged packets to a queue. (R)	
22		Support DSCP PHBs per RFCs 2474, 2494, 2597, 2598, and 3246. (R: LAN Switch). Note: Layer 2 switch is required to support RFC 2474 only.	
23		Support a minimum of one of the following: Weighted Fair Queuing (WFQ) IAW RFC 3662, Priority Queuing (PQ) IAW RFC 1046, or Class-Based WFQ IAW RFC 3366. (R)	
24	Must be able to assign a bandwidth or percent of traffic to any queue. (R)		
25	Network Monitoring	SNMP IAW RFC’s 1157, 2206, 3410, 3411, 3412, 3413 and 3414. (R)	5.3.1.3.7
26		SNMP traps IAW RFC1215. (R)	
27	Remote monitoring IAW RFC1281 and Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model IAW RFC 3826. (R)		
28	Product Requirements Summary IAW UCR2008 Table 5.3.1-5. (R)		5.3.1.3.9
29	E2E Performance (Voice)	No more than 5 ms Latency over any 5-minute period measured under congestion. (R)	5.3.1.4.1
		No more than 3 ms Jitter over any 5-minute period measured under congestion. (R)	
30	E2E Performance (Video)	Packet loss not to exceed engineered (queuing) parameters over any 5-minute period under congestion. (R)	5.3.1.4.2
		No more than 30 ms Latency over any 5-minute period measured under congestion. (R)	
		No more than 30 ms Jitter over any 5-minute period measured under congestion. (R)	
31	E2E Performance (Data)	Packet loss not to exceed engineered (queuing) parameters over any 5-minute period under congestion. (R)	5.3.1.4.3
		No more than 50 ms Latency over any 5-minute period measured under congestion	


**Table 2-1. SUT Capability and Functional Requirements (continued)**

ID	Requirement (See note.)		UCR Reference																																																																								
32	LAN Network Management	Configuration Control for ASLAN and Non-ASLAN. (R)	5.3.1.6.1																																																																								
33		Operational Controls for ASLAN and Non-ASLAN. (R)	5.3.1.6.2																																																																								
34		Performance Monitoring for ASLAN and Non-ASLAN. (R)	5.3.1.6.3																																																																								
35		Alarms for ASLAN and Non-ASLAN. (R)	5.3.1.6.4																																																																								
36		Reporting for ASLAN and Non-ASLAN. (R)	5.3.1.6.5																																																																								
37	Redundancy	Redundant Power Supplies. (Required on standalone redundant products.)	5.3.1.7.7																																																																								
38		Chassis Failover. (Required on standalone redundant products.)																																																																									
39		Switch Fabric Failover. (Required on standalone redundant products.)																																																																									
40		Non-LACP Link Failover.(R)																																																																									
41		Fiber Blade Failover. (R)																																																																									
42		Stack Failover. (C) (Required if the stack supports more than 96 users.)																																																																									
43		CPU (routing engine) blade Failover. (R)																																																																									
49	Support IPv6 packets over Ethernet IAW RFC2464. (R)		5.3.5.4																																																																								
76	Site Requirements	Engineering Requirements: Physical Media for ASLAN and Non-ASLAN. (R) (Site requirement)	5.3.1.7.1																																																																								
77		Battery Back up two hours for non-ASLAN components and eight hours for ASLAN components. (R) (Site requirement)	5.3.1.7.5																																																																								
78		Availability of 99.999 percent (Special C2), and 99.997 percent (C2) for ASLAN (R), and 99.9 percent (non-C2 and C2(R) for non-ASLAN. (R) (Site requirement)	5.3.1.7.6																																																																								
79	IA Security requirements	Port-Based Access Control IAW IEEE 802.1x (R)	5.3.1.3.2																																																																								
80		Secure methods for network configuration. SSH2 instead of Telnet and support RFCs 4251-4254. Must use HTTPS instead of http, and support RFCs 2660 and 2818 for ASLAN and Non-ASLAN. (R)	5.3.1.6																																																																								
81		Security (R)		5.3.1.3.8																																																																							
82		Must meet IA requirements IAW UCR 2008 Section 5.4 for ASLAN and non-ASLAN. (R)		5.3.1.5																																																																							
<p><b>NOTE:</b> All requirements are for core, distribution, and access layer components unless otherwise specified.</p> <p><b>LEGEND:</b></p> <table> <tr> <td>ASLAN</td> <td>Assured Services Local Area Network</td> <td>HTTP</td> <td>Hypertext Transfer Protocol</td> <td>MPLS</td> <td>Multiprotocol Label Switching</td> </tr> <tr> <td>C</td> <td>Conditional</td> <td>HTTPS</td> <td>Hyper Text Transfer Protocol, Secure</td> <td>ms</td> <td>millisecond</td> </tr> <tr> <td>C2</td> <td>Command and Control</td> <td>IA</td> <td>Information Assurance</td> <td>PHB</td> <td>Per Hop Behavior</td> </tr> <tr> <td>C2(R)</td> <td>Command and Control ROUTINE only</td> <td>IAW</td> <td>In Accordance with</td> <td>QoS</td> <td>Quality of Service</td> </tr> <tr> <td>CPU</td> <td>Central Processing Unit</td> <td>ID</td> <td>Identification</td> <td>R</td> <td>Required</td> </tr> <tr> <td>DISR</td> <td>Department of Defense Information Technology Standards Registry</td> <td>IEEE</td> <td>Institute of Electrical and Electronics Engineers</td> <td>RFC</td> <td>Request for Comments</td> </tr> <tr> <td>DSCP</td> <td>Differentiated Services Code Point</td> <td>IPv4</td> <td>Internet Protocol version 4</td> <td>SNMP</td> <td>Simple Network Management Protocol</td> </tr> <tr> <td>E2E</td> <td>End-to-End</td> <td>IPv6</td> <td>Internet Protocol version 6</td> <td>SSH2</td> <td>Secure Shell Version 2</td> </tr> <tr> <td>Gbps</td> <td>Gigabits per second</td> <td>LACP</td> <td>Link Aggregation Control Protocol</td> <td>SUT</td> <td>System Under Test</td> </tr> <tr> <td></td> <td></td> <td>LAN</td> <td>Local Area Network</td> <td>TCI</td> <td>Tag Control Information</td> </tr> <tr> <td></td> <td></td> <td>Mbps</td> <td>Megabits per second</td> <td>UCR</td> <td>Unified Capabilities Requirements</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>VLAN</td> <td>Virtual Local Area Network</td> </tr> </table>				ASLAN	Assured Services Local Area Network	HTTP	Hypertext Transfer Protocol	MPLS	Multiprotocol Label Switching	C	Conditional	HTTPS	Hyper Text Transfer Protocol, Secure	ms	millisecond	C2	Command and Control	IA	Information Assurance	PHB	Per Hop Behavior	C2(R)	Command and Control ROUTINE only	IAW	In Accordance with	QoS	Quality of Service	CPU	Central Processing Unit	ID	Identification	R	Required	DISR	Department of Defense Information Technology Standards Registry	IEEE	Institute of Electrical and Electronics Engineers	RFC	Request for Comments	DSCP	Differentiated Services Code Point	IPv4	Internet Protocol version 4	SNMP	Simple Network Management Protocol	E2E	End-to-End	IPv6	Internet Protocol version 6	SSH2	Secure Shell Version 2	Gbps	Gigabits per second	LACP	Link Aggregation Control Protocol	SUT	System Under Test			LAN	Local Area Network	TCI	Tag Control Information			Mbps	Megabits per second	UCR	Unified Capabilities Requirements					VLAN	Virtual Local Area Network
ASLAN	Assured Services Local Area Network	HTTP	Hypertext Transfer Protocol	MPLS	Multiprotocol Label Switching																																																																						
C	Conditional	HTTPS	Hyper Text Transfer Protocol, Secure	ms	millisecond																																																																						
C2	Command and Control	IA	Information Assurance	PHB	Per Hop Behavior																																																																						
C2(R)	Command and Control ROUTINE only	IAW	In Accordance with	QoS	Quality of Service																																																																						
CPU	Central Processing Unit	ID	Identification	R	Required																																																																						
DISR	Department of Defense Information Technology Standards Registry	IEEE	Institute of Electrical and Electronics Engineers	RFC	Request for Comments																																																																						
DSCP	Differentiated Services Code Point	IPv4	Internet Protocol version 4	SNMP	Simple Network Management Protocol																																																																						
E2E	End-to-End	IPv6	Internet Protocol version 6	SSH2	Secure Shell Version 2																																																																						
Gbps	Gigabits per second	LACP	Link Aggregation Control Protocol	SUT	System Under Test																																																																						
		LAN	Local Area Network	TCI	Tag Control Information																																																																						
		Mbps	Megabits per second	UCR	Unified Capabilities Requirements																																																																						
				VLAN	Virtual Local Area Network																																																																						


**8. TEST NETWORK DESCRIPTION.** The SUT was tested at JITC's Global Information Grid Network Test Facility in a manner and configuration similar to that of the DSN operational environment. A notional diagram of the SUT within an ASLAN VoIP architecture is depicted in Figure 2-2 and the Notional non-ASLAN VoIP architecture is depicted in Figure 2-3. The notional ASLAN and non-ASLAN combined VoIP architecture is depicted in Figure 2-4. The ASLAN test configuration used to test the SUT in a homogeneous network is depicted in Figure 2-5, and the heterogeneous test network configurations are depicted in Figures 2-6 and 2-7.



**Figure 2-2. SUT Notional ASLAN VoIP Architecture**



**Figure 2-3. SUT Notional Non-ASLAN VoIP Architecture**



**Figure 2-4. SUT Notional ASLAN and non-ASLAN Combined VoIP Architecture**






Figure 2-5. SUT Homogenous Test Configuration



**Figure 2-6. SUT Heterogeneous Test Configuration with Cisco**



**Figure 2-7. SUT Heterogeneous Test Configuration with Brocade**

**9. SYSTEM CONFIGURATIONS.** Table 2-2 provides the system configurations, hardware, and software components tested with the SUT. The SUT is certified with other IP systems listed on the UC APL that are certified for use with an ASLAN or non-ASLAN.

**Table 2-2. Tested System Configuration**

System Name	Release
Extreme BlackDiamond 8806	12.3.1
Extreme BlackDiamond 8810	12.3.1
Extreme BlackDiamond 12804	12.3.1
Extreme Summit X650-24x	12.3.1
Extreme Summit X250e-48P	12.3.1
Extreme Summit X450e-24P	12.3.1

**Table 2-2. Tested System Configuration (continued)**

System Name		Release										
Extreme Summit X150-24P		12.3.1										
Brocade NetIron XMR-8000		4.0.06										
Brocade NetIron MLX-8		4.0.06										
Brocade BigIron RX-8		2.7.01										
Brocade FastIron SX-800		5.0.00										
Brocade FastIron Edge 4802-PoE		4.1.01										
Brocade FastIron GS-648P-PoE		4.3.02										
Brocade FastIron GS-648P-PoE		5.0.00										
Brocade FastIron FWS-648G-PoE		4.3.02										
Cisco 7609-S		IOS 12.2 (33) SRD										
Cisco 4900M		IOS 12.2 (50) SG										
Cisco WS-C3560E-12SD		IOS 12.2 (46) SE										
Component (See note.)	Release	Function	Sub-component	Description								
<b><u>Summit X350-48T</u></b> , X350-24t, X350-24t-TAA, X350-48t-TAA	12.3.1	Access	Not Applicable	24/48 10/100/1000BASE-T, 4 unpopulated mini-GBIC ports, option slot for 10 Gigabit option card XGM2-2xn/xf, 1 AC PSU, ExtremeXOS L2 Edge license, connector for EPS-500 external redundant PSU								
<p><b>NOTE:</b> Components bolded and underlined were tested by JITC. The other components in the family series were not tested; however, they utilize the same software and hardware and JITC analysis determined them to be functionally identical for interoperability certification purposes and they are also certified for joint use.</p> <p><b>LEGEND:</b></p> <table> <tr> <td>JITC</td> <td>Joint Interoperability Test Command</td> <td>SFP</td> <td>Small Form Factor Pluggable</td> </tr> <tr> <td>PSU</td> <td>Power Supply Unit</td> <td>SUT</td> <td>System Under Test</td> </tr> </table>					JITC	Joint Interoperability Test Command	SFP	Small Form Factor Pluggable	PSU	Power Supply Unit	SUT	System Under Test
JITC	Joint Interoperability Test Command	SFP	Small Form Factor Pluggable									
PSU	Power Supply Unit	SUT	System Under Test									

**10. TESTING LIMITATIONS.** None.

**11. TEST RESULTS**

**a. Discussion.** The SUT is certified to support DSN Assured Services over IP. If a component meets the minimum requirements for deployment in an ASLAN, it also meets the lesser requirements for deployment in a non-ASLAN. Non-ASLANs are “commercial grade” and provide support to Command and Control (C2) (ROUTINE only calls) (C2(R)) or non-C2 voice subscribers. The SUT is certified for joint use deployment in a non-ASLAN for C2R and non-C2 traffic. When deployed in a non-ASLAN, the SUT may also be used to receive all levels of precedence, but are limited to originating ROUTINE precedence only. Non-ASLANs do not need to meet the availability or redundancy requirements of the C2 or Special C2 users and they are not authorized as subscribers on a non-ASLAN.

**b. Test Conduct.** The SUT was tested as a layer 2 access switch in both homogeneous and heterogeneous ASLAN configurations and met all of the requirements with testing and/or the vendor’s LoC as outlined in the sub paragraphs below.

(1) The UCR 2008, Change 1, paragraphs 5.3.1.2.1, 5.3.1.7.7, 5.3.1.7.7.1, 5.3.1.7.7.2, state that ASLAN components can have no single point of failure for more than 96 users for C2 and Special C2 users. The UCR 2008, Change 1, paragraph 5.3.1.7.7, states the following Redundancy requirements. Redundancy can be met if the product itself provides redundancy internally or a secondary product is added to the ASLAN to provide redundancy to the primary product. Single-product redundancy may be met with a modular chassis that at a minimum provides the following: dual power supplies, dual processors, termination sparing, redundancy protocol, no single point of failure, and switch fabric or backplane redundancy. In the event of a component failure in the network, all calls that are active shall not be disrupted (loss of existing connection requiring redialing) and the path through the network shall be restored within five seconds. If a secondary product has been added to provide redundancy to a primary product, the failover to the secondary product must not result in any lost calls. In the event of a primary product failure, all calls that are active shall not be disrupted and the failover to the secondary product must be restored within five seconds. Non-ASLAN components can have a single point of failure for C2(R) and non-C2 users. The SUT met all of these requirements. The SUT was equipped with redundant uplinks, processors, and power supplies. All of the redundant components were tested and found to meet all the failover and access requirements with a measured restoral within 2.0 seconds with no loss of existing active circuits.

(2) The UCR 2008, Change 1, paragraph 5.3.1.3, states that the ASLAN infrastructure components shall meet the requirements in the subparagraphs below. The SUT was tested using 155 percent oversubscription of the total aggregate uplink bandwidth for 1 Gbps. This included 100 percent of uplink aggregate in untagged best effort data, and 55 percent of uplink aggregate in tagged Internet Protocol version 4 (IPv4) and Internet Protocol version 6 (IPv6) voice, video, and preferred data traffic.

(a) The SUT shall be non-blocking for a minimum of 50 percent (maximum voice and video traffic) of its maximum rated output capacity for egress ports that interconnect (trunk) the product to other products. Non-blocking is defined as the capability to send and receive 64 to 1518 byte packets at full duplex rates from ingress ports to egress ports without losing any packets. The SUT met this requirement by insuring that higher priority tagged traffic was queued above lower priority tagged traffic and untagged best effort data.

(b) The SUT shall have the capability to transport prioritized voice packets (media and signaling) with no more than 1 millisecond (ms) jitter across all switches. All ASLAN infrastructure components shall have the capability to transport prioritized video packets (media and signaling) with no more than 10 ms jitter across all switches. The jitter shall be achievable over any five-minute period measured from ingress ports to egress ports under congested conditions. The SUT met this requirement with a measured jitter of 0 ms for voice and video packets.

(c) All access products shall have the capability to transport prioritized voice and video packets (media and signaling) with no more than 0.01 percent packet loss. The packet loss shall be achievable over any five-minute period measured from ingress ports to egress ports under congested conditions. The SUT met this requirement with a measured packet loss of 0.00 percent for voice and video packets.

(d) The SUT shall have the capability to transport prioritized voice packets (media and signaling), with no more than 2 ms latency. All ASLAN infrastructure components shall have the capability to transport prioritized video packets (media and signaling), with no more than 10 ms latency. The latency shall be achievable over any five-minute period measured from ingress ports to egress ports under congested conditions. The SUT met this requirement with measured latency of .33 ms to .53 with an average of .43 ms of latency for voice and video packets.

(3) The UCR 2008, Change 1, paragraph 5.3.1.3.1, states that, at a minimum, access products shall provide the following interface rates and other rates may be provided as conditional interfaces: 10 Mbps in accordance with IEEE 802.3i and 100 Mbps in accordance with IEEE 802.3u. Refer to Table 2-3 for a detailed list of interfaces that were tested. The SUT met these requirements.

**Table 2-3. SUT Interface Status**

Interface	Applicability	CRs/FRs (See note 1.)	Status
	Access		Access
<b>Network Management Interfaces for Layer 2 Access Switches</b>			
EIA/TIA (Serial) 232	R	EIA/TIA-232	Met
IEEE 802.3i (10BaseT UTP)	C	1, 6-15, 18-28, 31, 32-36, 49	Not Tested <sup>2</sup>
IEEE 802.3u (100BaseT UTP)	C	1, 6-15, 18-28, 31, 32-36, 49	Met
IEEE 802.3ab (1000BaseT UTP)	C	1, 6-15, 18-28, 31, 32-36, 49	Met
<b>Uplink Interfaces for Layer 2 Access Switches</b>			
IEEE 802.3u (100BaseT UTP)	R	1-15, 16, 18-24, 28-31, 40, 49	Met
IEEE 802.3u (100BaseFX)	C	1-6, 11, 16, 18-24, 28-31, 40-41, 49	Met
IEEE 802.3ab (1000BaseT UTP)	C	1-16, 18-24, 28-31, 40, 49	Met
IEEE 802.3z1000BaseX Fiber	C	1-5, 8-16, 18-24, 28-31, 40, 49	Met
IEEE 802.3ae (10GBaseX)	C	1-5, 8-16, 18, 19, 40-41, 49	Not Tested <sup>2</sup>
<b>Access Interfaces for Layer 2 Access Switches</b>			
IEEE 802.3i (10BASET UTP)	R	1-15, 18-24, 28-41, 49	Met
IEEE 802.3u (100BaseT UTP)	R	1-15, 18-24, 28-41, 49	Met
IEEE 802.3u (100BaseFX)	C	1-6, 11, 18-24, 28-31, 49	Met
IEEE 802.3ab (1000BaseT UTP)	C	1-15, 18-24, 28-41, 49	Met
IEEE 802.3z (1000BaseX Fiber)	C	1-6, 11, 18-24, 28-31, 49	Met
<b>Generic Requirements for all Interfaces</b>			
Generic Requirements not associated with specific interfaces	R	30-32, 35, 36, 40, 69-71	Met
DoD IPv6 Profile Requirements	R	UCR Section 5.3.5.5 (See note 3.)	Met
Security	R	UCR Sections 5.3.1.3.8, 5.3.1.5, 5.3.1.6, and 5.4 (See note 4.)	Met

**Table 2-3. SUT Interface Status (continued)**

<b>NOTES:</b>			
1	The SUT's specific capability and functional requirement ID numbers depicted in the CRs/FRs column can be cross-referenced in Table 2-1. These requirements are for the following Extreme Summit switch models, which are certified in the Layer 2 access layer: <b><u>Summit X350-48T</u></b> , X350-24t, X350-24t-TAA, and X350-48t-TAA. The JITC tested the devices that are bolded and underlined. The other devices listed that are not bolded or underlined are in the same family series as the SUT were not tested; however, they utilize the same OS software and hardware and JITC analysis determined them to be functionally identical for interoperability certification purposes.		
2	This interface is not offered by the SUT, and is not a required interface.		
3	IPv6 requirements are met by both testing and a vendor letter of compliance.		
4	Security testing is accomplished via DISA-led Information Assurance test teams and published in a separate report, Reference (e).		
<b>LEGEND:</b>			
802.3ab	1000BaseT Gbps Ethernet over twisted pair at 1 Gbps (125 Mbps)	EIA-232	Standard for defining the mechanical and electrical characteristics for connecting Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) data communications devices
802.3ae	10 Gbps Ethernet		
802.3i	10BaseT Mbps over twisted pair		
802.3u	Standard for carrier sense multiple access with collision detection at 100 Mbps	FRs	Functional Requirements
802.3z	Gigabit Ethernet Standard	Gbps	Gigabits per second
1000BaseFX	1000 Mbps Ethernet over fiber	ID	Identification
1000BaseT	1000 Mbps (Baseband Operation, Twisted Pair) Ethernet	IEEE	Institute of Electrical and Electronics Engineers
		IPv6	Internet Protocol version 6
		JITC	Joint Interoperability Test Command
ASLAN	Assured Services Local Area Network	Mbps	Megabits per second
C	Conditional	OS	Operating System
CRs	Capability Requirements	R	Required
DISA	Defense Information Systems Agency	SUT	System Under Test
EIA	Electronic Industries Alliance	TIA	Telecommunications Industry Association
		UTP	Unshielded Twisted Pair

(4) The UCR 2008, Change 1, paragraph 5.3.1.3.2, states that the ASLAN infrastructure components shall provide the following parameters on a per port basis: auto-negotiation, force mode, flow control, filtering, link aggregation, spanning tree protocol, multiple spanning tree, rapid reconfiguration of spanning tree, and port-based access control. The SUT was tested with a series of forced port speeds as well as auto-negotiation. Link failover testing was performed which confirmed spanning tree convergence. All these requirements were met by both testing and vendors LoC.

(5) The UCR 2008, Change 1, paragraph 5.3.1.3.3, states that the ASLAN infrastructure components shall support Differentiated Services Code Points (DSCP) in accordance with Request for Comment (RFC) 2474 as stated in the subparagraphs below:

(a) The ASLAN infrastructure components shall be capable of accepting any packet tagged with a DSCP value (0-63) on an ingress port and assign that packet to a QoS behavior listed in Section 5.3.1.3.6. The SUT prioritized the following traffic for queuing from lowest to highest with distinct IPv4 DSCP tags using an IP loader: Data best effort, preferred data, video media and signaling, and voice media and signaling. The IP load included a data best effort load of 100 percent line rate and the other traffic at 55 percent of line rate (25 percent of video signaling, voice signaling, and voice media in the highest priority queue, and 25 percent of video media in the next lower

priority queue, and 5 percent of preferred data in the lowest priority queue). The IP loader recorded that the higher prioritized traffic was properly queued by the SUT above lower prioritized best effort traffic. In addition, it was verified that the SUT can assign any DSCP value from 0-63 for each type of traffic, which met this requirement.

(b) The ASLAN infrastructure components shall be capable of accepting any packet tagged with a DSCP value (0-63) on an ingress port and reassign that packet to any new DSCP value (0-63). Current DSCP values are provided in Section 5.3.3.3.2. The SUT met this requirement through vendors LoC.

(c) The ASLAN infrastructure components must be able to support the prioritization of aggregate service classes with queuing according to Section 5.3.1.3.6. The SUT prioritized the following traffic for queuing from lowest to highest with distinct IPv6 service class tags using an IP loader: Data best effort, preferred data, video media and signaling, and voice media and signaling. The IP load included a data best effort load of 100 percent line rate and the other traffic at 55 percent of line rate (25 percent of video signaling, voice signaling, and voice media in the highest priority queue, and 25 percent of video media in the next lower priority queue, and 5 percent of preferred data in the lowest priority queue). The IP loader recorded that the higher prioritized traffic was properly queued by the SUT above lower prioritized best effort traffic. In addition it was verified that the SUT can assign any IPv6 traffic class value from 0-63 for each type of traffic which met this requirement.

(d) The ASLAN infrastructure components may support the 3-bit user priority field of the IEEE 802.1Q 2-byte Tag Control Information (TCI) field. Default values are provided in Table 5.3.1-4. If provided, the following Class of Service (CoS) requirements apply: The ASLAN infrastructure components shall be capable of accepting any frame tagged with a user priority value (0-7) on an ingress port and assign that frame to a QoS behavior listed in Section 5.3.1.3.6. The ASLAN infrastructure components shall be capable of accepting any frame tagged with a user priority value (0-7) on an ingress port and reassign that frame to any new user priority value (0-7). The SUT met this requirement with a vendor LoC.

(6) The UCR 2008, Change 1, paragraph 5.3.1.3.4, states that the ASLAN infrastructure components shall be capable of the Virtual LAN (VLAN) capabilities in accordance with IEEE 802.1Q. The SUT was configured with a preset VLAN ID tag using the IP loader. This load was captured at the egress and ingress to insure that the SUT was properly assigning the VLAN ID in the proper VLAN and not modifying or misplacing the assigned VLAN traffic in any way. In addition, the SUT has the ability to assign any VLAN ID any value from 0 through 4096. The SUT met this requirement with both testing and vendor LoC.

(7) The UCR 2008, Change 1, paragraph 5.3.1.3.5, states that the ASLAN infrastructure components shall meet the Department of Defense Information Technology Standards Registry (DISR) protocol requirements for IPv4 and IPv6. The

SUT prioritized the following traffic for queuing from lowest to highest with distinct IPv4 DSCP tags and IPv6 service class tags using an IP loader: Data best effort, preferred data, video media and signaling, and voice media and signaling. The IP load included a data best effort load of 100 percent line rate and the other traffic at 55 percent of line rate (25 percent of video signaling, voice signaling, and voice media in the highest priority queue, and 25 percent of video media in the next lower priority queue, and 5 percent of preferred data in the lowest priority queue). The IP loader recorded that the higher prioritized traffic was properly queued by the SUT above lower prioritized best effort traffic. It was verified that the SUT can assign any IPv4 DSCP or IPv6 traffic class value from 0-63 for each type of traffic which met this requirement. The IPv6 RFC DISR profile requirements were also met by the vendor's LoC.

(8) The UCR 2008, Change 1, paragraph 5.3.1.3.6, states that the ASLAN infrastructure components shall be capable of providing the following QoS features:

(a) Provide a minimum of four queues. The SUT has the ability to support up to eight assignable queues; however, only a four-queue model was tested and is covered under this certification.

(b) Assign a DSCP or Traffic Class value to any of the queues. The SUT met this requirement through testing and the vendor's LoC.

(c) Support Differentiated Services (DiffServ) per hop behaviors (PHBs) in accordance with RFCs 2472, 2494, 2597, 2598, and 3246. The SUT met this requirement through testing and the vendor's LoC.

(d) Support, at a minimum, one of the following: Weighted Fair Queuing (WFQ) in accordance with RFC 3662, Priority Queuing (PQ) in accordance with RFC 1046, or Class-Based WFQ in accordance with RFC 3366. The SUT supports all three types of queuing. WFQ and PQ queuing types were met through testing and Class-Based WFQ was met with the vendor's LoC.

(e) All queues shall be capable of having bandwidth assigned or percentage of traffic. The SUT prioritized the following traffic for queuing from lowest to highest with distinct IPv4 DSCP tags and IPv6 service class tags using an IP loader: Data best effort, preferred data, video media and signaling, and voice media and signaling. The IP load included a data best effort load of 100 percent line rate and the other traffic at 55 percent of line rate (25 percent of video signaling, voice signaling, and voice media in the highest priority queue, and 25 percent of video media in the next lower priority queue, and 5 percent of preferred data in the lowest priority queue). The IP loader recorded that the higher prioritized traffic was properly queued by the SUT above lower prioritized best effort traffic at the assigned bandwidth per queue. Subsequently, the IP loader was reconfigured to increase the video traffic to 35 percent of line rate to ensure the SUT only allowed 25 percent throughput of the video traffic. The captured video throughput measured by the IP loader was 24.999 percent of the

line rate, which met this requirement. In addition to testing, this requirement was met by the vendor's LoC.

(9) The UCR 2008, Change 1, paragraph 5.3.1.3.7, states that the ASLAN infrastructure components shall be capable of providing the following Network Monitoring features:

(a) Simple Network Management Protocol (SNMP) in accordance with RFCs 1157, 2206, 3410, 3411, 3412, 3413, and 3414. Testing of this requirement was met using an SNMP management tool, which was used to verify SNMP SETS, GETS, and TRAPS. In addition, the SUT met this requirement through the vendor's LoC.

(b) SNMP Traps in accordance with RFC 1215. The SUT met this requirement through testing and the vendor's LoC.

(c) Remote Monitoring (RMON) in accordance with RFC 2819. The SUT met this requirement with the vendor's LoC.

(d) Coexistence between Version 1, Version 2, and Version 3 of the Internet-standard Network Management Framework in accordance with RFC 3584. The SUT met this requirement with the vendor's LoC.

(e) The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model in accordance with RFC 3826. Security is tested by DISA-led Information Assurance test teams and published in a separate report, Reference (e).

(10) The UCR 2008, Change 1, paragraph 5.3.1.3.9, states that all switches meet Product Requirements in accordance with UCR 2008, Change 1, Table 5.3.1-5. The SUT met these requirements listed in Table 5.3.1-5 as stipulated throughout this document by testing and/or vendor LoC.

(11) The UCR 2008, Change 1, section 5.3.1.4, states that the ASLAN infrastructure components shall be capable of meeting the End-to-End (E2E) performance requirements for voice, video, and data services. The E2E performance across a LAN is measured from the traffic ingress point to the traffic egress port. The requirements are measured over any five-minute period under congested conditions. Congested condition is defined as 100 percent of link capacities (as defined by baseline traffic engineering (25 percent voice/signaling, 25 percent video, 25 percent preferred data, and 25 percent best effort traffic). The E2E requirements are ASLAN requirements. However, all of the E2E voice, video, and data services performance requirements were met by the SUT when included within an ASLAN. Refer to paragraphs 11.b.(2)(b), 11.b.(2)(c), and 11.b.(2)(d).

(12) The UCR 2008, Change 1, section 5.3.1.6, states that LAN infrastructure components must meet the requirements in the subparagraphs below. Near Real Time (NRT) is defined as within five seconds of detecting the event, excluding transport time.

(a) LANs shall have the ability to perform remote network product configuration/reconfiguration of objects that have existing DoD GIG management capabilities. The NMS shall report configuration change events in NRT, whether or not the change was authorized. The system shall report the success or failure of authorized configuration change attempts in NRT. The SUT met this requirement by responding in NRT of less than 1 second.

(b) LAN infrastructure components must provide metrics to the NMS to allow them to make decisions on managing the network. Network management systems shall have an automated NM capability to obtain the status of networks and associated assets in NRT 99 percent of the time (with 99.9 percent as an Objective Requirement). Specific metrics are defined in UCR 2008, Change 1, Sections 5.3.2.17 and 5.3.2.18. The SUT met this requirement by responding in NRT of less than 1 second 100 percent of the time.

(c) LAN components shall be capable of providing status changes 99 percent of the time (with 99.9 percent as an Objective Requirement) by means of an automated capability in NRT. An NMS will have an automated NM capability to obtain the status of networks and associated assets 99 percent of the time (with 99.9 percent as an Objective Requirement) in NRT. The NMS shall collect statistics and monitor bandwidth utilization, delay, jitter, and packet loss. The SUT met this requirement by responding in NRT of less than 1 second 100 percent of the time.

(d) LAN components shall be capable of providing SNMP alarm indications to an NMS. The NMSs will have the NM capability to perform automated fault management of the network, to include problem detection, fault correction, fault isolation and diagnosis, problem tracking until corrective actions are completed, and historical archiving. Alarms will be correlated to eliminate those that are duplicate or false, initiate test, and perform diagnostics to isolate faults to a replaceable component. Alarms shall be reported as TRAPs via SNMP in NRT. More than 99.95 percent of alarms shall be reported in NRT. The SUT met this requirement by responding in NRT of less than 1 second 100 percent of the time using an over the counter SNMP tool.

(e) An NMS will have the NM capability of automatically generating and providing an integrated/ correlated presentation of network and all associated networks. The SUT met this requirement with the vendor's LoC.

(13) The UCR 2008, Change 1, paragraph 5.3.5.4, states that layer 2 switches must support IPv6 packets over Ethernet in accordance with RFC2464. The SUT met this requirement with both testing and the vendor LoC.

(14) The UCR 2008, Change 1, paragraphs 5.3.1.3.8, 5.3.1.5, 5.3.1.6, state that ASLAN components must meet security requirements. Security is tested by DISA-led Information Assurance test teams and published in a separate report, Reference (e).

**c. System Interoperability Results.** The SUT is certified for joint use within the DSN as layer 2 access switch. It is also certified with any digital switching systems listed on the UC APL which are certified for use with an ASLAN or non-ASLAN. The SUT is certified to support DSN Assured Services over IP as an ASLAN in accordance with the requirements set forth in the UCR. If a system meets the minimum requirements for an ASLAN, it also meets the lesser requirements for a non-ASLAN. Non-ASLANs are “commercial grade” and provide support to C2R or non-C2 voice subscribers. The SUT is certified for joint use as a non-ASLAN for C2R and non-C2 traffic. Non-ASLANs may provide MLPP to users authorized to originate only ROUTINE precedence calls but terminate all precedence levels. Non-ASLANs do not need to meet the availability or redundancy requirements of the Special C2 users or the C2 users capable of originating precedence calls above ROUTINE. Since non-ASLANs are not required to support the reliability requirements detailed in the UCR for ASLANs, C2 users and Special C2 users are not authorized to be served by a non-ASLAN.

**12. TEST AND ANALYSIS REPORT.** No detailed test report was developed in accordance with the Program Manager’s request. JITC distributes interoperability information via the JITC Electronic Report Distribution (ERD) system, which uses Unclassified-But-Sensitive Internet Protocol Router Network (NIPRNet) e-mail. More comprehensive interoperability status information is available via the JITC System Tracking Program (STP). The STP is accessible by .mil/gov users on the NIPRNet at <https://stp.fhu.disa.mil>. Test reports, lessons learned, and related testing documents and references are on the JITC Joint Interoperability Tool (JIT) at <http://jit.fhu.disa.mil> (NIPRNet), or <http://199.208.204.125> (SIPRNet). Information related to DSN testing is on the Telecom Switched Services Interoperability (TSSI) website at <http://jitic.fhu.disa.mil/tssi>. Due to the sensitivity of the information, the Information Assurance Accreditation Package (IAAP) that contains the approved configuration and deployment guide must be requested directly through government civilian or uniformed military personnel from the Unified Capabilities Certification Office (UCCO), e-mail: [ucco@disa.mil](mailto:ucco@disa.mil).