



## DEFENSE INFORMATION SYSTEMS AGENCY

P. O. BOX 549  
FORT MEADE, MARYLAND 20755-0549

IN REPLY  
REFER TO: Joint Interoperability Test Command (JITE)

### MEMORANDUM FOR DISTRIBUTION

**10 Mar 11**

**SUBJECT:** Extension of the Special Interoperability Test Certification of the Fujitsu FLASHWAVE 4500 with Software Release 8.2

**References:** (a) DoD Directive 4630.05, "Interoperability and Supportability of Information Technology (IT) and National Security Systems (NSS)," 5 May 2004  
(b) CJCSI 6212.01E, "Interoperability and Supportability of Information Technology and National Security Systems," 15 December 2008  
(c) through (f), see Enclosure

1. References (a) and (b) establish the Defense Information Systems Agency (DISA), Joint Interoperability Test Command (JITC), as the responsible organization for interoperability test certification.
2. The Fujitsu FLASHWAVE 4500 with Software Release 8.2 is hereinafter referred to as the System Under Test (SUT). The SUT meets all of the critical interoperability requirements for the Defense Switched Network (DSN) and is certified for joint use. The SUT met the critical interoperability requirements for a Strategic Network Element set forth in appendices 5 and 9 of Reference (c) using test procedures derived from Reference (d). Although the SUT offers European Basic Multiplex Rate (E1) access interfaces, these interfaces were not tested by JITC and are not covered under this certification. No other configurations, features, or functions, except those cited within this report, are certified by the JITC. This certification expires upon changes that affect interoperability, but no later than three years from the date of the original memorandum (23 March 2009).
3. The extension of this certification is based upon Desktop Review (DTR) 7. The original certification is based on interoperability testing conducted by JITC, DISA adjudication of open test discrepancy reports, review of the vendor's Letters of Compliance (LoC), and Defense Information Assurance (IA)/Security Accreditation Working Group (DSAWG) accreditation. Interoperability testing was conducted by JITC at the Global Information Grid Network Test Facility, Fort Huachuca, Arizona from 7 July through 1 August 2008. Regression testing was conducted from 1 through 5 December 2008 and documented in Reference (e). Review of vendor's LoC was completed on 11 December 2008. DISA adjudication of outstanding test discrepancy reports was completed on 18 December 2008. DSAWG grants accreditation based on the security testing completed by DISA-led Information Assurance test teams and published in a separate report, Reference (f). DSAWG accreditation was granted on 10 March 2009 and

expires three years from date of issue. The original certification specified the expiration date four years from date of issue; however, this certification is also based on the IA accreditation, which is limited to three years, so expiration date has been changed to reflect the maximum authorized timeframe. Additionally, this DTR was requested to include the latest version number for the previously certified component listed in Table 1. The component included in Table 1 was certified by JITC in the original certification. The JITC determined there is no risk in approving this DTR because this change improves the manufacturing process without changing unit functionality or performance. This hardware version number update reflects minor hardware changes in the SUT: the filter changed from separate filters to a one-piece filter in the fan and adds a new power transistor. These changes have no effect on the functionality, performance, or interoperability of the SUT. Therefore, JITC approves this DTR. DISA Network Systems Directorate has approved the Information Assurance posture of SUT in this DTR on 11 February 2011.

**Table 1. SUT Component Version Numbers**

Part Number	Part Number Description	Correct/New Version Number
FC9580FAN2	Fan Unit (4 Per Shelf)	08
<b>LEGEND:</b> SUT System Under Test		

4. The SUT Interoperability Test Summary is shown in Table 2 and the Capability and Feature Requirements used to evaluate the interoperability of the SUT are indicated in Table 3.

**Table 2. SUT Interoperability Test Summary**

DSN Access Interfaces			
DSN Switch Access	Critical	Status	Remarks
T1 CAS (AMI/SF) DTMF, MFR1, DP	No <sup>1</sup>	Certified	Met all CRs and FRs.
T1 CAS (B8ZS/ESF) DTMF, MFR1, DP	No <sup>1</sup>	Certified	Met all CRs and FRs.
T1 PRI (ANSI T1.619a)	No <sup>1</sup>	Certified	Met all CRs and FRs.
T1 SS7 (ANSI T1.619a)	No <sup>1</sup>	Certified	Met all CRs and FRs.
E1 CAS (HDB3) DTMF, MFR1, DP	No <sup>1</sup> (Europe only)	Not Tested	The SUT offers this interface; however it was not tested. The SUT E1 CAS interface is therefore not certified by JITC, or authorized for use by the DSN PMO for use within the DSN. This is not a required interface for a Strategic Network Element.
E1 ISDN PRI (ITU-T Q.955.3)	No <sup>1</sup> (Europe only)	Not Tested	The SUT offers this interface; however it was not tested. The SUT E1 CAS interface is therefore not certified by JITC, or authorized for use by the DSN PMO for use within the DSN. This is not a required interface for a Strategic Network Element.
E1 SS7 (ANSI T1.619a)	No <sup>1</sup> (Europe only)	Not Tested	The SUT offers this interface; however it was not tested. The SUT E1 CAS interface is therefore not certified by JITC, or authorized for use by the DSN PMO for use within the DSN. This is not a required interface for a Strategic Network Element.
DS3	No <sup>1</sup>	Certified	Met all CRs and FRs.
DS3C	No <sup>1</sup>	Certified	Met all CRs and FRs.
10/100 Mbps Ethernet	No <sup>1</sup>	Certified	Met all CRs and FRs.
Gigabit Ethernet	No <sup>1</sup>	Certified	Met all CRs and FRs.

**Table 2. SUT Interoperability Test Summary (continued)**

DSN Transport Interfaces				
Optical Carrier Level	Transport Level	Critical	Status	Remarks
OC-3	VT 1.5	No <sup>2</sup>	Certified	Met all CRs and FRs.
	STS-1	No <sup>2</sup>	Certified	Met all CRs and FRs.
OC-12	VT 1.5	No <sup>2</sup>	Certified	Met all CRs and FRs.
	STS-1	No <sup>2</sup>	Certified	Met all CRs and FRs.
OC-48	VT 1.5	No <sup>2</sup>	Certified	Met all CRs and FRs.
	STS-1	No <sup>2</sup>	Certified	Met all CRs and FRs.
OC-192	VT 1.5	No <sup>2</sup>	Certified	Met all CRs and FRs.
	STS-1	No <sup>2</sup>	Certified	Met all CRs and FRs.
Features And Capabilities				
Features and Capabilities		Critical	Status	Remarks
Synchronization		Yes	Certified	Met all CRs and FRs.
Network Management		Yes	Certified	Met all CRs and FRs.
Security		Yes	See note 3.	See note 3.
<b>NOTES:</b>				
1 The UCR does not stipulate a minimum Access interface requirement for a Strategic Network Element.				
2 The UCR does not stipulate a minimum Transport interface requirement for a Strategic Network Element.				
3 Security is tested by DISA-led Information Assurance test teams and published in a separate report, Reference (f).				
<b>LEGEND:</b>				
10/100BaseT	10/100 Mbps (Baseband Operation, Twisted Pair) Ethernet	ITU-T	International Telecommunication Union – Telecommunication Standardization Sector	
AMI	Alternate Mark Inversion	Mbps	Megabits per second	
ANSI	American National Standards Institute	MFR1	Multi-frequency Recommendation 1	
B8ZS	Bipolar Eight Zero Substitution	MLPP	Multi-Level Precedence and Preemption	
CAS	Channel Associated Signaling	OC-3	Optical Carrier Level 3 (155 Mbps)	
CR	Capability Requirements	OC-12	Optical Carrier Level 12 (622 Mbps)	
DISA	Defense Information Systems Agency	OC-48	Optical Carrier Level 48 (2.448 Gbps)	
DP	Dial Pulse	OC-192	Optical Carrier Level 192 (10 Gbps)	
DS3	Digital Signal Level 3 (44.736 Mbps)	PRI	Primary Rate Interface	
DS3C	Digital Signal Level 3 (89.472 Mbps)	Q.955.3	ISDN Signaling Standard for E1 MLPP	
DTMF	Dual Tone Multi-Frequency	SF	Super Frame	
DSN	Defense Switched Network	SS7	Signaling System 7	
E1	European Basic Multiplex Rate (2.048 Mbps)	SUT	System Under Test	
ESF	Extended Super Frame	STS	Synchronous Transport Signal	
FR	Feature Requirements	T1	Digital Transmission Link Level 1 (1.544 Mbps)	
Gbps	Gigabits per second	T1.619a	SS7 and ISDN MLPP Signaling Standard for T1	
HDB3	High Density Bipolar 3	UCR	Unified Capabilities Requirements	
ISDN	Integrated Services Digital Network	VT1.5	Virtual Tributary 1.5	

**Table 3. SUT Capability and Feature Interoperability Requirements**

<b>DSN Access Interfaces</b>			
<b>Interface</b>	<b>Critical</b>	<b>Requirements Required or Conditional</b>	<b>References</b>
T1 CAS	No <sup>1</sup>	<ul style="list-style-type: none"> <li>• DS1 Interface Characteristics (C)</li> <li>• DS1 Supervisory Channel Associated Signaling (C)</li> </ul>	<ul style="list-style-type: none"> <li>• UCR para. A9.5.1.2.4</li> <li>• UCR para. A9.5.1.2.4</li> </ul>
T1 SS7 (ANSI T1.619a)	No <sup>1</sup>	<ul style="list-style-type: none"> <li>• DS1 Clear Channel Capability (C)</li> <li>• DS1 Alarm and Restoral Requirements (C)</li> </ul>	<ul style="list-style-type: none"> <li>• UCR para. A9.5.1.2.4</li> <li>• UCR para. A9.5.1.2.4</li> </ul>
T1 ISDN PRI (ANSI T1.607/ANSI T1.619a)	No <sup>1</sup>	<ul style="list-style-type: none"> <li>• E1 Interface Characteristics (C)</li> <li>• E1 Supervisory Channel Associated Signaling (C)</li> </ul>	<ul style="list-style-type: none"> <li>• UCR para. A9.5.1.2.5</li> <li>• UCR para. A9.5.1.2.5</li> </ul>
E1 ISDN PRI (ITU-T Q.955.3)	No <sup>1</sup> (Europe only)	<ul style="list-style-type: none"> <li>• E1 Clear Channel Capability (C)</li> <li>• E1 Alarm and Restoral Requirements (C)</li> </ul>	<ul style="list-style-type: none"> <li>• UCR para. A9.5.1.2.5</li> <li>• UCR para. A9.5.1.2.5</li> </ul>
E1 CAS	No <sup>1</sup> (Europe only)	<ul style="list-style-type: none"> <li>• MOS (R)</li> <li>• BERT (R)</li> </ul>	<ul style="list-style-type: none"> <li>• UCR para. A9.5.1.1</li> <li>• UCR para. A9.5.1.1</li> </ul>
E1 SS7 (ANSI T1.619a)	No <sup>1</sup> (Europe only)	<ul style="list-style-type: none"> <li>• Secure Transmission (Voice and Data) (R)</li> <li>• Modem (R)</li> <li>• Facsimile (R)</li> </ul>	<ul style="list-style-type: none"> <li>• UCR para. A9.5.1.1</li> <li>• UCR para. A9.5.1.1</li> <li>• UCR para. A9.5.1.1</li> </ul>
DS3, DS3C	No <sup>1</sup>	<ul style="list-style-type: none"> <li>• Call Control Signals (R)</li> <li>• Delay (R)</li> </ul>	<ul style="list-style-type: none"> <li>• UCR para. A9.5.1.1</li> <li>• UCR para. A9.5.1.1</li> </ul>
10/100 Mbps Ethernet	No <sup>1</sup>	<ul style="list-style-type: none"> <li>• Call Congestion Control (R)</li> <li>• Call Congestion (R)</li> </ul>	<ul style="list-style-type: none"> <li>• UCR para. A9.5.1.1</li> <li>• UCR para. A9.5.1.1.3</li> </ul>
Gigabit Ethernet	No <sup>1</sup>	<ul style="list-style-type: none"> <li>• Voice Compression (C)</li> <li>• DS3 Interface Requirements (R)</li> <li>• IP Interface (C)</li> </ul>	<ul style="list-style-type: none"> <li>• UCR para. A9.5.1.2.6</li> <li>• UCR para. A9.5.1.2.9</li> </ul>
<b>DSN Transport Interfaces</b>			
<b>Interface</b>	<b>Critical</b>	<b>Requirements Required or Conditional</b>	<b>References</b>
OC-3	No <sup>2</sup>	<ul style="list-style-type: none"> <li>• MLPP (R)</li> <li>• GR-303-CORE (R)</li> <li>• GR-253-CORE (R)</li> <li>• GR-782-CORE (R)</li> <li>• ANSI T1.105-2001 (R)</li> <li>• DS1 Rate Transport via VT1.5 (R)</li> </ul>	<ul style="list-style-type: none"> <li>• UCR para. A5.5.1</li> <li>• UCR para. A5.5.2</li> </ul>
OC-12	No <sup>2</sup>	<ul style="list-style-type: none"> <li>• DS1 Rate Provisioning (R)</li> <li>• DS0 Call Processing (R)</li> <li>• DS0 to OC-3 Route Assignment (R)</li> <li>• Facility Alarms (R)</li> <li>• DS1 AIS/Yellow (R)</li> <li>• DS0 AIS/DS0 RAI (R)</li> </ul>	<ul style="list-style-type: none"> <li>• UCR para. A5.5.2</li> <li>• UCR para. A5.5.2</li> <li>• UCR para. A5.5.3</li> <li>• UCR para. A5.5.4</li> <li>• UCR para. A5.5.4</li> <li>• UCR para. A5.5.4</li> </ul>
OC-48	No <sup>2</sup>	<ul style="list-style-type: none"> <li>• Synchronization in accordance with GR-518-CORE (R)</li> <li>• Synchronization in accordance with GR-253-CORE (R)</li> <li>• Synchronization in accordance with GR-436-CORE (R)</li> <li>• Reliability (R)</li> <li>• Security (R)</li> <li>• MOS (R)</li> <li>• BERT (R)</li> </ul>	<ul style="list-style-type: none"> <li>• UCR para. A5.5.5</li> <li>• UCR para. A5.5.5</li> <li>• UCR para. A5.5.5</li> <li>• UCR para. A5.5.6</li> <li>• UCR para. A5.6</li> <li>• UCR para. A9.5.1.1</li> <li>• UCR para. A9.5.1.1</li> </ul>
OC-192	No <sup>2</sup>	<ul style="list-style-type: none"> <li>• Secure Transmission (Voice and Data) (R)</li> <li>• Modem (R)</li> <li>• Facsimile (R)</li> <li>• Call Control Signals (R)</li> <li>• Delay (R)</li> <li>• Call Congestion Control (R)</li> <li>• Voice Compression (C)</li> </ul>	<ul style="list-style-type: none"> <li>• UCR para. A9.5.1.1</li> <li>• UCR para. A9.5.1.1.3</li> <li>• UCR para. A9.5.1.1.4</li> </ul>

**Table 3. SUT Capability and Feature Interoperability Requirements (continued)**

SUT Features And Capabilities			
Feature/Capability	Critical	Requirements Required or Conditional	References
Synchronization	Yes	• Timing (R)	• UCR para. A9.5.1.2.7
Network Management	Yes	• Management Option (R) - Local Management (Front Panel and/or External Console) (C) - ADIMSS (C) • Fault Management (C) • Loop Back Capability (C) • Operational Configuration Restoral (R)	• UCR para. A9.5.2.1  • UCR para. A9.5.2.2 • UCR para. A9.5.2.3 • UCR para. A9.5.3
Security	Yes	• DIACAP and STIGs (R)	• UCR para. A9.6

**NOTES:**  
1 The UCR does not stipulate a minimum Access interface requirement for a Strategic Network Element.  
2 The UCR does not stipulate a minimum Transport interface requirement for a Strategic Network Element.

**LEGEND:**

A	Appendix	ISDN	Integrated Services Digital Network
ADIMSS	Advanced DSN Integrated Management Support System	ITU-T	International Telecommunication Union - Telecommunication Standardization Sector
AIS	Alarm Indication Signal	LSSGR	Local Access and Transport Area (LATA) Switching Systems Generic Requirements
ANSI	American National Standards Institute	Mbps	Megabits per second
BERT	Bit Error Rate Test	MLPP	Multi-Level Precedence and Preemption
C	Conditional	MOS	Mean Opinion Score
CAS	Channel Associated Signaling	OC-3	Optical Carrier Level 3 (155 Mbps)
DIACAP	DoD Information Assurance Certification and Accreditation Process	OC-12	Optical Carrier Level 12 (622 Mbps)
DoD	Department of Defense	OC-48	Optical Carrier Level 48 (2.448 Gbps)
DS0	Digital Signal Level 0	OC-192	Optical Carrier Level 192 (10 Gbps)
DS1	Digital Signal Level 1	para	paragraph
DS3	Digital Signal Level 3	PRI	Primary Rate Interface
DS3C	Digital Signal Level 3 - Concatenated	Q.955.3	ISDN Signaling standard for E1 MLPP
DSN	Defense Switched Network	R	Required
DSS1	Digital Subscriber Signaling 1	RAI	Remote Alarm Indication
DWDM	Dense Wavelength Division Multiplexing	SONET	Synchronous Optical Network
E1	European Basic Multiplex Rate (2.048 Mbps)	SS7	Signaling System 7
Gbps	Gigabits per second	STIGs	Secure Technical Implementation Guides
GR	Generic Requirement	SUT	System Under Test
GR-253-CORE	SONET Transport Systems: Common Generic Criteria	T1	Digital Transmission Link Level 1 (1.544 Mbps)
GR-303-CORE	Integrated Digital Loop Carrier System Generic Requirements, Objectives, and Interface	T1.105-2001	SONET – Basic Description include Multiplexer structure, rates, formats
GR-436-CORE	Digital Network Synchronization Plan	T1.607	ISDN – Layer 3 Signaling Specification for Circuit Switched Bearer Service for DSS1
GR-518-CORE	LSSGR: Synchronization, Section 18	T1.619a	SS7 and ISDN MLPP Signaling Standard for T1
GR-782-CORE	SONET Digital Switch Trunk Interface Criteria	UCR	Unified Capabilities Requirements
IP	Internet Protocol	VT1.5	Virtual Tributary 1.5

5. No detailed test report was developed in accordance with the Program Manager’s request. JITC distributes interoperability information via the JITC Electronic Report Distribution (ERD) system, which uses Unclassified-But-Sensitive Internet Protocol Router Network (NIPRNet) e-mail. More comprehensive interoperability status information is available via the JITC System Tracking Program (STP). The STP is accessible by .mil/gov users on the NIPRNet at <https://stp.fhu.disa.mil>. Test reports, lessons learned, and related testing documents and references are on the JITC Joint Interoperability Tool (JIT) at <http://jit.fhu.disa.mil> (NIPRNet). Information related to DSN testing is on the Telecom Switched Services Interoperability (TSSI) website at <http://jitc.fhu.disa.mil/tssi>. Due to the sensitivity of the information, the Information Assurance Accreditation Package (IAAP) that contains the approved configuration and

JITC Memo, JTE, Extension of the Special Interoperability Test Certification of the Fujitsu FLASHWAVE 4500 with Software Release 8.2

deployment guide must be requested directly through government civilian or uniformed military personnel from the Unified Capabilities Certification Office (UCCO), e-mail: [ucco@disa.mil](mailto:ucco@disa.mil).

6. The JITC point of contact is Mr. Khoa Hoang, DSN 879-4376, commercial (520) 538-4376, FAX DSN 879-4347, or e-mail to [khoa.hoang@disa.mil](mailto:khoa.hoang@disa.mil). The JITC's mailing address is P.O. Box 12798, Fort Huachuca, AZ 85670-2798. The tracking number for the SUT is 0820405.

FOR THE COMMANDER:

Enclosure a/s

  
for BRADLEY A. CLARK  
Acting Chief  
Battlespace Communications Portfolio

Distribution (electronic mail):

Joint Staff J-6

Joint Interoperability Test Command, Liaison, TE3/JT1

Office of Chief of Naval Operations, CNO N6F2

Headquarters U.S. Air Force, Office of Warfighting Integration & CIO, AF/XCIN (A6N)

Department of the Army, Office of the Secretary of the Army, DA-OSA CIO/G-6 ASA (ALT), SAIS-IOQ

U.S. Marine Corps MARCORSSYSCOM, SIAT, MJI Division I

DOT&E, Net-Centric Systems and Naval Warfare

U.S. Coast Guard, CG-64

Defense Intelligence Agency

National Security Agency, DT

Defense Information Systems Agency, TEMC

Office of Assistant Secretary of Defense (NII)/DOD CIO

U.S. Joint Forces Command, Net-Centric Integration, Communication, and Capabilities Division, J68

Defense Information Systems Agency, GS23

## ADDITIONAL REFERENCES

- (c) Defense Information Systems Agency, "Department of Defense Voice Networks Unified Capabilities Requirements (UCR), 21 December 2007
- (d) Joint Interoperability Test Command (JITC), "Defense Switched Network Generic Switch Test Plan (GSTP), Change 2," 2 October 2006
- (e) JITC Memo, JTE, "Special Interoperability Test Certification of the Fujitsu FLASHWAVE 4500 with Software Release 8.2," 23 March 2009
- (f) Joint Interoperability Test Command, "Information Assurance (IA) Assessment of Fujitsu FLASHWAVE 4500 with Software Release 8.2 (Tracking Number 0820405)," 10 March 2009