



## DEFENSE INFORMATION SYSTEMS AGENCY

P. O. BOX 549  
FORT MEADE, MARYLAND 20755-0549

IN REPLY  
REFER TO: Joint Interoperability Test Command (JTE)

**8 Mar 13**

### MEMORANDUM FOR DISTRIBUTION

**SUBJECT:** Extension of the Special Interoperability Test Certification of the Hewlett-Packard (HP) 6600 from Release K.15.04.0003 to Release K.15.09.0009

**References:** (a) DoD Directive 4630.05, "Interoperability and Supportability of Information Technology (IT) and National Security Systems (NSS)," 5 May 2004  
(b) CJCSI 6212.01E, "Interoperability and Supportability of Information Technology and National Security Systems," 15 December 2008  
(c) through (e), see Enclosure

1. References (a) and (b) establish Joint Interoperability Test Command (JITC), as the responsible organization for interoperability test certification.
2. The HP 6600 with Release K.15.04.0003 is hereinafter referred to as the System Under Test (SUT). The SUT meets all of its critical interoperability requirements and is certified for joint use within the Defense Information Systems Network (DISN) as an Assured Services Local Area Network (ASLAN) Layer 2/Layer 3 Access switch. The SUT is certified as interoperable for joint use with other ASLAN components listed on the Unified Capabilities (UC) Approved Products List (APL) with the following interfaces: 1000Base-SX, 1000Base-LX, 10Gbase-SR, 10Gbase-LR, 10/100/1000BaseT. JITC tested all these interfaces with the exception of the 10BaseT interface. JITC analysis determined the 10BaseT interface is low risk for certification based on the vendor's Letter of Compliance (LoC) to the Institute of Electrical and Electronics Engineers (IEEE) 802.3i standard and the testing data collected at all other data rates. The SUT meets the critical interoperability requirements set forth in Reference (c), using test procedures derived from Reference (d).

The SUT is certified to support Assured Services within an ASLAN. If a component meets the minimum requirements for deployment in an ASLAN, it also meets the lesser requirements for deployment in a non-ASLAN. Non-ASLANs are "commercial grade" and provide support to Command and Control (C2) (ROUTINE only calls) (C2(R)) or non-C2 voice subscribers. When deployed in a non-ASLAN, the SUT may also be used to receive all levels of precedence, but is limited to supporting calls that are originated at ROUTINE precedence only. Non-ASLANs do not meet the availability or redundancy requirements for C2 or Special C2 users and therefore are not authorized to support precedence calls originated above ROUTINE.

No other configurations, features, or functions, except those cited within this document, are certified by JITC. This certification expires upon changes that affect interoperability, but no later than 5 October 2014, which is three years from the date of the original UC APL memorandum.

3. The extension of this certification is based upon Desktop Review (DTR) 2. The original certification, documented in Reference (e), is based on interoperability testing conducted by JITC, review of the vendor's LoC, DISA adjudication of open test discrepancy reports (TDRs), and DISA Certifying Authority (CA) Recommendation. Interoperability testing was conducted by JITC, Fort Huachuca, Arizona, from 31 May through 8 July 2011. Review of the vendor's LoC was completed on 30 June 2011. DISA adjudication of open TDRs was completed on 26 July 2011. The DISA CA provided a positive Recommendation on 21 September 2011 based on the security testing completed by DISA-led Information Assurance (IA) test teams and published in a separate report, Reference (f). DTR 2 was requested to update the software from Release K.15.04.003 to K.15.09.0009 to address previously documented interoperability and IA issues. JITC determined this DTR would require Interoperability and IA Verification and Validation (V&V) testing. V&V testing was conducted from 1 through 12 October 2012 and from 10 through 14 December 2012. Two TDRs were closed, one previous TDR remained open, and one new TDR was identified as discussed in the subparagraphs below.

a. The SUT met all Class of Service requirements with the following exception: the Open Shortest Path First version 3 (OSPFv3) Internet Protocol version 6 (IPv6) Differentiated Services Code Point (DSCP) values are incorrectly marked with a DSCP value of 0. This discrepancy was originally adjudicated as having a minor operational impact based on vendor's submission of a Plan of Action and Milestones (POA&M). During V&V testing it was again verified that the OSPF v3 DSCP values are incorrectly marked. DISA has accepted and approved the vendor's new POA&M and adjudicated this discrepancy as having a minor operational impact.

b. During V&V testing, it was noted that the SUT incorrectly tagged the Virtual Router Redundancy Protocol (VRRP) Internet Protocol version 4 (IPv4) DSCP traffic. The SUT is required to tag all signaling traffic at 48 and be able to tag any value 0-63. The SUT incorrectly tags the VRRP IPv4 DSCP traffic at 0. DISA has accepted and approved the vendor's new POA&M and adjudicated this discrepancy as having a minor operational impact.

c. During the initial certification test, the Department of Defense Information Technology Standards Registry (DISR) profile protocols were met with vendor's LoC and/or testing with the following minor exception adjudicated by DISA with a vendor's submission of a POA&M. The vendor's submitted LoC stated that their SUT cannot set the full range of OSPFv3 dead interval. This discrepancy was verified to be fixed during V&V testing.

d. During the initial certification test, IPv6 failover exceeded the 5 second requirement (5.8 seconds) with a link failover to the Brocade ASLAN component. This discrepancy was adjudicated by DISA as having a minor operational impact based on the vendor's submission of a POA&M. This discrepancy was verified to be fixed during V&V testing.

The DISA CA provided a positive recommendation for this DTR on 7 March 2013, based on the security testing completed DISA-led IA test teams and published in a separate report, Reference (f). Therefore, JITC approves this DTR.

4. Table 1 provides a Unified Capabilities Approved Products List (UC APL) product summary. Table 2 provides the SUT interface interoperability status, and Table 3 provides the Capability



**Table 3. SUT CRs and FRs Status**

CR/FR ID	Capability/ Function	Applicability <sup>1</sup>	UCR Reference	Status	Remarks
1	<b>General Performance Parameters</b>				
	Performance Parameters	Required	5.3.1.3	Met	
	Port Interface Rates	Required	5.3.1.3.1	Met	
	Port Parameter Requirements	Required	5.3.1.3.2	Met	
	Class of Service Markings	Required	5.3.1.3.3	Partially Met <sup>2,3</sup>	
	VLAN Capabilities	Required	5.3.1.3.4	Met	
	Protocols	Required	5.3.1.3.5	Met <sup>4</sup>	
	QoS Features	Required	5.3.1.3.6	Partially Met <sup>2</sup>	
	Network Monitoring	Required	5.3.1.3.7	Met	
	Security	Required	5.3.1.3.8	Met <sup>5</sup>	
2	<b>E2E Performance Requirements</b>				
	Voice Services	Required	5.3.1.4.1	Met <sup>6</sup>	
	Video services	Required	5.3.1.4.2	Met <sup>6</sup>	
	Data services	Required	5.3.1.4.3	Met <sup>6</sup>	
3	<b>NM Requirements</b>				
	Configuration Control	Required	5.3.1.6.1	Met	
	Operational Changes	Required	5.3.1.6.2	Met	
	Performance Monitoring	Required	5.3.1.6.3	Met	
	Alarms	Required	5.3.1.6.4	Met	
	Reporting	Required	5.3.1.6.5	Met	
4	<b>Engineering Requirements</b>				
	Physical Media	Required	5.3.1.7.1	Met <sup>7</sup>	
	Traffic Engineering	Required	5.3.1.7.3	Met <sup>7</sup>	Configured with four queues, each set to 25% of total bandwidth.
	Availability	Required	5.3.1.7.6	Met <sup>7</sup>	100% availability during test.
	Redundancy	Required	5.3.1.7.7	Partially Met <sup>8</sup>	
5	<b>MPLS</b>				
	MPLS Requirements	Conditional	5.3.1.8.4.1	Not Tested <sup>9</sup>	
	MPLS VPN Augmentation to VLANs	Conditional	5.3.1.8.4.2	Not Tested <sup>9</sup>	
6	<b>IPv6 Requirements</b>				
Product Requirements	Required	5.3.5.4	Met		

**NOTES:**

1. The annotation of 'required' refers to a high-level requirement category. The applicability of each sub-requirement is provided in Reference (e), Enclosure 3. The SUT does not need to provide conditional requirements. However, if a capability is provided, it must function according to the specified requirements.
2. The SUT met all Class of Service requirements with the following exception: OSPFv3 IPv6 DSCP values are incorrectly marked with a DSCP value of 0. This discrepancy was originally adjudicated as having a minor operational impact based on the vendor's submission of a POA&M. However, during testing it was verified that the OSPF v3 DSCP values are still incorrectly marked. DISA has accepted and approved the vendor's new POA&M and adjudicated this discrepancy as having a minor operational impact.
3. During testing for DTR 2, it was noted that the SUT incorrectly tagged the VRRP IPv4 DSCP traffic. The SUT is required to tag all signaling traffic at 48 and be able to tag any value 0-63. The SUT incorrectly tags the VRRP IPv4 DSCP traffic at 0. DISA has accepted and approved the vendor's new POA&M and adjudicated this discrepancy as having a minor operational impact.
4. The DISR profile protocols were met with vendor's LoC and/or testing with the following minor exception adjudicated by DISA with a vendor's submission of a POA&M. The vendor's submitted LoC stated that their SUT cannot set the full range of OSPFv3 dead interval. This discrepancy was verified to be fixed during DTR testing.
5. Refers to IA requirements for UCR 2008, Change 2, Section 5.4. Detailed IA requirements are included in Reference (f).

**Table 3. SUT CRs and FRs Status (continued)**

<b>NOTES (continued):</b>			
6. This requirement was verified and met using simulated voice, video, and data traffic in an operational emulated environment to meet E2E requirements. The SUT must be deployed in accordance with deployment guide and engineering guidelines provided in UCR 5.3.1.4.			
7. This requirement was met with the following stipulations: It is the site's responsibility to configure the SUT in a manner which meets the engineering requirements listed in Section 11.2 d. of Reference (e), Enclosure 2 and that does not create a single point of failure which could impact more than 96 C2 users.			
8. This requirement was met with the following exception: IPv6 failover exceeded the 5 second requirement (5.8 seconds) with a link failover to the Brocade ASLAN component. This discrepancy was adjudicated by DISA as having a minor operational impact based on the vendor's submission of a POA&M. This discrepancy was verified to be fixed during DTR testing.			
9. MPLS is conditional for a core, distribution, or access switch.			
<b>LEGEND:</b>			
ASLAN	Assured Services Local Area Network	LoC	Letter of Compliance
C2	Command and Control	MPLS	Multiprotocol Label Switching
CR	Capability Requirement	NM	Network Management
DISA	Defense Information Systems Agency	OSPFv3	Open Shortest Path First version 3
DTR	Desktop Review	POA&M	Plan of Action and Milestones
E2E	End-to-End	QoS	Quality of Service
FR	Functional Requirement	SUT	System Under Test
IA	Information Assurance	UCR	Unified Capabilities Requirements
ID	Identification	VLAN	Virtual Local Area Network
IPv4	Internet Protocol version 4	VPN	Virtual Private Network
IPv6	Internet Protocol version 6	VRRP	Virtual Router Redundancy Protocol

5. No detailed test report was developed in accordance with the Program Manager's request. JITC distributes interoperability information via the JITC Electronic Report Distribution (ERD) system, which uses Unclassified-But-Sensitive Internet Protocol Router Network (NIPRNet) e-mail. More comprehensive interoperability status information is available via the JITC System Tracking Program (STP). STP is accessible by .mil/gov users on the NIPRNet at <https://stp.fhu.disa.mil>. Test reports, lessons learned, and related testing documents and references are on the JITC Joint Interoperability Tool (JIT) at <http://jit.fhu.disa.mil> (NIPRNet). Information related to DSN testing is on the Telecom Switched Services Interoperability (TSSI) website at <http://jitc.fhu.disa.mil/tssi>. Due to the sensitivity of the information, the Information Assurance Accreditation Package (IAAP) that contains the approved configuration and deployment guide must be requested directly through government civilian or uniformed military personnel from the Unified Capabilities Certification Office (UCCO), e-mail: [disa.meade.ns.list.unified-capabilities-certification-office@mail.mil](mailto:disa.meade.ns.list.unified-capabilities-certification-office@mail.mil). All associated data is available on the DISA UCCO website located at <http://www.disa.mil/ucco/>.

JITC Memo, JTE, Extension of the Special Interoperability Test Certification of the Hewlett-Packard (HP) 6600 from Release K.15.04.0003 to Release K.15.09.0009

6. The JITC point of contact is CPT James Torres, DSN 879-5575, commercial (520) 538-5575, FAX DSN 879-4347, or e-mail to james.m.torres.mil@mail.mil. JITC's mailing address is P.O. Box 12798, Fort Huachuca, AZ 85670-2798. The UCCO tracking number for the SUT is 1036206.

FOR THE COMMANDER:

Enclosure a/s

  
for RICHARD A. MEADOR  
Chief  
Battlespace Communications Portfolio

Distribution (electronic mail):

DoD CIO  
Joint Staff J-6, JCS  
USD(AT&L)  
ISG Secretariat, DISA, JTA  
U.S. Strategic Command, J665  
US Navy, OPNAV N2/N6FP12  
US Army, DA-OSA, CIO/G-6 ASA(ALT), SAIS-IOQ  
US Air Force, A3CNN/A6CNN  
US Marine Corps, MARCORSYSCOM, SIAT, A&CE Division  
US Coast Guard, CG-64  
DISA/TEMC  
DIA, Office of the Acquisition Executive  
NSG Interoperability Assessment Team  
DOT&E, Netcentric Systems and Naval Warfare  
Medical Health Systems, JMIS IV&V  
HQUSAISEC, AMSEL-IE-IS  
UCCO

## **ADDITIONAL REFERENCES**

- (c) Office of the Assistant Secretary of Defense, "Department of Defense Unified Capabilities Requirements 2008, Change 2," 31 December 2010
- (d) Joint Interoperability Test Command, "ASLAN Component Test Plan (UCTP)," November 2010
- (e) Joint Interoperability Test Command, Memo, JTE, "Special Interoperability Test Certification of the Hewlett-Packard (HP) 6600 with Release K.15.04.0003," 29 September 2011
- (f) Joint Interoperability Test Command, "Information Assurance (IA) Assessment of HP 6600 with Release (Rel.) K.15.04.0003 (Tracking Number 1036206)," Draft