



DEFENSE INFORMATION SYSTEMS AGENCY

P. O. BOX 549
FORT MEADE, MARYLAND 20755-0549

IN REPLY
REFER TO: Joint Interoperability Test Command (JTE)

26 Jun 13

MEMORANDUM FOR DISTRIBUTION

SUBJECT: Extension of the Special Interoperability Test Certification of the Hewlett Packard (HP) A7500 Series Release 5.20.R6701

References: (a) DoD Directive 4630.05, "Interoperability and Supportability of Information Technology (IT) and National Security Systems (NSS)," 5 May 2004
(b) CJCSI 6212.01E, "Interoperability and Supportability of Information Technology and National Security Systems," 15 December 2008
(c) through (g), see Enclosure

1. References (a) and (b) establish the Defense Information Systems Agency (DISA), Joint Interoperability Test Command (JITC), as the responsible organization for interoperability test certification.

2. The HP A7510 and A7506 with Release 5.20 are hereinafter referred to as the system under test (SUT). The vendor submitted a Desktop Review (DTR) request to include component Stock Keeping Unit (SKU) numbers in addition to the component SKUs they are identical to and were included in the original certification. The SUT meets all of its critical interoperability requirements and is certified for joint use within the Defense Information System Network (DISN) as an Assured Services Local Area Network (ASLAN) core, distribution, and access switch. The SUT is certified as interoperable for joint use within the DISN with other ASLAN components listed on the Unified Capabilities (UC) Approved Products List (APL) with the following interfaces: 10000/1000Base SX/LX, 100BaseFX, and 10/100/1000BaseT. The SUT met the critical interoperability requirements set forth in Reference (c) using test procedures derived from Reference (d). The HP A7506-V and A7503 employ the same software and similar hardware as the SUT. The JITC analysis determined these systems to be functionally identical to the SUT for interoperability certification purposes and they are also certified for joint use.

The SUT is certified to support Defense Switched Network (DSN) Assured Services over Internet Protocol. If a component meets the minimum requirements for deployment in an ASLAN, it also meets the lesser requirements for deployment in a non-ASLAN. Non-ASLANs are "commercial grade" and provide support to Command and Control (C2) (ROUTINE only calls) (C2(R)) or non-C2 voice subscribers. The SUT is certified for joint use deployment in a non-ASLAN for C2R and non-C2 traffic. When deployed in a non-ASLAN, the SUT may also be used to receive all levels of precedence, but is limited to supporting calls that are originated at ROUTINE precedence only. Non-ASLANs do not meet the availability or redundancy requirements for C2 or Special C2 users and therefore are not authorized to support precedence calls originated above ROUTINE.

Testing of the SUT did not include video services or data applications; however, simulated preferred data, best effort data, and video traffic was generated during testing to determine the SUT’s ability to prioritize and properly queue voice media and signaling traffic. No other configurations, features, or functions, except those cited within this document, are certified by the JITC. This certification expires upon changes that affect interoperability, but no later than three years from the date of Defense Information Assurance (IA)/Security Accreditation Working Group (DSAWG) accreditation (23 November 2010).

3. The extension of this certification is based on Desktop Review (DTR) 5. The original certification, documented in Reference (e), is based on interoperability testing conducted by JITC, DISA adjudication of open test discrepancy reports (TDRs), review of the vendor’s Letters of Compliance (LoC), and DSAWG accreditation. Interoperability testing was conducted by JITC at the Global Information Grid Network Test Facility, Fort Huachuca, Arizona, from 11 January through 19 March 2010. Review of the vendor’s LoC was completed on 3 May 2010. DISA adjudication of outstanding TDRs was completed on 3 May 2010. DSAWG granted accreditation on 23 November 2010 based on the security testing completed by DISA-led IA test teams and published in a separate report, Reference (f). The test and certification was conducted on 3Com switches, which have all been renamed after HP purchased 3Com in 2010. The documentation for the 3Com certification is provided in Reference (g). This DTR was requested to include Trade Agreements Act (TAA) SKU numbers. These products are identical to the ones tested; however, they have a different site of manufacture. Table 1 denotes the additional TAA SKU numbers in parenthesis next to the SKU numbers they are identical to. This DTR was also requested to correct a SKU, included with DTR 2, from JD233A (JC716A) to JD232A (JC716A). JITC determined through analysis that this DTR would not impact the interoperability certified features and functions of the SUT. Additionally, the DISA CA has approved this DTR to include the additional TAA SKUs without further testing. Therefore, the original IA approval applies to this DTR and JITC approves this DTR.

Table 1. HP to 3Com Switch Product Cross-Reference

<u>3Com Switch</u> (See note 1.)	<u>HP Switch</u> (See note 1.)	<u>Release</u> (See note 2.)	<u>Function</u>
<u>3CS7910E</u>	<u>A7510</u>	5.20.R6701	Core, Distribution, Access Switch
<u>3CS7906E</u>	<u>A7506</u>	5.20.R6701	Core, Distribution, Access Switch
S7906E-V	A7506-V	5.20.R6701	Core, Distribution, Access Switch
S7903E	A7503	5.20.R6701	Core, Distribution, Access Switch
<u>3Com Switch Subcomponent</u> (See note 1.)	<u>HP Switch Subcomponent</u> (See note 1.)		<u>Function</u>
0231A92P	JD202A		12-Port Advanced 1000BASE-X Module (SFP)
0231A79J	JD207A		12-port 100/1000BASE-X Module (SFP)
<u>0231A998</u>	<u>JD220A (JC701A)</u>		<u>Saliency VI-Plus 768G Switch Fabric</u>
0231A935	JD195A		384G Advanced Switch Fabric
0231A934	JF219B		384G Switch Fabric support smaller mac/routing table
0231A998	JF224A (JD224A)		384 Gbps Fabric with additional 12 1000BASE-X SFP
<u>0231A933</u>	<u>JD193B (JC699A)</u>		<u>384G Switch Fabric, with 2 10GBASE-X (XFP)</u>
<u>0231A0AE</u>	<u>JD191A (JC713A)</u>		<u>8-port 10GBASE-X Extended (XFP)</u>
0231A973	JD232A (JC716A) (See note 3.)		4 port 10GBASE-X Enhanced (XFP)
0231A977	JD235A (JC719A)		4 port 10GBASE-X Extended (XFP)
<u>0231A974</u>	<u>JD233A</u>		<u>2-port 10GBASE-X (XFP) Enhanced</u>

Table 1. HP to 3Com Switch Product Cross-Reference (continued)

3Com Switch Subcomponent (See note 1.)	HP Switch Subcomponent (See note 1.)	Function
0231A978	JD236A	2-port 10GBASE-X (XFP) Extended
0231A92Q	JD201A	S7900E 2-Port 10GBASE-X (XFP)
0231A76P	JD200A	1-port 10GBASE-X XFP
0231A92W	JE147A (JD199B)	48-port 10/100/1000BASE-TX
NA	JD229B (JC712A) (See note 4.)	48 port Gig-T PoE+
0231A48J	JD192A (See note 5.)	Dual Inline Memory Module (DIMM)
0231A930	JE150A (JD210A) (JC709A) (See note 4.)	48-Port 10/100/1000BASE-T Module
0231A92X	JD221A	48-Port 1000BASE-X Module(SFP)
0231A972	JD231A (JC715A) (See note 4.)	24-port 100/1000BASE-X Combo Enhanced (SFP)
0231A975	JD234A (JC718A) (See note 4.)	24-port 100/1000BASE-X Extended (SFP)
0231A932	JE152A (JD204B)	24-Port 10/100/1000BASE-T Module (RJ45)
0231A90F	JD223A	24-Port 1000BASE-X/100BASE-FX Module with 8 Combo Ports (SFP)
0231A931	JE151A (JD203B) (JC704A) (See note 4.)	24-Port 1000BASE-X Module (SFP)
0231A971	JD230A (JD714A) (See note 4.)	24-port 1000BASE-X Combo (SFP) with 2-port 10GBASE-X Extended (XFP)
0231A76V	JD206A	24-port 10/100/1000BASE-T (RJ45) with 2-port 10GBASE-X Module (XFP)
0231A92N	JD205A	24-Port 1000BASE-X (SFP) and 2-Port 10GBASE-X Module (XFP)

NOTES:

- Components bolded and underlined were tested by JITC. The other components in the family series were not tested; however, they utilize the same software and hardware and JITC analysis determined them to be functionally identical for interoperability certification purposes and they are also certified for joint use.
- DTR 4 updated the software from the originally certified Release 5.20 to Release 5.20.R6701.
- DTR 2 incorrectly specified SKU JC716A with JD233A. This DTR corrected the error by listing SKU JC716A with JD232A.
- This DTR and DTR 2 were requested to include TAA SKU numbers in parenthesis next to the SKU numbers they are identical to. These products are identical to the ones tested; however, they have a different site of manufacture.
- The 0231A92W/JE147A 48-port 10/100/1000BASE-TX Ethernet card includes two optional DIMM modules (part number 0231A48J/JD192A). This card is certified for joint use with or without the DIMM modules. Each module provides Power over Ethernet for 24 ports.

LEGEND:

DIMM	Dual Inline Memory Module	PWR	Power over Ethernet
DTR	Desktop Review	SFP	Small Form Factor Pluggable
Gbps	Gigabits per second	SKU	Stock Keeping Unit
HP	Hewlett Packard	TAA	Trade Agreements Act
JITC	Joint Interoperability Test Command	XFP	10 Gigabit Small Form Factor Pluggable

4. Table 2 provides the SUT’s interface status. The SUT capability and functional requirements are listed in Table 3.

Table 2. SUT Interface Status

Interface	Applicability			CRs/FRs (See note 1.)	Status		
	Co	D	A		Co	D	A
Network Management Interfaces for Core Layer Switches							
EIA/TIA-232 (Serial)	R	R	R	EIA/TIA-232	Met	Met	Met
IEEE 802.3i (10BaseT UTP)	C	C	C	1, 6-15, 18-28, 31, 32-36, 48-53, 58-60, 65, 67-71	Not Tested (See note 2.)		
IEEE 802.3u (100BaseT UTP)	C	C	C	1, 6-15, 18-28, 31, 32-36, 48-53, 58-60, 65, 67-71	Met (See note 3.)	Met (See note 3.)	Met (See note 3.)
IEEE 802.3ab (1000BaseT UTP)	C	C	C	1, 6-15, 18-28, 31, 32-36, 48-53, 58-60, 65, 67-71	Met (See note 3.)	Met (See note 3.)	Met (See note 3.)

Table 2. SUT Interface Status (continued)

Interface	Applicability			CRs/FRs (See note 1.)	Status		
	Co	D	A		Co	D	A
Uplink Interfaces for Core Layer Switches							
IEEE 802.3u (100BaseT UTP)	R	R	R	1-15, 16, 18-24, 28-31, 40, 44-53, 55-60, 65-75	Met (See notes 3, 4.)	Met (See notes 3, 4.)	Met (See notes 3, 4.)
IEEE 802.3u (100BaseFX)	C	C	C	1-6, 11, 16, 18-24, 28-31, 40-41, 44-53, 55-60, 65-75	Met (See notes 3, 4.)	Met (See notes 3, 4.)	Met (See notes 3, 4.)
IEEE 802.3ab (1000BaseT UTP)	C	C	C	1-16, 18-24, 28-31, 40, 44-53, 55-60, 65-75	Met (See notes 3, 4.)	Met (See notes 3, 4.)	Met (See notes 3, 4.)
IEEE 802.3z (1000BaseX Fiber)	R	R	C	1-5, 8-16, 18-24, 28-31, 40, 44-53, 55-60, 65-75	Met (See notes 3, 4.)	Met (See notes 3, 4.)	Met (See notes 3, 4.)
IEEE 802.3ae (10GBaseX)	C	C	C	1-5, 8-16, 18, 19, 40-41, 44-53, 55-60, 65-75	Met (See notes 3, 4.)	Met (See notes 3, 4.)	Met (See notes 3, 4.)
Access Interfaces for Core Layer Switches							
IEEE 802.3i (10BaseT UTP)	C	C	R	1-15, 18-24, 28-41, 44-54, 58-71	Met (See notes 3, 5.)	Met (See notes 3, 5.)	Met (See notes 3, 5.)
IEEE 802.3u (100BaseT UTP)	R	R	R	1-15, 18-24, 28-41, 44-54, 58-71	Met (See notes 3, 5.)	Met (See notes 3, 5.)	Met (See notes 3, 5.)
IEEE 802.3u (100BaseFX)	C	C	C	1-6, 11, 18-24, 28-31, 44-54, 58-71	Met (See notes 3, 5.)	Met (See notes 3, 5.)	Met (See notes 3, 5.)
IEEE 802.3ab (1000BaseT UTP)	C	C	C	1-15, 18-24, 28-41, 44-54, 58-71	Met (See notes 3, 5.)	Met (See notes 3, 5.)	Met (See notes 3, 5.)
IEEE 802.3z (1000BaseX Fiber)	R	R	C	1-6, 11, 18-24, 28-31, 44-54, 58-71	Met (See notes 3, 5.)	Met (See notes 3, 5.)	Met (See notes 3, 5.)
Generic Requirements for all Interfaces							
Generic Requirements not associated with specific interfaces	R	R	R	30-32, 35, 36, 40, 69-71	Met	Met	Met
DoD IPv6 Profile Requirements	R	R	R	UCR Section 5.3.5.5	Met (See notes 3, 4, 5.)	Met (See notes 3, 4, 5.)	Met (See notes 3, 4, 5.)
Security	R	R	R	UCR Sections 5.3.1.3.8, 5.3.1.5, 5.3.1.6, and 5.4	Met (See note 6.)	Met (See note 6.)	Met (See note 6.)
NOTES:							
<p>1. The SUT's specific capability and functional requirement ID numbers depicted in the CRs/FRs column can be cross-referenced in Table 3. These requirements are for the following HP switches, which are certified in the ASLAN Core, Distribution, and Access layers: <u>A7510, A7506, A7506-V, and A7503</u>. JITC tested the devices that are bolded and underlined. The other devices listed that are not bolded or underlined are in the same family series as the SUT were not tested; however, they utilize the same OS software and hardware and JITC analysis determined them to be functionally identical for interoperability certification purposes.</p> <p>2. This interface is not offered by the SUT. This is not a required interface for a core, distribution, or access switch.</p> <p>3. During the original interoperability test, the SUT did not support the following IPv6 RFC: 4007 for ID number 53 depicted in Table 3. DISA adjudicated this as minor on 3 May 2010 with the stipulation that the vendor provide a POAM. The vendors original POAM stated they would comply by 1 October 2011 with a software update. DTR 4 includes Release 5.20.R6701, which is compliant to this RFC based on the vendor's LOC.</p> <p>4. During the original interoperability test, the SUT did not support the following authentication RFC: 2404 for ID number 74 depicted in Table 3. DISA adjudicated this as minor on 3 May 2010 with the stipulation that the vendor provide a POAM. The vendors original POAM stated they would comply by 1 January 2011 with a software update. DTR 4 includes Release 5.20.R6701, which is compliant to this RFC based on the vendor's LOC.</p> <p>5. During the original interoperability test, the SUT did not support the following IPv6 RFC: 3315 for ID number 54 depicted in Table 3. This requirement is conditional with support of DHCP and does not apply to the SUT.</p> <p>6. Security testing is accomplished via DISA-led Information Assurance test teams and published in a separate report, Reference (f).</p>							

Table 2. SUT Interface Status (continued)

LEGEND:			
802.3ab	1000BaseT Gbps Ethernet over twisted pair at 1 Gbps (125 Mbps)	DISA	Defense Information Systems Agency
802.3ae	10 Gbps Ethernet	EIA	Electronic Industries Alliance
802.3i	10BaseT Mbps over twisted pair	EIA-232	Standard for defining the mechanical and electrical characteristics for connecting Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE)
802.3u	Standard for carrier sense multiple access with collision detection at 100 Mbps		data communications devices
802.3z	Gigabit Ethernet Standard	FRs	Functional Requirements
10BaseT	10 Mbps (Baseband Operation, Twisted Pair) Ethernet	Gbps	Gigabits per second
100BaseT	100 Mbps (Baseband Operation, Twisted Pair) Ethernet	ID	Identification
100BaseFX	100 Mbps Ethernet over fiber	ICMP	Internet Control Message Protocol
1000BaseFX	1000 Mbps Ethernet over fiber	IEEE	Institute of Electrical and Electronics Engineers
1000BaseT	1000 Mbps (Baseband Operation, Twisted Pair) Ethernet	IPv6	Internet Protocol version 6
10GBaseX	10000 Mbps Ethernet over Category 5 Twisted Pair Copper	JITC	Joint Interoperability Test Command
A	Access	Mbps	Megabits per second
ASLAN	Assured Services Local Area Network	OS	Operating System
C	Conditional	POAM	Plan of Action and Milestones
Co	Core	R	Required
CRs	Capability Requirements	RFCs	Request for Comments
D	Distribution	SUT	System Under Test
		TIA	Telecommunications Industry Association
		UCR	Unified Capabilities Requirements
		UTP	Unshielded Twisted Pair

Table 3. SUT Capability and Functional Requirements

ID	Requirement (See note.)	UCR Reference	
1	ASLAN components can have no single point of failure for >96 users for C2 and Special C2 users. Non-ASLAN components can have a single point of failure for C2(R) and non-C2 users. (R)	5.3.1.2.1, 5.3.1.7.7	
2	Non-blocking of any voice or video traffic at 50%. (R)	5.3.1.3	
3	Maximum of 1 ms of jitter for all ASLAN components. (R)	5.3.1.3	
4	Maximum of 0.02% packet loss for core and distribution layer components and 0.01% for access layer components. (R)	5.3.1.3	
5	Maximum of 2 ms latency for core and distribution layer components and 2 ms for access layer components. (R)	5.3.1.3	
6	100 Mbps IAW IEEE 802.3u and 1 Gbps IAW IEEE 802.3z for core and distribution layer components and 10 Mbps IAW IEEE 802.3i and 100 Mbps IAW IEEE 802.3u for access layer components. (R)	5.3.1.3.1	
7	Force mode and auto-negotiation IAW IEEE 802.3, filtering IAW RFC 1812, and flow control IAW IEEE 802.3x. (R)	5.3.1.3.2	
8	Port Parameter Requirements	5.3.1.3.2	
9			Auto-negotiation IAW IEEE 802.3. (R)
10			Force mode IAW IEEE 802.3. (R)
11			Flow control IAW IEEE 802.3x. (R)
12			Filtering IAW RFC 1812. (R)
13			Link Aggregation IAW IEEE 802.3ad (output/egress ports only). (R)
14			Spanning Tree Protocol IAW IEEE 802.1D. (R)
15			Multiple Spanning Tree IAW IEEE 802.1s. (R)
16	Rapid Reconfiguration of Spanning Tree IAW IEEE 802.1w. (R)		
16	LACP link Failover and Link Aggregation IAW IEEE 802.3ad (uplink ports only). (R)	5.3.1.3.2, 5.3.1.7.7.1	
17	Class of Service Marking: Layer 3 DSCPs IAW RFC 2474. (R) Layer 2 3-bit user priority field of the IEEE 802.1Q 2-byte TCI field. (C)	5.3.1.3.3	
18	VLAN Capabilities IAW IEEE 802.1Q. (R)	5.3.1.3.4	
19	Protocols IAW DISR profile (IPv4 and IPv6). IPv4 (R: LAN Switch, Layer 2 Switch): IPv6 (R: LAN Switch, C: Layer 2 Switch). Note: Layer 2 switch is required to support only RFC 2460, 5095, 2464, and be able to queue packets based on DSCPs in accordance with RFC 2474.	5.3.1.3.5	
20	QoS Features	5.3.1.3.6	
21			Shall support minimum of 4 queues. (R)
22			Must be able to assign VLAN tagged packets to a queue. (R)
23			Support DSCP PHBs per RFCs 2474, 2494, 2597, 2598, and 3246. (R: LAN Switch). Note: Layer 2 switch is required to support RFC 2474 only.
24			Support a minimum of one of the following: Weighted Fair Queuing (WFQ) IAW RFC 3662, Priority Queuing (PQ) IAW RFC 1046, or Class-Based WFQ IAW RFC 3366. (R)
24	Must be able to assign a bandwidth or percent of traffic to any queue. (R)		

Table 3. SUT Capability and Functional Requirements (continued)

ID	Requirement (See note.)		UCR Reference
25	Network Monitoring	SNMP IAW RFC's 1157, 2206, 3410, 3411, 3412, 3413, and 3414. (R)	5.3.1.3.7
26		SNMP traps IAW RFC1215. (R)	
27		Remote monitoring IAW RFC1281 and Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model IAW RFC 3826. (R)	
28	Product Requirements Summary IAW UCR2008 Table 5.3.1-5. (R)		5.3.1.3.9
29	E2E Performance (Voice)	No more than 5 ms Latency over any 5-minute period measured under congestion. (R)	5.3.1.4.1
		No more than 3 ms Jitter over any 5-minute period measured under congestion. (R)	
		Packet loss not to exceed engineered (queuing) parameters over any 5-minute period under congestion. (R)	
30	E2E Performance (Video)	No more than 30 ms Latency over any 5-minute period measured under congestion. (R)	5.3.1.4.2
		No more than 30 ms Jitter over any 5-minute period measured under congestion. (R)	
		Packet loss not to exceed engineered (queuing) parameters over any 5-minute period under congestion. (R)	
31	E2E Performance (Data)	No more than 50 ms Latency over any 5-minute period measured under congestion (R)	5.3.1.4.3
		Packet loss not to exceed engineered (queuing) parameters over any 5-minute period under congestion. (R)	
32	LAN Network Management	Configuration Control for ASLAN and non-ASLAN. (R)	5.3.1.6.1
33		Operational Controls for ASLAN and non-ASLAN. (R)	5.3.1.6.2
34		Performance Monitoring for ASLAN and non-ASLAN. (R)	5.3.1.6.3
35		Alarms for ASLAN and non-ASLAN. (R)	5.3.1.6.4
36		Reporting for ASLAN and non-ASLAN. (R)	5.3.1.6.5
37	Redundancy	Redundant Power Supplies. (Required on standalone redundant products.)	5.3.1.7.7
38		Chassis Failover. (Required on standalone redundant products.)	
39		Switch Fabric Failover. (Required on standalone redundant products.)	
40		Non-LACP Link Failover.(R)	
41		Fiber Blade Failover. (R)	
42		Stack Failover. (C) (Required if the stack supports more than 96 users.)	
43		CPU (routing engine) blade Failover. (R)	
44	MPLS	MPLS May not add measurable Loss or Jitter to system. (C)	5.3.1.8.4.1
45		MPLS Conforms to RFCs in Table 5.3.1-14. (C)	5.3.1.8.4.1
46		MPLS Support L2 and L3 VPNs. (C)	5.3.1.8.4.2.1 /2
47	IPv6 Product Requirements: Dual Stack for IPv4 and IPv6 IAW RFC 4213 if routing functions are supported. (C)		5.3.5.4
48	IPv6 System Requirements	Support IPv6 IAW RFCs 2460 and 5095 if routing functions are supported. (C)	5.3.5.4
49		Support IPv6 packets over Ethernet IAW RFC2464. (R)	5.3.5.4
50		Support MTU discovery IAW RFC 1981 if routing functions are supported. (C)	5.3.5.4.1
51		Support a minimum MTU of 1280 IAW RFCs 2460 and 5095. (R)	5.3.5.4.1
52		Shall support IPv6 addresses IAW RFC4291. (R)	5.3.5.4.3
53		Shall support IPv6 scoped addresses IAW RFC4007. (R)	5.3.5.4.3
54		if routing functions are supported: If DHCP is supported must be IAW RFC3315, if DHCPv6 is supported it shall be IAW RFC 3313. (C)	5.3.5.4.4
55	IPv6 Router Advertisements	If the system supports routing functions, the system shall inspect valid router advertisements sent by other routers and verify that the routers are advertising consistent information on a link and shall log any inconsistent router advertisements, and shall prefer routers that are reachable over routers whose reachability is suspect or unknown (C).	5.3.5.4.5.2
56		If the system supports routing functions, the system shall include the MTU value in the router advertisement message for all links in accordance with RFC 2461 and RFC 4861. (C)	
57		IPv6 Neighbor Discovery: The system shall not set the override flag bit in the neighbor advertisement message for solicited advertisements for anycast addresses or solicited proxy advertisements. (R)	
58	IPv6 Neighbor Discovery	if routing functions are supported: Neighbor discovery IAW RFCs 2461 and 4861. (C)	5.3.5.4.5
59		The system shall not set the override flag bit in the neighbor advertisement message for solicited advertisements for anycast addresses or solicited proxy advertisements. (R)	
60		The system shall set the override flag bit in the neighbor advertisement message to "1" if the message is not an anycast address or a unicast address for which the system is providing proxy service. (R)	

Table 3. SUT Capability and Functional Requirements (continued)

ID	Requirement (See note.)	UCR Reference
61	If the system supports stateless IP address Auto-configuration, the system shall support IPv6 SLAAC for interfaces supporting UC functions in accordance with RFC 2462 and RFC 4862.(C)	5.3.5.4.6
62	If the product supports IPv6 SLAAC, the product shall have a configurable parameter that allows the function to be enabled and disabled. (C)	
63	If the product supports IPv6 SLAAC, the product shall have a configurable parameter that allows the “managed address configuration” flag and the “other stateful configuration” flag to always be set and not perform stateless auto-configuration. (C)	
64	If the product supports stateless IP address auto-configuration including those provided for the commercial market, the DAD shall be disabled in accordance with RFC 2462 and RFC 4862.(C)	
65	The system shall support manual assignment of IPv6 addresses. (R)	
66	If the system provides routing functions, the system shall default to using the “managed address configuration” flag and the “other stateful flag” set to TRUE in their router advertisements when stateful auto-configuration is implemented. (C)	
67	The system shall support the ICMPv6 as described in RFC 4443. (R)	5.3.5.4.7
68	The system shall have a configurable rate limiting parameter for rate limiting the forwarding of ICMP messages. (R)	
69	The system shall support the capability to enable or disable the ability of the system to generate a Destination Unreachable message in response to a packet that cannot be delivered to its destination for reasons other than congestion. (R) Required if LS supports routing functions.	
70	The system shall support the enabling or disabling of the ability to send an Echo Reply message in response to an Echo Request message sent to an IPv6 multicast or anycast address (C). Required if LS supports routing functions.	
71	The system shall validate ICMPv6 messages, using the information contained in the payload, prior to acting on them (C). Required if LS supports routing functions.	
72	If the system supports routing functions, the system shall support the OSPF for IPv6 as described in RFC 2740 (C).	5.3.5.4.8
73	If the system supports routing functions, the system shall support securing OSPF with Internet Protocol Security (IPSec) as described for other IPSec instances in UCR 2008, Section 5.4 (C).	
74	If the system supports routing functions, the system shall support OSPF for IPv6 as described in RFC 2740, router to router integrity using IP authentication header with HMAC-SHA1-96 with ESP and AH as described in RFC 2404, shall support OSPFv3 IAW RFC 4552 (C).	
75	If the system supports routing functions, the system shall support the Multicast Listener Discovery (MLD) process as described in RFC 2710 and extended in RFC 3810 (C).	
76	Engineering Requirements: Physical Media for ASLAN and non-ASLAN. (R) (Site requirement)	5.3.1.7.1
77	Battery Back up two hours for non-ASLAN components and eight hours for ASLAN components. (R) (Site requirement)	5.3.1.7.5
78	Availability of 99.999 percent (Special C2), and 99.997 percent (C2) for ASLAN (R), and 99.9 percent (non-C2 and C2(R) for non-ASLAN. (R) (Site requirement)	5.3.1.7.6
79	Port-Based access Control IAW IEEE 802.1x (R)	5.3.1.3.2
80	Secure methods for network configuration. SSH2 instead of Telnet and support RFCs 4251-4254. Must use HTTPS instead of http, and support RFCs 2660 and 2818 for ASLAN and non-ASLAN. (R)	5.3.1.6
81	Security (R)	5.3.1.3.8
82	Must meet IA requirements IAW UCR 2008 Section 5.4 for ASLAN and non-ASLAN. (R)	5.3.1.5

NOTE: All requirements are for core, distribution, and access layer components unless otherwise specified.

Table 3. SUT Capability and Functional Requirements (continued)

LEGEND:					
ASLAN	Assured Services Local Area Network	HTTP	Hypertext Transfer Protocol	ms	millisecond
C	Conditional	HTTPS	Hyper Text Transfer Protocol, Secure	MTU	Maximum Transmission Unit
C2	Command and Control	IA	Information Assurance	OSPF	Open Shortest Path First
C2(R)	Command and Control ROUTINE only	IAW	In Accordance with	OSPFv3	Open Shortest Path First Version 3
CPU	Central Processing Unit	ICMP	Internet Control Message Protocol	PHB	Per Hop Behavior
DAD	Duplicate Address Detection	ICMPv6	Internet Control Message Protocol for IPv6	QoS	Quality of Service
DHCP	Dynamic Host Configuration Protocol	ID	Identification	R	Required
DHCPv6	Dynamic Host Configuration Protocol for IPv6	IEEE	Institute of Electrical and Electronics Engineers	RFC	Request for Comments
DISR	Department of Defense Information Technology Standards Registry	IPv4	Internet Protocol version 4	SLAAC	Stateless Auto Address Configuration
DSCP	Differentiated Services Code Point	IPv6	Internet Protocol version 6	SNMP	Simple Network Management Protocol
E2E	End-to-End	LACP	Link Aggregation Control Protocol	SSH2	Secure Shell Version 2
HMAC	Hash-based Message Authentication Code	LAN	Local Area Network	SUT	System Under Test
		LS	LAN Switch	TCI	Tag Control Information
		Mbps	Megabits per second	UC	Unified Capabilities
		MPLS	Multiprotocol Label Switching	UCR	Unified Capabilities Requirements
				VLAN	Virtual Local Area Network
				VPN	Virtual Private Network

5. No detailed test report was developed in accordance with the Program Manager's request. JITC distributes interoperability information via the JITC Electronic Report Distribution (ERD) system, which uses Unclassified-But-Sensitive Internet Protocol Router Network (NIPRNet) e-mail. More comprehensive interoperability status information is available via the JITC System Tracking Program (STP). STP is accessible by .mil/gov users on the NIPRNet at <https://stp.fhu.disa.mil>. Test reports, lessons learned, and related testing documents and references are on the JITC Joint Interoperability Tool (JIT) at <http://jit.fhu.disa.mil> (NIPRNet). Due to the sensitivity of the information, the Information Assurance Accreditation Package (IAAP) that contains the approved configuration and deployment guide must be requested directly through government civilian or uniformed military personnel from the Unified Capabilities Certification Office (UCCO), e-mail: disa.meade.ns.list.unified-capabilities-certification-office@mail.mil. All associated data is available on the DISA UCCO website located at <http://www.disa.mil/Services/Network-Services/UCCO>.

6. The JITC point of contact is CPT James Torres, DSN 879-5575, commercial (520) 538-5575, FAX DSN 879-4347, or e-mail to james.m.torres.mil@mail.mil. The JITC's mailing address is P.O. Box 12798, Fort Huachuca, AZ 85670-2798. The Tracking Number for the SUT is 0920503.

FOR THE COMMANDER:

Enclosure a/s


 for RICHARD A. MEADOR
 Chief
 Battlespace Communications Portfolio

JITC Memo, JTE, Extension of the Special Interoperability Test Certification of the Hewlett Packard (HP) A7500 Series Release 5.20.R6701

Distribution (electronic mail):

DoD CIO

Joint Staff J-6, JCS

USD(AT&L)

ISG Secretariat, DISA, JTA

U.S. Strategic Command, J665

US Navy, OPNAV N2/N6FP12

US Army, DA-OSA, CIO/G-6 ASA(ALT), SAIS-IOQ

US Air Force, A3CNN/A6CNN

US Marine Corps, MARCORSSYSCOM, SIAT, A&CE Division

US Coast Guard, CG-64

DISA/TEMC

DIA, Office of the Acquisition Executive

NSG Interoperability Assessment Team

DOT&E, Netcentric Systems and Naval Warfare

Medical Health Systems, JMIS IV&V

HQUSAISEC, AMSEL-IE-IS

UCCO

ADDITIONAL REFERENCES

- (c) Office of the Assistant Secretary of Defense, "Department of Defense Unified Capabilities Requirements 2008 Change 1," 22 January 2010
- (d) Joint Interoperability Test Command, "Defense Switched Network Generic Switch Test Plan (GSTP), Change 2," 2 October 2006
- (e) Joint Interoperability Test Command, Memo, JTE, "Special Interoperability Test Certification of the Hewlett Packard (HP) A7500 Series with Release 5.20," 25 March 2011
- (f) Joint Interoperability Test Command, "Information Assurance (IA) Assessment of 3Com S7900E (Tracking Number 0920503)," 23 November 2010
- (g) Joint Interoperability Test Command, Memo, JTE, "Special Interoperability Test Certification of the 3Com Switch 7900 Series with Release 5.20," 23 November 2010