



DEFENSE INFORMATION SYSTEMS AGENCY

P. O. BOX 549
FORT MEADE, MARYLAND 20755-0549

IN REPLY
REFER TO: Joint Interoperability Test Command (JTE)

28 Aug 13

SUBJECT: Extension of the Joint Interoperability Certification of the Juniper Networks MX240, MX480, and MX960 Switch Series with Software Release Junos 12.2 to add the MX-MPC3E-3D-R-B and MIC3-3D-1X100GE-CXP modules

References: (a) Department of Defense (DoD) Directive 4630.05, "Interoperability and Supportability of Information Technology (IT) and National Security Systems (NSS)," 5 May 2004
(b) DoD Instruction 8100.04, "DoD Unified Capabilities (UC)," 9 December 2010
(c) through (e), see Enclosure

1. References (a) and (b) establish the Defense Information Systems Agency (DISA), Joint Interoperability Test Command (JITC), as the responsible organization for interoperability test certification.

2. The Juniper Networks MX240, MX480, and MX960 switch series with software release Junos 12.1 is hereinafter referred to as the system under test (SUT). The SUT meets all of its critical interoperability requirements and is certified for joint use within the Defense Information Systems Network (DISN) as an Assured Services Local Area Network (ASLAN) Core, Distribution, and Layer 2/Layer 3 Access switch. The SUT was also tested and certified for Multiprotocol Label Switching (MPLS) and Layer 2/Layer 3 Virtual Private Networks (VPNs). The SUT is certified as interoperable for joint use with other ASLAN components listed on the Unified Capabilities (UC) Approved Products List (APL) with the following interfaces: 10/100/1000BaseT and 100/1000BaseX for access, and 1000BaseT and 1000/10000BaseX for uplink. All of these interfaces were tested with the exception of the 10BaseT interface. JITC analysis determined that the 10BaseT interface is a low risk for certification based on the vendor's Letter of Compliance (LoC) to comply with the Institute of Electrical and Electronics Engineers (IEEE) 802.3i standard and the testing data collected at all other data rates. The SUT meets the critical interoperability requirements set forth in Reference (c), using test procedures derived from Reference (d). The Juniper switches listed under components in Table 1 all employ the same software and similar hardware as the SUT. JITC analysis determined these systems to be functionally identical to the SUT for interoperability certification purposes, and they are also certified for joint use.

The SUT is certified to support Assured Services within an ASLAN. If a component meets the minimum requirements for deployment in an ASLAN, it also meets the lesser requirements for deployment in a non-ASLAN. Non-ASLANs are "commercial grade" and provide support to Command and Control (C2) (ROUTINE only calls) (C2(R)) or non-C2 voice subscribers. When deployed in a non-ASLAN, the SUT may also be used to receive all levels of precedence, but is limited to supporting calls that are originated at ROUTINE precedence only. Non-ASLANs do not meet the availability or redundancy requirements for C2 or Special C2 users and therefore are not authorized to support precedence calls originated above ROUTINE.

JITC Memo, JTE, Extension of the Joint Interoperability Certification of the Juniper Networks MX240, MX480, and MX960 Switch Series with Software Release Junos 12.2 to add the MX-MPC3E-3D-R-B and MIC3-3D-1X100GE-CXP modules

Testing of the SUT did not include video services or data applications; however, simulated video traffic, preferred data, and best effort data were generated during testing to determine the SUT's ability to prioritize and properly queue voice media and signaling traffic. No other configurations, features, or functions, except those cited within this document, are certified by JITC. This certification expires upon changes that affect interoperability but no later than three years from the date of this memorandum (25 March 2013).

3. The extension of this certification is based upon Desktop Review (DTR) 3. The original certification, documented in Reference (e) is based on interoperability testing conducted by the United States Army Information Systems Engineering Command, Technology Integration Center (USAISEC TIC), review of the vendor's LoC, DISA adjudication of open test discrepancy reports (TDRs), and the DISA Certifying Authority (CA) Recommendation. The interoperability testing was conducted by the USAISEC TIC, Fort Huachuca, Arizona, from 30 July through 13 November 2012. Review of the vendor's LoC was completed on 4 December 2012. The DISA adjudication of outstanding TDRs was completed on 11 February 2013. The DISA CA provided a positive recommendation on 20 November 2012, based on the security testing completed by USAISEC TIC-led information assurance (IA) test teams. The IA test results are published in a separate report, Reference (f). This DTR was requested to add the MX-MPC3E-3D-R-B and MIC3-3D-1X100GE-CXP modules to the existing certification. The MX-MPC3E-3D-R-B is identical from a hardware perspective to the MX-MPC3E-3D, which was tested and certified under DTR2. The "-R-B" suffix indicates a different version of software license that supports larger routing table scaling. The MIC3-3D-1X100GE-CXP module is nearly identical in hardware design to the MIC3-3D-1X100GE-CFP, which was tested and certified under DTR2. The MIC3-3D-1X100GE-CXP module differs from the MIC3-3D-1X100GE-CFP module in that it is designed to support CXP (short range) optical versus CFP (long range) optical and therefore the physical interfaces differ in size. No previous interoperability discrepancies were closed. JITC determined that the risk was minor in approving this DTR without further interoperability testing since the new modules are identical or nearly identical in hardware design to previously tested modules. The DISA CA provided a positive recommendation on 20 November 2012, based on the security testing completed by USAISEC TIC-led information assurance (IA) test teams. The IA test results are published in a separate report, Reference (f). This DTR 3 request required no additional IA testing. The original IA approval applies to this DTR. Therefore, JITC approves this DTR.

4. Table 1 provides a UC APL product summary. Table 2 provides the SUT interface interoperability status and Table 3 provides the Capability Requirements (CRs) and Functional Requirements (FRs) status. The threshold CRs/FRs for ASLAN components are established by Section 5.3.a of Reference (c) and were used to evaluate the interoperability of the SUT.

JITC Memo, JTE, Extension of the Joint Interoperability Certification of the Juniper Networks MX240, MX480, and MX960 Switch Series with Software Release Junos 12.2 to add the MX-MPC3E-3D-R-B and MIC3-3D-1X100GE-CXP modules

Table 1. UC APL Product Summary

Component (See note 1.)	Release (See note 2.)	Sub-Component (See note 1.)	Certification Applicability																																						
			Core	Distribution	Access																																				
MX960BASE-AC MX960BASE-AC-ECM MX960BASE-DC MX960BASE-DC-ECM MX960-PREMIUM2-AC MX960-PREMIUM2-AC-ECM MX960-PREMIUM2-DC MX960-PREMIUM2-DC-ECM MX960-PREMIUM-AC MX960-PREMIUM-AC-ECM MX960-PREMIUM-DC MX960-PREMIUM-DC-ECM <u>MX480BASE-AC</u> MX480BASE-DC <u>MX480-PREMIUM2-AC</u> MX480-PREMIUM2-DC MX480-PREMIUM-AC MX480-PREMIUM-DC MX240BASE-AC-HIGH MX240BASE-AC-LOW MX240BASE-DC MX240-PREMIUM2-AC-HIGH MX240-PREMIUM2-AC-LOW MX240-PREMIUM2-DC MX240-PREMIUM-AC-HIGH MX240-PREMIUM-AC-LOW MX240-PREMIUM-DC	JUNOS OS 12.2	RE-S-1300-2048, <u>RE-S-2000-4096</u> , RE-S-1800X2-8G, RE-S-1800X2-16G, RE-S-1800X4-8G, <u>RE-S-1800X4-16G</u> , <u>SCB-MX960</u> , <u>SCBE-MX</u> , <u>DPCE-R-20GE-2XGE</u> , <u>DPCE-R-2XGE-XFP</u> , <u>DPCE-R-40GE-SFP</u> , <u>DPCE-R-40GE-TX</u> , <u>DPCE-R-4XGE-XFP</u> , <u>DPCE-R-Q-20GE-2XGE</u> , <u>DPCE-R-Q-20GE-SFP</u> , <u>MPC-3D-16XGE-SFPP-R</u> , MPC-3D-16XGE-SFPP (See note 3.), MX-MPC1E-3D (See note 3.), MX-MPC1E-3D-Q (See note 3.), MX-MPC1E-3D-Q-R-B, <u>MX-MPC1E-3D-R-B</u> , MX-MPC2E-3D (See note 3.), MX-MPC2E-3D-EQ (See note 3.), MX-MPC2E-3D-EQ-R-B, MX-MPC2E-3D-P (See note 3.), MX-MPC2E-3D-P-Q-B (See note 3.), MX-MPC2E-3D-P-Q-R-B, MX-MPC2E-3D-P-R-B, MX-MPC2E-3D-Q (See note 3.), MX-MPC2E-3D-Q-R-B, <u>MX-MPC2E-3D-R-B</u> , <u>MIC-3D-20GE-SFP</u> , <u>MIC-3D-2XGE-XFP</u> , <u>MIC-3D-40GE-TX</u> , <u>MIC-3D-4XGE-XFP</u> , <u>MS-DPC</u> , MX-MPC3E-3D (See note 4.), MIC3-3D-1X100GE-CFP (See note 4.), MIC3-3D-2X40GE-QSFPP (See note 4.) MX-MPC3E-3D-R-B (see Note 5), MIC3-3D-1X100GE-CXP (see Note 6)	Yes	Yes	Yes																																				
<p>NOTES:</p> <ol style="list-style-type: none"> Components bolded and underlined were tested by the USAISEC TIC. The other components in the family series were not tested; however, they utilize the same OS software and similar hardware. JITC analysis determined them to be functionally identical for interoperability certification purposes and they are also certified for joint use. The SUT was updated to JUNOS from 12.1 to 12.2 with Desktop Review 1. JUNOS Release 12.2 is required to support the 40 GE MICs. Noted Trio (3D) cards without the "-R" designation are reduced scale, L3 switching cards that do not support MPLS L3 VPN (RFC 2547) with their basic licensing. Additional licensing must be applied to these cards to enable the full L3 scale capabilities of the card, to include support for MPLS L3 VPN (RFC 2547). The MX-MPC3E-3D Modular Port Concentrator and the 100 GE and 40GE MICs which install in the MPC3E line card were added with Desktop Review 2, which included a multi-vendor test event. The MX-MPC3E-3D-R-B is identical from a hardware perspective to the MX-MPC3E-3D, which was tested and certified under DTR2. The "-R-B" suffix indicates a different version of software license that supports larger routing table scaling. The MIC3-3D-1X100GE-CXP module is nearly identical in hardware design to the MIC3-3D-1X100GE-CFP, which was tested and certified under DTR2. The MIC3-3D-1X100GE-CXP module differs from the MIC3-3D-1X100GE-CFP module in that it is designed to support CXP (short range) optical versus CFP (long range) optical and therefore the physical interfaces differ in size. <p>LEGEND:</p> <table> <tr> <td>APL</td> <td>Approved Products List</td> <td>MPLS</td> <td>Multiprotocol Label Switching</td> </tr> <tr> <td>CFP</td> <td>C (100 Gb) Form-factor Pluggable</td> <td>OS</td> <td>Operating System</td> </tr> <tr> <td>CXP</td> <td>C (100 Gb/12 Lane) eXtended-capability Pluggable</td> <td>TIC</td> <td>Technology Integration Center</td> </tr> <tr> <td>DTR</td> <td>Desktop Review</td> <td>UC</td> <td>Unified Capabilities</td> </tr> <tr> <td>GE</td> <td>Gigabit Ethernet</td> <td>UCR</td> <td>Unified Capabilities Requirements</td> </tr> <tr> <td>JITC</td> <td>Joint Interoperability Test Command</td> <td>USAISEC</td> <td>U.S. Army Information Systems Engineering Command</td> </tr> <tr> <td>JUNOS</td> <td>Juniper Operating System</td> <td>VPN</td> <td>Virtual Private Network</td> </tr> <tr> <td>L3</td> <td>Layer 3</td> <td></td> <td></td> </tr> <tr> <td>MIC</td> <td>Modular Interface Card</td> <td></td> <td></td> </tr> </table>						APL	Approved Products List	MPLS	Multiprotocol Label Switching	CFP	C (100 Gb) Form-factor Pluggable	OS	Operating System	CXP	C (100 Gb/12 Lane) eXtended-capability Pluggable	TIC	Technology Integration Center	DTR	Desktop Review	UC	Unified Capabilities	GE	Gigabit Ethernet	UCR	Unified Capabilities Requirements	JITC	Joint Interoperability Test Command	USAISEC	U.S. Army Information Systems Engineering Command	JUNOS	Juniper Operating System	VPN	Virtual Private Network	L3	Layer 3			MIC	Modular Interface Card		
APL	Approved Products List	MPLS	Multiprotocol Label Switching																																						
CFP	C (100 Gb) Form-factor Pluggable	OS	Operating System																																						
CXP	C (100 Gb/12 Lane) eXtended-capability Pluggable	TIC	Technology Integration Center																																						
DTR	Desktop Review	UC	Unified Capabilities																																						
GE	Gigabit Ethernet	UCR	Unified Capabilities Requirements																																						
JITC	Joint Interoperability Test Command	USAISEC	U.S. Army Information Systems Engineering Command																																						
JUNOS	Juniper Operating System	VPN	Virtual Private Network																																						
L3	Layer 3																																								
MIC	Modular Interface Card																																								

JITC Memo, JTE, Extension of the Joint Interoperability Certification of the Juniper Networks MX240, MX480, and MX960 Switch Series with Software Release Junos 12.2 to add the MX-MPC3E-3D-R-B and MIC3-3D-1X100GE-CXP modules

Table 2. SUT Interface Interoperability Status

Interface	Applicability			UCR 2008, Change 3 Reference	Threshold CR/FR (See note 1.)	Status	Remarks
	Co	D	A				
Serial	C	C	C	5.3.1.3.9	1-4	Not Certified (See note 3.)	N/A
10Base-X	C	C	C (See note 2.)	5.3.1.3.1	1-6	Certified (See note 4.)	The SUT met CRs and FRs with the following IEEE standard: 802.3i (10BaseT).
100Base-X	R	R	C (See note 2.)	5.3.1.3.1	1-6	Certified	The SUT met CRs and FRs with the following IEEE standard: 802.3u (100BaseT).
1000Base-X	R	R	C (See note 2.)	5.3.1.3.1	1-6	Certified	The SUT met CR and FRs with the following IEEE standards: 802.3ab (1000BaseT), 802.3z (1000Base-SX, 1000Base-LX).
10000Base-X	C	C	C	5.3.1.3.1	1-6	Certified	The SUT met CRs and FRs with the following IEEE standard: 802.3ae (10GBase-SR, 10GBase-LR).
40000Base-X	C	C	C	5.3.1.3.1	1-6	Certified (See note 5.)	The SUT met CRs and FRs with the following IEEE standard: 802.3ba 2010 (40/100Gbps).
100000Base-X	C	C	C	5.3.1.3.1	1-6	Certified (See note 5.)	The SUT met CRs and FRs with the following IEEE standard: 802.3ba 2010 (40/100Gbps).
802.11a	C	C	C	5.3.1.3.1/5.3.1.7.2	1-6	Not Tested	(See note 6.)
802.11b	C	C	C	5.3.1.3.1/5.3.1.7.2	1-6	Not Tested	(See note 6.)
802.11g	C	C	C	5.3.1.3.1/5.3.1.7.2	1-6	Not Tested	(See note 6.)
802.11n	C	C	C	5.3.1.3.1/5.3.1.7.2	1-6	Not Tested	(See note 6.)
802.16	C	C	C	5.3.1.3.1/5.3.1.7.2	1-6	Not Tested	(See note 6.)

NOTES:

1. The SUT high-level CR and FR ID numbers depicted in the Threshold CRs/FRs column can be cross-referenced in Table 3. These high-level CR/FR requirements refer to a detailed list of requirements provided in Enclosure 3.
2. Core and Distribution products must minimally support 802.3u (100Base-X) and 802.3z (1000Base-X). Access products must minimally support one of the following standards: 802.3i (10BaseT), 802.3j (10BaseF), 802.3u (100BaseT/F), 802.3z (1000BaseF), or 802.3ab (1000BaseT). Other rates and standards may be provided as conditional interfaces.
3. The SUT does support this interface for Command Line Interface (CLI) connectivity during initial setup only. This interface was not tested and is not certified for UC connectivity use.
4. The USAISEC TIC tested all these interfaces with the exception of the 10BaseT interface. JITC analysis determined that the 10BaseT interface is a low risk for certification based on the vendor's LoC to the IEEE 802.3i and the testing data collected at all other data rates.
5. This interface was included with Desktop Review 2, which included the 40 and 100 Gbps cards listed in Table 1. The 40 Gbps card requires Release JUNOS 12.2.
6. The SUT does not support this interface. The interface was not tested, therefore, is not certified for use.

JITC Memo, JTE, Extension of the Joint Interoperability Certification of the Juniper Networks MX240, MX480, and MX960 Switch Series with Software Release Junos 12.2 to add the MX-MPC3E-3D-R-B and MIC3-3D-1X100GE-CXP modules

Table 2. SUT Interface Interoperability Status (continued)

LEGEND:		A	Access
802.3ab	1000BaseT Gbps Ethernet Over Twisted Pair at 1Gbps (125 Mbps)	C	Conditional
802.3ae	10 Gbps Ethernet	Co	Core
802.3i	10BaseT Mbps Over Twisted Pair	CR	Capability Requirement
802.3j	10 Mbps Over Fiber	D	Distribution
802.3u	Standard for Carrier Sense Multiple Access with Collision Detection at 100 Mbps	EIA	Electronic Industries Alliance
802.3z	Gigabit Ethernet Standard	EIA-232	Standard for Defining the Mechanical and Electrical Characteristics for Connecting Data Terminal Equipment (DTE) and Data Circuit-Terminating Equipment (DCE)
802.11/16	IEEE Wireless Standards		Data Communications Devices
10BaseF	10 Mbps Ethernet Over Fiber	FR	Functional Requirement
10BaseT	10 Mbps (Baseband Operation, Twisted Pair) Ethernet	Gbps	Gigabits Per Second
10Base-X	10 Mbps Ethernet Over Fiber or Copper	ID	Identification
100BaseF	100 Mbps Ethernet Over Fiber	IEEE	Institute of Electrical and Electronics Engineers
100BaseT	100 Mbps (Baseband Operation, Twisted Pair) Ethernet	JITC	Joint Interoperability Test Command
100Base-X	100 Mbps Ethernet Over Fiber or Copper	LoC	Letter of Compliance
1000BaseF	1000 Mbps Ethernet Over Fiber	LR	Long Range Optics
1000Base-LX	1000 Mbps Ethernet Over Fiber	LX	Single-Mode Fiber Optics
1000Base-SX	1000 Mbps Ethernet Over Fiber	Mbps	Megabits Per Second
1000BaseT	1000 Mbps (Baseband Operation, Twisted Pair) Ethernet	N/A	Not Applicable
1000Base-X	1000 Mbps Ethernet Over Fiber or Copper	R	Required
10000Base-X	10000 Mbps Ethernet Over Fiber or Copper	SR	Short Range Optics
10GBase-LR	10000 Mbps Ethernet Over Fiber	SX	Multi-Mode Fiber Optics
10GBase-SR	10000 Mbps Ethernet Over Fiber	SUT	System Under Test
		TIC	Technology Integration Center
		UCR	Unified Capabilities Requirements
		USAISEC	U.S. Army Information Systems Engineering Command

Table 3. SUT CRs and FRs Status

CR/FR ID	Capability/Function	Applicability (See note 1.)	UCR 2008, Change 3 Reference	Status
1	General Performance Parameters			
	Performance Parameters	Required	5.3.1.3	Met
	Port Interface Rates	Required	5.3.1.3.1	Met
	Port Parameter Requirements	Required	5.3.1.3.2	Met (See note 2.)
	Class of Service Markings	Required	5.3.1.3.3	Met
	VLAN Capabilities	Required	5.3.1.3.4	Met
	Protocols	Required	5.3.1.3.5	Partially Met (See note 3.)
	QoS Features	Required	5.3.1.3.6	Met
	Network Monitoring	Required	5.3.1.3.7	Met
	Security	Required	5.3.1.3.8	Met (See note 4.)
2	E2E Performance Requirements			
	Voice Services	Required	5.3.1.4.1	Met (See note 5.)
	Video Services	Required	5.3.1.4.2	Met (See note 5.)
	Data Services	Required	5.3.1.4.3	Met (See note 5.)
3	NM Requirements			
	Configuration Control	Required	5.3.1.6.1	Met
	Operational Changes	Required	5.3.1.6.2	Met
	Performance Monitoring	Required	5.3.1.6.3	Met
	Alarms	Required	5.3.1.6.4	Met
	Reporting	Required	5.3.1.6.5	Met

JITC Memo, JTE, Extension of the Joint Interoperability Certification of the Juniper Networks MX240, MX480, and MX960 Switch Series with Software Release Junos 12.2 to add the MX-MPC3E-3D-R-B and MIC3-3D-1X100GE-CXP modules

Table 3. SUT CRs and FRs Status (continued)

4	Engineering Requirements																																															
	Physical Media	Required	5.3.1.7.1	Met (See Note 6)																																												
	Wireless	Conditional	5.3.1.7.2	Not Tested (See Note 7)																																												
	Traffic Engineering	Required	5.3.1.7.3	Met (See Note 6)																																												
	Availability	Required	5.3.1.7.6	Met (See Note 6)																																												
	Redundancy	Required	5.3.1.7.7	Met (See Note 6)																																												
5	MPLS																																															
	MPLS Requirements	Conditional	5.3.1.8.4.1	Partially Met (See Note 3)																																												
	MPLS VPN Augmentation to VLANs	Conditional	5.3.1.8.4.2	Met																																												
6	IPv6 Requirements																																															
	Product Requirements	Required	5.3.5.4	Partially Met (See Note 3)																																												
<p>NOTES:</p> <p>1. The annotation of “required” refers to a high-level requirement category. The applicability of each sub-requirement is provided in Reference (e), Enclosure 3. The SUT does not need to provide conditional requirements. However, if a capability is provided, it must function according to the specified requirements.</p> <p>2. When port duplex is manually set on 10/100/1000 speed interfaces, SUT does not indicate the state of the duplex through the command line. DISA adjudicated this as a minor impact with a Condition of Fielding outlined in the Juniper MX Series Deployment Guide.</p> <p>3. The SUT does not comply with the following protocols:</p> <ul style="list-style-type: none"> a. RFC5798: Partial Comply - Virtual Router Redundancy Protocol (VRRP) Version 3 for IPv4 and IPv6. JUNOS 12.2, the next new software release, does support VRRP which will be submitted for verification and validation testing through UCCO Desktop Review process. DISA has adjudicated this discrepancy as having a minor operational impact and accepted the vendor’s POA&M. b. RFC 2737: Partial Comply - MIB (Entity). DISA adjudicated this as a minor impact with no POA&M required. c. RFC 4502: Partial Comply - RMON MIB. DISA adjudicated this as a minor impact with no POA&M required. d. RFC 3479 (MPLS): Non Comply – Fault Tolerance for the Label Distribution Protocol (LDP). JUNOS 12.1 does provide support for RFC 3478, Graceful Restart for LDP, which protects against LDP control plane failures. DISA has adjudicated this discrepancy as having minor operational impact with a Condition of Fielding that Juniper uses RFC3478 in lieu of RFC3479. <p>4. Security testing was accomplished via USAISEC TIC-led IA test teams and published in a separate report, Reference (e).</p> <p>5. This requirement was verified and met using simulated voice, video, and data traffic in an operational emulated environment to meet E2E requirements. The SUT must be deployed IAW deployment guide and engineering guidelines in UCR 2008, Change 3, Section 5.3.1.4.</p> <p>6. This requirement was met with the following stipulations: It is the site’s responsibility to configure the SUT in a manner which meets the engineering requirements listed in Reference (e), Enclosure 2, Section 11.2 d, and that it does not create a single point of failure which could impact more than 96 C2 users.</p> <p>7. Wireless requirements are conditional, were not tested, and, therefore, are not certified for use.</p> <p>LEGEND:</p> <table border="0"> <tr> <td>ASLAN</td> <td>Assured Services Local Area Network</td> <td>MIB</td> <td>Management Information Base</td> </tr> <tr> <td>C2</td> <td>Command and Control</td> <td>MPLS</td> <td>Multiprotocol Label Switching</td> </tr> <tr> <td>CR</td> <td>Capability Requirement</td> <td>NM</td> <td>Network Management</td> </tr> <tr> <td>DISA</td> <td>Defense Information Systems Agency</td> <td>POA&M</td> <td>Plan of Action and Milestones</td> </tr> <tr> <td>E2E</td> <td>End-to-End</td> <td>QoS</td> <td>Quality of Service</td> </tr> <tr> <td>FR</td> <td>Functional Requirement</td> <td>RFC</td> <td>Request For Comment</td> </tr> <tr> <td>IAW</td> <td>In Accordance With</td> <td>RMON</td> <td>Remote Monitoring</td> </tr> <tr> <td>ID</td> <td>Identification</td> <td>SUT</td> <td>System Under Test</td> </tr> <tr> <td>IPv4</td> <td>Internet Protocol Version 4</td> <td>UCR</td> <td>Unified Capabilities Requirements</td> </tr> <tr> <td>IPv6</td> <td>Internet Protocol Version 6</td> <td>VLAN</td> <td>Virtual Local Area Network</td> </tr> <tr> <td>JUNOS</td> <td>Juniper Operating System</td> <td>VPN</td> <td>Virtual Private Network</td> </tr> </table>					ASLAN	Assured Services Local Area Network	MIB	Management Information Base	C2	Command and Control	MPLS	Multiprotocol Label Switching	CR	Capability Requirement	NM	Network Management	DISA	Defense Information Systems Agency	POA&M	Plan of Action and Milestones	E2E	End-to-End	QoS	Quality of Service	FR	Functional Requirement	RFC	Request For Comment	IAW	In Accordance With	RMON	Remote Monitoring	ID	Identification	SUT	System Under Test	IPv4	Internet Protocol Version 4	UCR	Unified Capabilities Requirements	IPv6	Internet Protocol Version 6	VLAN	Virtual Local Area Network	JUNOS	Juniper Operating System	VPN	Virtual Private Network
ASLAN	Assured Services Local Area Network	MIB	Management Information Base																																													
C2	Command and Control	MPLS	Multiprotocol Label Switching																																													
CR	Capability Requirement	NM	Network Management																																													
DISA	Defense Information Systems Agency	POA&M	Plan of Action and Milestones																																													
E2E	End-to-End	QoS	Quality of Service																																													
FR	Functional Requirement	RFC	Request For Comment																																													
IAW	In Accordance With	RMON	Remote Monitoring																																													
ID	Identification	SUT	System Under Test																																													
IPv4	Internet Protocol Version 4	UCR	Unified Capabilities Requirements																																													
IPv6	Internet Protocol Version 6	VLAN	Virtual Local Area Network																																													
JUNOS	Juniper Operating System	VPN	Virtual Private Network																																													

5. No detailed test report was developed in accordance with the Program Manager's request. JITC distributes interoperability information via the JITC Electronic Report Distribution (ERD) system, which uses Unclassified-But-Sensitive Internet Protocol Router Network (NIPRNet)

JITC Memo, JTE, Extension of the Joint Interoperability Certification of the Juniper Networks MX240, MX480, and MX960 Switch Series with Software Release Junos 12.2 to add the MX-MPC3E-3D-R-B and MIC3-3D-1X100GE-CXP modules

e-mail. More comprehensive interoperability status information is available via the JITC System Tracking Program (STP). STP is accessible by .mil/gov users on the NIPRNet at <https://stp.fhu.disa.mil>. Test reports, lessons learned, and related testing documents and references are on the JITC Joint Interoperability Tool (JIT) at <http://jit.fhu.disa.mil> (NIPRNet). Due to the sensitivity of the information, the Information Assurance Accreditation Package (IAAP) that contains the approved configuration and deployment guide must be requested directly through government civilian or uniformed military personnel from the Unified Capabilities Certification Office (UCCO), e-mail: disa.meade.ns.list.unified-capabilities-certification-office@mail.mil. All associated data is available on the DISA UCCO website located at [website located at http://www.disa.mil/Services/Network-Services/UCCO](http://www.disa.mil/Services/Network-Services/UCCO).

6. The testing point of contact Mr. James Hatch, DSN 821-2860, commercial (520) 533-2860, or email to james.d.hatch12.civ@mail.mil. The JITC point of contact is Ms. Anita Brown, DSN 879-5164, commercial (520) 538-5164, or e-mail to anita.l.brown53.civ@mail.mil. JITC's mailing address is P.O. Box 12798, Fort Huachuca, AZ 85670-2798. The UCCO tracking number for the SUT is 1124204.

FOR THE COMMANDER:



Enclosure a/s

for RICHARD A. MEADOR
Chief
Battlespace Communications Portfolio

DISTRIBUTION (electronic mail):

DoD CIO
Joint Staff J-6, JCS
USD(AT&L)
ISG Secretariat, DISA, JTA
U.S. Strategic Command, J665
US Navy, OPNAV N2/N6FP12
US Army, DA-OSA, CIO/G-6 ASA(ALT), SAIS-IOQ
US Air Force, A3CNN/A6CNN
US Marine Corps, MARCORSSYSCOM, SIAT, A&CE Division
US Coast Guard, CG-64
DISA/TEMC
DIA, Office of the Acquisition Executive
NSG Interoperability Assessment Team
DOT&E, Netcentric Systems and Naval Warfare
Medical Health Systems, JMIS IV&V
Defense Information Systems Agency, NS23

ADDITIONAL REFERENCES

- (c) Office of the DoD Chief Information Officer, "Department of Defense Unified Capabilities Requirements 2008, Change 3," September 2011
- (d) Joint Interoperability Test Command, "ASLAN Component Test Plan (UCTP)," February 2012
- (e) Joint Interoperability Test Command, Memo, JTE, "Joint Interoperability Certification of the Juniper Networks MX240, MX480, and MX960 Switch Series with Software Release Junos 12.1," 25 March 2013
- (f) U.S. Army Information Systems Engineering Command, Technology Integration Center (USAISEC TIC), "Information Assurance (IA) Assessment of Juniper MX240/480/960 Junos 12.1 (Tracking Number 1124204)," 23 October 2012