



DEFENSE INFORMATION SYSTEMS AGENCY

P. O. BOX 549
FORT MEADE, MARYLAND 20755-0549

IN REPLY
REFER TO: Joint Interoperability Test Command (JTE)

28 Sep 12

MEMORANDUM FOR DISTRIBUTION

SUBJECT: Extension of the Special Interoperability Test Certification of Network Equipment Technologies (NET) Promina 800 from Software Release 4.x5.03, Version 95.55 to Software Release 4.x5.04, Version 95.56 and NET Promina 400 from Software Release 4.x5.03, Version 105.55 to Software Release 4.x5.04, Version 105.56

References: (a) DOD Directive 4630.05, "Interoperability and Supportability of Information Technology (IT) and National Security Systems (NSS)," 5 May 2004
(b) CJCSI 6212.01E, "Interoperability and Supportability of Information Technology and National Security Systems," 15 December 2008
(c) through (f), see Enclosure

1. References (a) and (b) establish the Defense Information Systems Agency (DISA), Joint Interoperability Test Command (JITC), as the responsible organization for interoperability test certification.

2. The NET Promina 800 with Software Release 4.x5.03, Version 95.55 and NET Promina 400 with Software Release 4.x5.03, Version 105.55 are hereinafter referred to as the System Under Test (SUT). The SUT meets all of its critical interoperability requirements and is certified as interoperable for joint use within the Defense Information Systems Network (DISN) as a Deployable Network Element and Fixed Network Element as set forth in Reference (c) with some limitations, which are discussed as follows:

- The SUT is certified for joint use within the DISN with the following access interfaces: Digital Transmission Link Level 1 (T1) Channel Associated Signaling (CAS), Primary Rate Interface (PRI), Signaling System 7 (SS7), European Basic Multiplex Rate (E1) CAS, PRI, SS7, and Electronic Industries Alliance (EIA)-530 Serial.
- The SUT also has two transport interfaces that are certified for joint use within the DISN: EIA-530 Serial, and Trunk 3 (T1 only).
- Additionally, the Asynchronous Transfer Mode (ATM) Optical Carrier Level 3 (OC-3) transport interface is certified only with the Promina 800. The Promina 400 does not have an ATM OC-3 interface and, therefore, was not certified for that interface.
- The T1 access interface of the Primary Rate Card (PRC) with Primary Voice Secure (PVS) is only certified for clear channel mode over the Trunk 3 transport interface.
- The T1 access interface of the Primary Voice Secure - Enhanced (PVS-E) is certified for Channel Associated Signaling and clear channel mode with 9.6 Kilobits per second compression over the Trunk 3 transport interface.

JITC Memo, JTE, Extension of the Special Interoperability Test Certification of Network Equipment Technologies (NET) Promina 800 from Software Release 4.x5.03, Version 95.55 to Software Release 4.x5.04, Version 95.56 and NET Promina 400 from Software Release 4.x5.03, Version 105.55 to Software Release 4.x5.04, Version 105.56

- The SUT is interoperable in mated pairs with the Promina NX-1000 provided both the SUT and the NX-1000 are loaded with the same certified software release.

The SUT meets the critical interoperability requirements set forth in Reference (c) and testing was conducted using test procedures derived from Reference (d). No other configurations, features, or functions, except those cited within this report, are certified by the JITC. This certification expires upon changes that affect interoperability, but no later than three years from the date of the Unified Capabilities Approved Products List memorandum (2 March 2012).

3. The extension of this certification is based upon Desktop Review (DTR) 1. The original certification is based on interoperability testing, review of the vendor’s Letters of Compliance (LoC), and DISA Certifying Authority (CA) accreditation. Interoperability testing was conducted by JITC at the Global Information Grid Network Test Facility, Fort Huachuca, Arizona, from 12 September through 10 November 2011 and documented in Reference (e). Review of the vendor’s LoC was completed on 29 November 2011. DISA CA granted accreditation on 15 February 2012 based on the security testing completed by DISA-led Information Assurance (IA) test teams and published in a separate report, Reference (f). This DTR was requested to update the certified Promina 800 release from 4.x5.03, Version 95.55 to Release 4.x5.04, Version 95.56 and the certified Promina 400 release from 4.x5.03, Version 105.55 to Release 4.x5.04, Version 105.56, which only includes fixes for IA findings found during the initial IA test event. JITC conducted interoperability and IA verification and validation (V&V) testing in support of this DTR from 16 through 20 April 2012. The DISA CA approved the new configuration on 4 September 2012, based on review of the DISA-led IA test teams updated report, Reference (f). There is no modification to the functionality or interoperability of the SUT. Therefore, JITC approves this DTR.

4. The SUT Interoperability Test Summary is shown in Table 1 and the Capability and Feature Requirements used to evaluate the interoperability of the SUT are indicated in Table 2. The interoperability test status is based on the SUT’s ability to meet:

- DISN services for Network and Applications specified in Reference (c).
- The overall system interoperability performance derived from test procedures listed in Reference (d).

Table 1. SUT Interoperability Test Summary

DISN Access Interfaces			
Interface & Signaling	Critical	Status	Remarks
T1 CAS (AMI/SF) DTMF, MFR1	No ¹	Certified	Met all CRs and FRs.
T1 CAS (B8ZS/ESF) DTMF, MFR1	No ¹	Certified	Met all CRs and FRs.
T1 PRI (ANSI T1.607/T1.619a)	No ¹	Certified	Met all CRs and FRs.
T1 SS7 (ANSI T1.619a)	No ¹	Certified	Met all CRs and FRs.
E1 CAS (HDB3) DTMF, MFR1	No ¹ (Europe only)	Certified	Met all CRs and FRs.

JITC Memo, JTE, Extension of the Special Interoperability Test Certification of Network Equipment Technologies (NET) Promina 800 from Software Release 4.x5.03, Version 95.55 to Software Release 4.x5.04, Version 95.56 and NET Promina 400 from Software Release 4.x5.03, Version 105.55 to Software Release 4.x5.04, Version 105.56

Table 1. SUT Interoperability Test Summary (continued)

DISN Access Interfaces			
Interface & Signaling	Critical	Status	Remarks
E1 ISDN PRI (ITU-T Q.931/Q.955.3)	No ¹ (Europe only)	Certified	Met all CRs and FRs.
E1 SS7 (ANSI T1.619a)	No ¹ (Europe only)	Certified	Met all CRs and FRs.
Serial (EIA-530)	No ¹	Certified	Met all CRs and FRs.
DISN Transport Interfaces			
Transport Level	Critical	Status	Remarks
Serial (EIA-530) SA-TRK	No ²	Certified	Met all CRs and FRs.
T1 TRK- 3	No ²	Certified ³	Met all CRs and FRs.
ATM OC-3	No ²	Certified ⁴	Met all CRs and FRs.
Features And Capabilities			
Features And Capabilities	Critical	Status	Remarks
Synchronization	Yes	Certified	Met all CRs and FRs.
Network Management	Yes	Certified	Met all CRs and FRs.
Security	Yes	Certified	Met all CRs and FRs ⁵ .

NOTES:

1. The UCR does not stipulate a minimum Access interface requirement for an F-NE or D-NE.
2. The UCR does not stipulate a minimum Transport interface requirement for an F-NE or D-NE.
3. The TRK-3 Transport offers T1, E1 and Serial back plane interfaces; however, only the T1 interfaces was tested and is certified for joint use within the DISN.
4. The ATM-OC3 Transport interface is only certified for joint use within the DISN with the NET Promina 800 only. The ATM-OC3 transport interface is not supported by the NET Promina 400.
5. Information assurance testing is accomplished via DISA-led Information Assurance test teams and published in a separate report, Reference (f).

LEGEND:

AMI	Alternate Mark Inversion	ISDN	Integrated Services Digital Network
ANSI	American National Standards Institute	ITU-T	International Telecommunication Union – Telecommunication Standardization Sector
B8ZS	Bipolar Eight Zero Substitution	MFR1	Multi-Frequency Recommendation 1
CAS	Channel Associated Signaling	PRI	Primary Rate Interface
CR	Capability Requirements	Q.931	Signaling Standard for ISDN
DCE	Data Circuit-Terminating Equipment	Q.955.3	ISDN Signaling Standard for E1 MLPP
DISA	Defense Information Systems Agency	SA -TRK	Symmetric Asymmetric-Trunk
DISN	Defense Information System Network	SF	Super Frame
D-NE	Deployable Network Element	SS7	Signaling System 7
DTE	Data Terminal Equipment	SUT	System Under Test
DTMF	Dual Tone Multi-Frequency	T1	Digital Transmission Link Level 1 (1.544 Mbps)
E1	European Basic Multiplex Rate (2.048 Mbps)	T1.607	ISDN – Layer 3 Signaling Specification for Circuit Switched Bearer Service for DSS1
EIA	Electronic Industries Alliance	T1.619a	SS7 and ISDN MLPP Signaling Standard for T1
EIA-530	Standard for 25-position interface for DTE and DCE employing serial binary data interchange	TRK-3	Trunk-3
ESF	Extended Super Frame	UCR	Unified Capabilities Requirements
F-NE	Fixed Network Element		
FR	Feature Requirements		

JITC Memo, JTE, Extension of the Special Interoperability Test Certification of Network Equipment Technologies (NET) Promina 800 from Software Release 4.x5.03, Version 95.55 to Software Release 4.x5.04, Version 95.56 and NET Promina 400 from Software Release 4.x5.03, Version 105.55 to Software Release 4.x5.04, Version 105.56

Table 2. SUT CR and FR Interoperability Requirements

DISN Access Interfaces			
Interface	Critical	Requirements Required or Conditional	References
T1 CAS (AMI/SF) DTMF, MFR1	No ¹	<ul style="list-style-type: none"> • DS1 Interface Characteristics (C) • DS1 Supervisory Channel Associated Signaling (C) 	<ul style="list-style-type: none"> • UCR Section 5.9.2.3.4 • UCR Section 5.9.2.3.4
T1 CAS (B8ZS/ESF) DTMF, MFR1	No ¹	<ul style="list-style-type: none"> • DS1 Clear Channel Capability (C) • DS1 Alarm and Restoral Requirements (C) 	<ul style="list-style-type: none"> • UCR Section 5.9.2.3.4 • UCR Section 5.9.2.3.4
T1 PRI (ANSI T1.607/T1.619a)	No ¹	<ul style="list-style-type: none"> • E1 Interface Characteristics (C) • E1 Supervisory Channel Associated Signaling (C) • E1 Clear Channel Capability (C) 	<ul style="list-style-type: none"> • UCR Section 5.9.2.3.5 • UCR Section 5.9.2.3.5 • UCR Section 5.9.2.3.5
T1 SS7 (ANSI T1.619a)	No ¹	<ul style="list-style-type: none"> • E1 Alarm and Restoral Requirements (C) • MOS (R) (F-NE Only) • MOS (R) (D-NE Only) 	<ul style="list-style-type: none"> • UCR Section 5.9.2.3.5 • UCR Section 5.9.2.1 • UCR Section 5.9.3.1
E1 CAS (HDB3) DTMF, MFR1	No ¹	<ul style="list-style-type: none"> • BERT (R) (F-NE Only) • BERT (R) (D-NE Only) 	<ul style="list-style-type: none"> • UCR Section 5.9.2.1 • UCR Section 5.9.3.1
E1 ISDN PRI (ITU-T Q.931/Q.955.3)	No ¹	<ul style="list-style-type: none"> • Secure Transmission (Voice and Data) (R) (F-NE Only) • Secure Transmission (Voice and Data) (R) (D-NE Only) 	<ul style="list-style-type: none"> • UCR Section 5.9.2.1 • UCR Section 5.9.3.8
E1 SS7 (ANSI T1.619a)	No ¹	<ul style="list-style-type: none"> • Modem (R) • Facsimile (R) • Call Control Signals (R) • Alarms (R) (F-NE Only) • Alarms (R) (D-NE Only) 	<ul style="list-style-type: none"> • UCR Section 5.9.2.1 • UCR Section 5.9.2.1 • UCR Section 5.9.2.1 • UCR Section 5.9.2.1.1 • UCR Section 5.9.3.5
Serial (EIA-530)	No ¹	<ul style="list-style-type: none"> • Call Congestion Control (R) (F-NE Only) • Call Congestion Control (R) (D-NE Only) • Call Congestion for TDM Transport (R) (D-NE Only) • Voice Compression (C) (F-NE Only) • Voice Compression (C) (D-NE Only) 	<ul style="list-style-type: none"> • UCR Section 5.9.2.1 • UCR Section 5.9.3.1 • UCR Section 5.9.3.4 • UCR Section 5.9.2.2 • UCR Section 5.9.3.1
DISN Transport Interfaces			
Interface	Critical	Requirements Required or Conditional	References
Serial (EIA-530) SA-TRK	No ²	<ul style="list-style-type: none"> • MOS (R) (F-NE Only) • MOS (R) (D-NE Only) • BERT (R) (F-NE Only) • BERT (R) (D-NE Only) • Secure Transmission (Voice and Data) (R) (F-NE Only) • Secure Transmission (Voice and Data) (R) (D-NE Only) • Modem (R) • Facsimile (R) • Call Control Signals (R) • Alarms (R) (F-NE Only) • Alarms (R) (D-NE Only) • Call Congestion Control (R) (F-NE Only) • Call Congestion Control (R) (D-NE Only) • Call Congestion for TDM Transport (R) (D-NE Only) • Voice Compression (C) (F-NE Only) • Voice Compression (C) (D-NE Only) • Delay (R) (F-NE Only) • Delay (R) (D-NE Only) 	<ul style="list-style-type: none"> • UCR Section 5.9.2.1 • UCR Section 5.9.3.1 • UCR Section 5.9.2.1 • UCR Section 5.9.3.1 • UCR Section 5.9.2.1 • UCR Section 5.9.2.1 • UCR Section 5.9.3.8 • UCR Section 5.9.2.1 • UCR Section 5.9.3.8 • UCR Section 5.9.2.1 • UCR Section 5.9.2.1.1 • UCR Section 5.9.3.5 • UCR Section 5.9.2.1 • UCR Section 5.9.3.1 • UCR Section 5.9.3.1 • UCR Section 5.9.3.4 • UCR Section 5.9.2.2 • UCR Section 5.9.3.1 • UCR Section 5.9.2.1.2.1 • UCR Section 5.9.3.3

JITC Memo, JTE, Extension of the Special Interoperability Test Certification of Network Equipment Technologies (NET) Promina 800 from Software Release 4.x5.03, Version 95.55 to Software Release 4.x5.04, Version 95.56 and NET Promina 400 from Software Release 4.x5.03, Version 105.55 to Software Release 4.x5.04, Version 105.56

Table 2. SUT CR and FR Interoperability Requirements (continued)

DISN Transport Interfaces			
Interface	Critical	Requirements Required or Conditional	References
T1 TRK-3	No ²	<ul style="list-style-type: none"> • DS1 Interface Characteristics (R) • MOS (R) (F-NE Only) • MOS (R) (D-NE Only) • BERT (R) (F-NE Only) • BERT (R) (D-NE Only) • Secure Transmission (Voice and Data) (R) (F-NE Only) • Secure Transmission (Voice and Data) (R) (D-NE Only) • Modem (R) • Facsimile (R) • Call Control Signals (R) • Alarms (R) (F-NE Only) • Alarms (R) (D-NE Only) • Call Congestion Control (R) (F-NE Only) • Call Congestion Control (R) (D-NE Only) • Call Congestion for TDM Transport (R) (D-NE Only) • Voice Compression (C) (F-NE Only) • Voice Compression (C) (D-NE Only) • Delay (R) (F-NE Only) • Delay (R) (D-NE Only) 	<ul style="list-style-type: none"> • UCR Section 5.9.2.3.4 • UCR Section 5.9.2.1 • UCR Section 5.9.3.1 • UCR Section 5.9.2.1 • UCR Section 5.9.3.1 • UCR Section 5.9.2.1 • UCR Section 5.9.3.8 • UCR Section 5.9.2.1 • UCR Section 5.9.2.1 • UCR Section 5.9.2.1 • UCR Section 5.9.2.1.1 • UCR Section 5.9.3.5 • UCR Section 5.9.2.1 • UCR Section 5.9.3.1 • UCR Section 5.9.3.4 • UCR Section 5.9.2.2 • UCR Section 5.9.3.1 • UCR Section 5.9.2.1.2.1 • UCR Section 5.9.3.3
ATM OC-3 NET Promina 800 only	No ²	<ul style="list-style-type: none"> • ANSI T1.105 (R) • GR-253-CORE (R) • MOS (R) (F-NE Only) • MOS (R) (D-NE Only) • BERT (R) (F-NE Only) • BERT (R) (D-NE Only) • Secure Transmission (Voice and Data) (R) (F-NE Only) • Secure Transmission (Voice and Data) (R) (D-NE Only) • Modem (R) • Facsimile (R) • Call Control Signals (R) • Alarms (R) (F-NE Only) • Alarms (R) (D-NE Only) • Call Congestion Control (R) (F-NE Only) • Call Congestion Control (R) (D-NE Only) • Call Congestion for TDM Transport (R) (D-NE Only) • Voice Compression (C) (F-NE Only) • Voice Compression (C) (D-NE Only) • Delay (R) (F-NE Only) • Delay (R) (D-NE Only) 	<ul style="list-style-type: none"> • UCR Section 5.5.3.4.2 • UCR Section 5.5.3.4.2 • UCR Section 5.9.2.1 • UCR Section 5.9.3.1 • UCR Section 5.9.2.1 • UCR Section 5.9.3.1 • UCR Section 5.9.2.1 • UCR Section 5.9.3.8 • UCR Section 5.9.2.1 • UCR Section 5.9.2.1 • UCR Section 5.9.2.1 • UCR Section 5.9.2.1.1 • UCR Section 5.9.3.5 • UCR Section 5.9.2.1 • UCR Section 5.9.3.1 • UCR Section 5.9.3.4 • UCR Section 5.9.2.2 • UCR Section 5.9.3.1 • UCR Section 5.9.2.1.2.1 • UCR Section 5.9.3.3

JITC Memo, JTE, Extension of the Special Interoperability Test Certification of Network Equipment Technologies (NET) Promina 800 from Software Release 4.x5.03, Version 95.55 to Software Release 4.x5.04, Version 95.56 and NET Promina 400 from Software Release 4.x5.03, Version 105.55 to Software Release 4.x5.04, Version 105.56

Table 2. SUT CR and FR Interoperability Requirements (continued)

SUT Features And Capabilities																																																																																															
Feature/Capability	Critical	Requirements Required or Conditional	References																																																																																												
Synchronization	Yes	<ul style="list-style-type: none"> • Timing (R) 	<ul style="list-style-type: none"> • UCR Section 5.9.2.3.7 																																																																																												
Network Management	Yes	<ul style="list-style-type: none"> • Management Option (R) <ul style="list-style-type: none"> Local Management (Front Panel and/or External Console) (C) ADIMSS (C) • Fault Management (C) • Loop Back Capability (C) • Operational Configuration Restoral (R) 	<ul style="list-style-type: none"> • UCR Section 5.9.2.4.1 • UCR Section 5.9.2.4.2 • UCR Section 5.9.2.4.3 • UCR Section 5.9.2.4.4 																																																																																												
Security	Yes	<ul style="list-style-type: none"> • STIGs and DoDI 8510.01 (DIACAP) (R) 	<ul style="list-style-type: none"> • UCR Section 5.9.2.6 																																																																																												
<p>NOTES:</p> <ol style="list-style-type: none"> 1. The UCR does not stipulate a minimum required DISN access interface. 2. The UCR does not stipulate a minimum required DISN transport interface. <p>LEGEND:</p> <table> <tr> <td>AMI</td> <td>Alternate Mark Inversion</td> <td>GR</td> <td>General Requirement</td> </tr> <tr> <td>ANSI</td> <td>American National Standards Institute</td> <td>HDB3</td> <td>High Density Bipolar Three</td> </tr> <tr> <td>ATM</td> <td>Asynchronous Transfer Mode</td> <td>ISDN</td> <td>Integrated Services Digital Network</td> </tr> <tr> <td>B8ZS</td> <td>Bipolar Eight Zero Substitution</td> <td>ITU-T</td> <td>International Telecommunication Union – Telecommunication Standardization Sector</td> </tr> <tr> <td>BERT</td> <td>Bit Error Rate Test</td> <td>MFR1</td> <td>Multi-Frequency Recommendation 1</td> </tr> <tr> <td>C</td> <td>Conditional</td> <td>MOS</td> <td>Mean Opinion Score</td> </tr> <tr> <td>CAS</td> <td>Channel Associated Signaling</td> <td>NET</td> <td>Network Equipment Technologies</td> </tr> <tr> <td>D-NE</td> <td>Deployable Network Element</td> <td>OC-3</td> <td>Optical Carrier Level 3</td> </tr> <tr> <td>DIACAP</td> <td>Department of Defense Information Assurance Certification and Accreditation Process</td> <td>PRI</td> <td>Primary Rate Interface</td> </tr> <tr> <td>DISN</td> <td>Defense Information System Network</td> <td>Q.931</td> <td>Signaling Standard for ISDN</td> </tr> <tr> <td>DoDI</td> <td>Department of Defense Instruction</td> <td>Q.955.3</td> <td>ISDN Signaling Standard for E1 MLPP</td> </tr> <tr> <td>DP</td> <td>Dial Pulse</td> <td>R</td> <td>Required</td> </tr> <tr> <td>DS1</td> <td>Digital Signal Level 1</td> <td>SA-TRK</td> <td>Symmetric Asymmetric-Trunk</td> </tr> <tr> <td>DSS1</td> <td>Digital Subscriber Signaling 1</td> <td>SF</td> <td>Super Frame</td> </tr> <tr> <td>DTMF</td> <td>Dual Tone Multi-Frequency</td> <td>SS7</td> <td>Signaling System 7</td> </tr> <tr> <td>E1</td> <td>European Basic Multiplex Rate (2.048 Mbps)</td> <td>STIG</td> <td>Security Technical Implementation Guides</td> </tr> <tr> <td>EIA</td> <td>Electronic Industries Alliance</td> <td>SUT</td> <td>System Under Test</td> </tr> <tr> <td>EIA-232</td> <td>Standard for defining the mechanical and electrical characteristics for connecting DTE and DCE data communications devices</td> <td>T1</td> <td>Digital Transmission Link Level 1 (1.544 Mbps)</td> </tr> <tr> <td>EIA-530</td> <td>Standard for 25-position interface for DTE and DCE employing serial binary data interchange</td> <td>T1.607</td> <td>ISDN – Layer 3 Signaling Specification for Circuit Switched Bearer Service for DSS1</td> </tr> <tr> <td>ESF</td> <td>Extended Super Frame</td> <td>T1.619a</td> <td>SS7 and ISDN MLPP Signaling Standard for T1</td> </tr> <tr> <td>F-NE</td> <td>Fixed Network Element</td> <td>TDM</td> <td>Time Division Multiplexing</td> </tr> <tr> <td></td> <td></td> <td>TRK-3</td> <td>Trunk-3</td> </tr> <tr> <td></td> <td></td> <td>UCR</td> <td>Unified Capabilities Requirements</td> </tr> </table>				AMI	Alternate Mark Inversion	GR	General Requirement	ANSI	American National Standards Institute	HDB3	High Density Bipolar Three	ATM	Asynchronous Transfer Mode	ISDN	Integrated Services Digital Network	B8ZS	Bipolar Eight Zero Substitution	ITU-T	International Telecommunication Union – Telecommunication Standardization Sector	BERT	Bit Error Rate Test	MFR1	Multi-Frequency Recommendation 1	C	Conditional	MOS	Mean Opinion Score	CAS	Channel Associated Signaling	NET	Network Equipment Technologies	D-NE	Deployable Network Element	OC-3	Optical Carrier Level 3	DIACAP	Department of Defense Information Assurance Certification and Accreditation Process	PRI	Primary Rate Interface	DISN	Defense Information System Network	Q.931	Signaling Standard for ISDN	DoDI	Department of Defense Instruction	Q.955.3	ISDN Signaling Standard for E1 MLPP	DP	Dial Pulse	R	Required	DS1	Digital Signal Level 1	SA-TRK	Symmetric Asymmetric-Trunk	DSS1	Digital Subscriber Signaling 1	SF	Super Frame	DTMF	Dual Tone Multi-Frequency	SS7	Signaling System 7	E1	European Basic Multiplex Rate (2.048 Mbps)	STIG	Security Technical Implementation Guides	EIA	Electronic Industries Alliance	SUT	System Under Test	EIA-232	Standard for defining the mechanical and electrical characteristics for connecting DTE and DCE data communications devices	T1	Digital Transmission Link Level 1 (1.544 Mbps)	EIA-530	Standard for 25-position interface for DTE and DCE employing serial binary data interchange	T1.607	ISDN – Layer 3 Signaling Specification for Circuit Switched Bearer Service for DSS1	ESF	Extended Super Frame	T1.619a	SS7 and ISDN MLPP Signaling Standard for T1	F-NE	Fixed Network Element	TDM	Time Division Multiplexing			TRK-3	Trunk-3			UCR	Unified Capabilities Requirements
AMI	Alternate Mark Inversion	GR	General Requirement																																																																																												
ANSI	American National Standards Institute	HDB3	High Density Bipolar Three																																																																																												
ATM	Asynchronous Transfer Mode	ISDN	Integrated Services Digital Network																																																																																												
B8ZS	Bipolar Eight Zero Substitution	ITU-T	International Telecommunication Union – Telecommunication Standardization Sector																																																																																												
BERT	Bit Error Rate Test	MFR1	Multi-Frequency Recommendation 1																																																																																												
C	Conditional	MOS	Mean Opinion Score																																																																																												
CAS	Channel Associated Signaling	NET	Network Equipment Technologies																																																																																												
D-NE	Deployable Network Element	OC-3	Optical Carrier Level 3																																																																																												
DIACAP	Department of Defense Information Assurance Certification and Accreditation Process	PRI	Primary Rate Interface																																																																																												
DISN	Defense Information System Network	Q.931	Signaling Standard for ISDN																																																																																												
DoDI	Department of Defense Instruction	Q.955.3	ISDN Signaling Standard for E1 MLPP																																																																																												
DP	Dial Pulse	R	Required																																																																																												
DS1	Digital Signal Level 1	SA-TRK	Symmetric Asymmetric-Trunk																																																																																												
DSS1	Digital Subscriber Signaling 1	SF	Super Frame																																																																																												
DTMF	Dual Tone Multi-Frequency	SS7	Signaling System 7																																																																																												
E1	European Basic Multiplex Rate (2.048 Mbps)	STIG	Security Technical Implementation Guides																																																																																												
EIA	Electronic Industries Alliance	SUT	System Under Test																																																																																												
EIA-232	Standard for defining the mechanical and electrical characteristics for connecting DTE and DCE data communications devices	T1	Digital Transmission Link Level 1 (1.544 Mbps)																																																																																												
EIA-530	Standard for 25-position interface for DTE and DCE employing serial binary data interchange	T1.607	ISDN – Layer 3 Signaling Specification for Circuit Switched Bearer Service for DSS1																																																																																												
ESF	Extended Super Frame	T1.619a	SS7 and ISDN MLPP Signaling Standard for T1																																																																																												
F-NE	Fixed Network Element	TDM	Time Division Multiplexing																																																																																												
		TRK-3	Trunk-3																																																																																												
		UCR	Unified Capabilities Requirements																																																																																												

5. No detailed test report was developed in accordance with the Program Manager’s request. JITC distributes interoperability information via the JITC Electronic Report Distribution (ERD) system, which uses Unclassified-But-Sensitive Internet Protocol Router Network (NIPRNet) e-mail. More comprehensive interoperability status information is available via the JITC System Tracking Program (STP). The STP is accessible by .mil/gov users on the NIPRNet at <https://stp.fhu.disa.mil>. Test reports, lessons learned, and related testing documents and references are on the JITC Joint Interoperability Tool (JIT) at <http://jit.fhu.disa.mil> (NIPRNet). Information related to DSN testing is on the Telecom Switched Services Interoperability (TSSI) website at <http://jitc.fhu.disa.mil/tssi>. Due to the sensitivity of the information, the Information Assurance Accreditation Package (IAAP) that contains the approved configuration and

JITC Memo, JTE, Extension of the Special Interoperability Test Certification of Network Equipment Technologies (NET) Promina 800 from Software Release 4.x5.03, Version 95.55 to Software Release 4.x5.04, Version 95.56 and NET Promina 400 from Software Release 4.x5.03, Version 105.55 to Software Release 4.x5.04, Version 105.56

deployment guide must be requested directly through government civilian or uniformed military personnel from the Unified Capabilities Certification Office (UCCO), e-mail: disa.meade.ns.list.unified-capabilities-certification-office@mail.mil.

6. The JITC point of contact is Capt Stéphane Arsenault, DSN 879-5269, commercial (520) 538-5269, FAX DSN 879-4347, or e-mail to Stephane.P.Arsenault.fm@mail.mil. The JITC's mailing address is P.O. Box 12798, Fort Huachuca, AZ 85670-2798. The tracking number for the SUT is 1023501.

FOR THE COMMANDER:



Enclosure a/s

for RICHARD A. MEADOR
Chief
Battlespace Communications Portfolio

Distribution (electronic mail):

DoD CIO
Joint Staff J-6, JCS
USD(AT&L)
ISG Secretariat, DISA, JTA
U.S. Strategic Command, J665
US Navy, OPNAV N2/N6FP12
US Army, DA-OSA, CIO/G-6 ASA(ALT), SAIS-IOQ
US Air Force, A3CNN/A6CNN
US Marine Corps, MARCORSSYSCOM, SIAT, A&CE Division
US Coast Guard, CG-64
DISA/TEMC
DIA, Office of the Acquisition Executive
NSG Interoperability Assessment Team
DOT&E, Netcentric Systems and Naval Warfare
Medical Health Systems, JMIS IV&V
HQUSAISEC, AMSEL-IE-IS
UCCO

ADDITIONAL REFERENCES

- (c) Defense Information Systems Agency (DISA), "Department of Defense Unified Capabilities Requirements 2008, Change 2," 31 December 2010
- (d) Joint Interoperability Test Command, "Defense Switched Network Generic Switch Test Plan (GSTP), Change 2," 2 October 2006
- (e) Joint Interoperability Test Command, Memo, JTE, "Special Interoperability Test Certification of Network Equipment Technologies (NET) Promina 800 with Software Release 4.x5.03, Version 95.55 and NET Promina 400 with Software Release 4.x5.03, Version 105.55," 29 February 2012
- (f) Joint Interoperability Test Command, "Information Assurance (IA) Assessment of NET Promina 800 with software Release 4.x5.03 Version 95.55, and Promina 400 with Software Release 4.x5.03 Version 105.55, (Tracking Number 1023501)," 20 January 2012