



DEFENSE INFORMATION SYSTEMS AGENCY

P. O. BOX 549
FORT MEADE, MARYLAND 20755-0549

IN REPLY
REFER TO: Joint Interoperability Test Command (JTE)

12 Dec 13

MEMORANDUM FOR DISTRIBUTION

SUBJECT: Extension of the Special Interoperability Test Certification of selected models from the Polycom High Definition Experience (HDX) family for the 9000 Series, 8000 High Definition (HD) Series, 7000 Series HD, 6000 HD, and 4000 HD Series with Software Release 2.7.0_J

References: (a) DoD Directive 4630.05, "Interoperability and Supportability of Information Technology (IT) and National Security Systems (NSS)," 5 May 2004
(b) CJCSI 6212.01E, "Interoperability and Supportability of Information Technology and National Security Systems," 15 December 2008
(c) through (g), see Enclosure 1

1. References (a) and (b) establish the Defense Information Systems Agency (DISA), Joint Interoperability Test Command (JITC), as the responsible organization for interoperability test certification.

2. The Polycom HDX 9004 and 9006 Rev. B Series, HDX 8000 HD Rev. A and B Series, HDX 7000 Rev. A, B and C Series, HDX 6000 HD, and HDX 4000 HD Rev. C Series with Software Release 2.7.0_J are hereinafter referred to as the System Under Test (SUT). The SUT meets all of its critical interface and functional interoperability requirements and is certified for joint use within the Defense Information Systems Network (DISN) as a Video Teleconferencing (VTC) system. The HDX 6000 HD codec (Internet Protocol [IP] only) is also certified, but not with Command and Control (C2) or Special C2 users unless the codec is connected to a certified IP to Time Division Multiplexing (TDM) gateway that interfaces with the Defense Switch Network. The Converged Management Application (CMA) provides remote centralized management of HDX video endpoints using a secure web interface and is certified as an optional management system with the SUT. The Polycom HDX 9002 and 9001 models employ the same software and similar hardware as the Polycom HDX 9004. The Polycom HDX 8006, 8004, and 8002 employ the same software and similar hardware as the Polycom HDX 8000 HD Rev A and B. The Polycom HDX 7002 and 7001 employ the same software and similar hardware as the Polycom HDX 7000 HD Rev A, B, and C. The Polycom HDX 4002 and 4001 employ the same software and similar hardware as the Polycom HDX 4000 HD. The JITC analysis determined these systems to be functionally identical to the SUT for interoperability certification purposes and they are also certified for joint use. A summary of all models certified is provided in Table 1.

JITC Memo, JTE, Extension of the Special Interoperability Test Certification of selected models from the Polycom High Definition Experience (HDX) family for the 9000 Series, 8000 High Definition (HD) Series, 7000 Series, 6000 HD, and 4000 HD Series using Software Release 2.7.0_J

The SUT also met the conditional requirements for an IP interface with the International Telecommunication Union – Telecommunication Standardization Sector (ITU-T) H.323 protocol; however, Assured Service is not yet defined for an IP interface with ITU-T H.323 protocol. Therefore, C2 VTC users and Special C2 VTC users are not authorized to be served by an IP interface with the ITU-T H.323 protocol. However, the SUT is certified for C2 and Special C2 VTC sessions via the TDM interfaces. The SUT meets the critical interoperability requirements set forth in Reference (c) using test procedures derived from Reference (d). No other configurations, features, or functions, except those cited within this report, are certified by the JITC. This certification expires upon changes that affect interoperability, but no later than three years from the date of the original Certifying Authority (CA) Recommendation (28 July 2011).

3. The extension of this certification is based upon Desktop Review (DTR) 3. The original certification, documented in Reference (e) is based on interoperability testing conducted by JITC, review of the vendor's Letters of Compliance (LoC), and DISA CA Recommendation. Interoperability testing was conducted by JITC at the Global Information Grid Network Test Facility, Fort Huachuca, Arizona, from 7 March through 25 March 2011. Review of the vendor's LoC was completed on 16 May 2011. The DISA CA provided a positive recommendation on 28 July 2011 based on the security testing completed by DISA-led IA test teams and published in separate reports, References (f) and (g). This DTR was requested to include Release 2.7.3_J, which includes the following three changes:

a. Support for the newest Pan/Tilt/Zoom camera. Mechanically there is no change to the camera or to its interoperability with HDX. However, there is a new integrated circuit in the camera (vice the previous camera), which also includes a new software driver.

b. Fix for a previous Plan of Action and Milestones (POA&M) for tagging IP management traffic.

c. Security vulnerabilities fixes.

JITC analysis determined that Verification and Validation (V&V) testing was required. JITC conducted V&V IO and IA testing from 7 October through 22 November 2013. JITC verified the functionality of the Pan/Tilt/Zoom camera. One previous interoperability discrepancy (listed in b above), i.e., the SUT did not properly tag Internet Protocol version 4 (IPv4) or Internet Protocol version 6 (IPv6) management traffic, was closed with this DTR. No new interoperability discrepancies were opened as a result of this V&V test. The validation of security fixes were documented in a separate report, Reference (f). The DISA CA provided a positive recommendation for this DTR on 5 November 2013, based on the security testing completed DISA-led IA test teams and published in a separate report, Reference (f). Therefore, JITC approves this DTR.

JITC Memo, JTE, Extension of the Special Interoperability Test Certification of selected models from the Polycom High Definition Experience (HDX) family for the 9000 Series, 8000 High Definition (HD) Series, 7000 Series, 6000 HD, and 4000 HD Series using Software Release 2.7.0_J

4. The SUT tested VTC systems and other VTC systems also certified by similarity are depicted in Table 1. The Functional Requirements used to evaluate the interoperability of the SUT, certified interfaces and the interoperability statuses are indicated in Table 2.

Table 1. SUT VTC Systems and other VTC Systems Certified by Similarity

	Tested VTC System (See note 1.)	VTC System Certified by Similarity	Supported Interfaces
SUT Release 2.7.3_J (See note 2.)	Polycom HDX 9004, 9006	Polycom HDX 9002	IP (10/100 Mbps with ITU-T H.323 protocol), ISDN BRI, ISDN PRI T1, ISDN PRI E1, and the following Serial interfaces: EIA-366A, EIA-449, EIA-530, ITU-T V.35 (See note 3.)
		Polycom HDX 9001	
	Polycom HDX 8000 HD (Rev A and B)	Polycom HDX 8006	IP (10/100 Mbps with ITU-T H.323 protocol), ISDN BRI, ISDN PRI T1, ISDN PRI E1, and the following Serial interfaces: EIA-366A, EIA-449, EIA-530, ITU-T V.35 (See note 3.)
		Polycom HDX 8004	
		Polycom HDX 8002	
	Polycom HDX 7000 HD (Rev A, B, and C)	Polycom HDX 7002	IP (10/100 Mbps with ITU-T H.323 protocol), ISDN BRI, ISDN PRI T1, ISDN PRI E1, and the following Serial interfaces: EIA-366A, EIA-449, EIA-530, ITU-T V.35 (See note 3.)
		Polycom HDX 7001	
	Polycom HDX 6000 HD (See note 4.)	NA	IP (10/100 Mbps with ITU-T H.323 protocol)
	Polycom HDX 4000 HD	Polycom HDX 4002	IP (10/100 Mbps with ITU-T H.323 protocol), ISDN BRI, ISDN PRI T1, ISDN PRI E1, and the following Serial interfaces: EIA-366A, EIA-449, EIA-530, ITU-T V.35 (See note 3.)
		Polycom HDX 4001	

NOTES:

1. These VTC systems were tested by JITC. The other VTC systems in the family series were not tested; however, they utilize the same software and hardware and JITC analysis determined them to be functionally identical for interoperability certification purposes and they are also certified for joint use.
2. The Polycom HDX series software release was updated from Release 2.7.0_J to 2.7.3_J with this DTR.
3. The electrical physical interface tested was ITU-T V.35 in accordance with ITU-T V.36/V.37.
4. The HDX 6000 is an IP only codec and requires the use of an ITU-T H.323 to ITU-T H.320 gateway solution in order to connect to the DSN. In testing, JITC has found minimal risk in certifying this with any ITU-T H.323 to ITU-T H.320 gateways certified and on the UC APL as a component to other certified VTC systems.

LEGEND:

APL	Approved Products List	ITU-T	International Telecommunication Union - Telecommunication Standardization Sector
BRI	Basic Rate Interface	JITC	Joint Interoperability Test Command
DCE	Data Circuit-Terminating Equipment	kbps	kilobits per second
DSN	Defense Switched Network	kHz	kilohertz
DTE	Data Terminal Equipment	Mbps	Megabits per second
E1	European Basic Multiplex Rate (2.048 Mbps)	NA	Not Applicable
EIA	Electronic Industries Alliance	PRI	Primary Rate Interface
EIA-366A	Standard for interface between DTE and automatic calling equipment for data communication	Rev	Revision
EIA-449	Standard for 37-position and 9-position interface for DTE and DCE employing serial binary data interchange	SUT	System Under Test
EIA-530	Standard for 25-position interface for DTE and DCE employing serial binary data interchange	T1	Digital Transmission Link Level 1 (1.544 Mbps)
H.320	Standard for narrowband VTC	UC	Unified Capabilities
H.323	Standard for multi-media communications on packet-based networks	V.35	Standard for data transmission at 48 kbps using 60-108 kHz group band circuits
HD	High Definition	V.36	Modems for synchronous data transmission using 60-108 kHz group band circuits
HDX	High Definition Experience	V.37	Synchronous data transmission at a data signaling rate higher than 72 kbps using 60-108 kHz group band circuits
IP	Internet Protocol	VTC	Video Teleconferencing
ISDN	Integrated Services Digital Network		

JITC Memo, JTE, Extension of the Special Interoperability Test Certification of selected models from the Polycom High Definition Experience (HDX) family for the 9000 Series, 8000 High Definition (HD) Series, 7000 Series, 6000 HD, and 4000 HD Series using Software Release 2.7.0_J

Table 2. SUT Functional Requirements and Interoperability Status

Interface	Critical	Certified	Requirements Required or Conditional	Status	UCR Reference
IP (10/100 Mbps) ITU-T H.323	No (See note 1.)	Yes (See note 2.)	The VTC system/endpoints shall meet the requirements of FTR1080B-2002. (R)	Met	5.2.4.2
			ITU-T H.323 in accordance with FTR 1080B-2002. (C)	Met	5.2.4.2
			Layer 3 Differential Service Code Point tagging as specified in the UCR, Section 5.3.1. (C)	Partially Met (See note 3.)	5.3.3.3.2
			A loss of any conferee on a multipoint videoconference shall not terminate or degrade the DSN service supporting VTC connections of any of the other conferees on the videoconference. (R)	Met	5.2.4.2
			Audio add-on interface, implemented independently of an IAS, shall be in accordance with the UCR, Section 5.2.3. (C)	Met	5.2.4.2
			Physical, electrical, and software characteristics shall not degrade or impair switch and associated network operations. (R)	Met	5.2.4.2
			VTU IP interface must be IPv6 capable and meet the Simple Server/Network Appliance IPv6 profile (R)	Partially Met (See note 4.)	5.3.5.2
ISDN BRI	No (See note 1.)	Yes	The VTC system/endpoints shall meet the requirements of FTR1080B-2002. (R)	Met	5.2.4.2
			A loss of any conferee on a multipoint videoconference shall not terminate or degrade the DSN service supporting VTC connections of any of the other conferees on the videoconference. (R)	Met	5.2.4.2
			Audio add-on interface, implemented independently of an IAS, shall be in accordance with the UCR, Section 5.2.3. (C)	Met	5.2.4.2
			Integrated BRI interface shall be in conformance with the requirements associated with a TA as described in the UCR, Section 5.2.3. (C)	Met	5.2.4.2
			Physical, electrical, and software characteristics shall not degrade or impair switch and associated network operations. (R)	Met	5.2.4.2
ISDN PRI T1 ISDN PRI E1	No (See note 1.)	Yes	The VTC system/endpoints shall meet the requirements of FTR1080B-2002. (R)	Met	5.2.4.2
			A loss of any conferee on a multipoint videoconference shall not terminate or degrade the DSN service supporting VTC connections of any of the other conferees on the videoconference. (R)	Met	5.2.4.2
			Audio add-on interface, implemented independently of an IAS, shall be in accordance with the UCR, Section 5.2.3. (C)	Met	5.2.4.2
			Integrated PRI interface shall be in conformance with IAS requirements in the UCR, Section 5.2.6. (C)	Met	5.2.4.2
			Physical, electrical, and software characteristics shall not degrade or impair switch and associated network operations. (R)	Met	5.2.4.2
Serial Interfaces: EIA-366A EIA-449 EIA-530 ITU-T V.35 (See note 5.)	No (See note 1.)	Yes	The VTC system/endpoints shall meet the requirements of FTR1080B-2002. (R)	Met	5.2.4.2
			A loss of any conferee on a multipoint videoconference shall not terminate or degrade the DSN service supporting VTC connections of any of the other conferees on the videoconference. (R)	Met	5.2.4.2
			Audio add-on interface, implemented independently of an IAS, shall be in accordance with the UCR, Section 5.2.3. (C)	Met	5.2.4.2
			Connections shall be in conformance with the requirements for serial interface(s) as described in FTR 1080B-2002. (R)	Met	5.2.4.2
			Physical, electrical, and software characteristics shall not degrade or impair switch and associated network operations. (R)	Met	5.2.4.2
Security	Yes	Certified	GR-815, STIGs, and DoDI 8510.bb (DIACAP) (R)	See note 6.	4.3.1 and 5.4.6.1

JITC Memo, JTE, Extension of the Special Interoperability Test Certification of selected models from the Polycom High Definition Experience (HDX) family for the 9000 Series, 8000 High Definition (HD) Series, 7000 Series, 6000 HD, and 4000 HD Series using Software Release 2.7.0_J

Table 2. SUT Functional Requirements and Interoperability Status (continued)

NOTES:			
1. The VTC system interface requirements can be met with ISDN PRI, Serial, or ISDN BRI. In addition the SUT may include an IP ITU-T H.323 conditional interface.			
2. The SUT also met the conditional requirements for an IP interface with the ITU-T H.323 protocol; however, Assured Service is not yet defined for an IP interface with ITU-T H.323 protocol. Therefore, C2 VTC users and Special C2 VTC users are not authorized to be served by an IP interface with the ITU-T H.323 protocol. However, the SUT is certified for C2 and Special C2 VTC sessions via the TDM interfaces. The HDX 6000 HD is certified for C2 and Special C2 VTC sessions via a certified gateway with the TDM interfaces.			
3. During testing for DTR 1, the SUT did not properly tag IPv4 or IPv6 management traffic. This discrepancy was fixed with this DTR, which includes Release 2.7.3_J.			
4. During the original test effort, the SUT met all of the IPv6 requirements for a VTC system with the following exceptions in the subparagraphs below. DISA had accepted and approved the vendor's POA&M and adjudicated these discrepancies as having a minor operational impact.			
a. The SUT does not support Duplicate Address Detection. This discrepancy was fixed with DTR 1, which included HDX Release 2.7.1_J.			
b. The SUT does not fully meet the ability to disable or enable Destination Unreachable messages. This discrepancy was fixed with DTR 1, which included CMA Release 5.2.0_J.			
c. The SUT does not have capability to toggle messages sent to any-cast or multi-cast. This discrepancy was fixed with DTR 1, which included CMA Release 5.2.0_J.			
d. The SUT only supports LDAP over IPv4 at this time. NM is not required to support IPv6; therefore, this has no operational impact.			
5. The electrical physical interface tested was ITU-T V.35 in accordance with ITU-T V.36/V.37.			
6. Security is tested by DISA-led Information Assurance test teams and published in separate report, References (f) and (g).			
LEGEND:			
ASD/NII	Assistant Secretary of Defense for Networks and Information Integration	HDX	High Definition Experience
BRI	Basic Rate Interface	IAS	Integrated Access Switch
C	Conditional	IP	Internet Protocol
C2	Command and Control	IPv4	Internet Protocol version 4
CPE	Customer Premise Equipment	IPv6	Internet Protocol version 6
DCE	Data Circuit-Terminating Equipment	ISDN	Integrated Services Digital Network
DIACAP	Department of Defense Information Assurance Certification and Accreditation Process	ITU-T	International Telecommunication Union – Telecommunication Standardization Sector
DISA	Defense Information Systems Agency	kbps	kilobits per second
DoDI	Department of Defense Instruction	kHz	kilohertz
DSN	Defense Switched Network	LDAP	Lightweight Directory Access Protocol
DTE	Data Terminal Equipment	Mbps	Megabits per seconds
DTR	Desktop Review	MCU	Multipoint Control Unit
E1	European Basic Multiplex Rate (2.048 Mbps)	NM	Network Management
EIA	Electronic Industries Alliance	OSD	Office of the Secretary of Defense
EIA-366A	Standard for interface between DTE and automatic calling equipment for data communication	POA&M	Plan of Action and Milestones
EIA-449	Standard for 37-position and 9-position interface for DTE and DCE employing serial binary data interchange	PRI	Primary Rate Interface
EIA-530	Standard for 25-position interface for DTE and DCE employing serial binary data interchange	R	Required
FTR	Federal Telecommunications Recommendation	STIGs	Security Technical Implementation Guides
GR	Generic Requirements	SUT	System Under Test
GR-815	Generic Requirements For Network Element/Network System (NE/NS) Security	T1	Digital Transmission Link Level 1 (1.544 Mbps)
H.320	Standard for narrowband VTC	TDM	Time Division Multiplexing
H.323	Standard for multi-media communications on packet-based networks	UCR	Unified Capabilities Requirements
HD	High Definition	V.35	Standard for data transmission at 48 kbps using 60-108 kHz group band circuits
		V.36	Modems for synchronous data transmission using 60-108 kHz group band circuits
		V.37	Synchronous data transmission at a data signaling rate higher than 72 kbps using 60-108 kHz group band circuits
		VTC	Video Teleconferencing
		VTU	Video Teleconferencing Unit

5. JITC distributes interoperability information via the JITC Electronic Report Distribution (ERD) system, which uses Sensitive but Unclassified IP Data (formerly known as NIPRNet) e-mail. Interoperability status information is available via the JITC System Tracking Program (STP). STP is accessible by .mil/.gov users at <https://stp.fhu.disa.mil/>. Test reports, lessons learned, and related testing documents and references are on the JITC Joint Interoperability Tool

JITC Memo, JTE, Extension of the Special Interoperability Test Certification of selected models from the Polycom High Definition Experience (HDX) family for the 9000 Series, 8000 High Definition (HD) Series, 7000 Series, 6000 HD, and 4000 HD Series using Software Release 2.7.0_J

(JIT) at <https://jit.fhu.disa.mil/>. Due to the sensitivity of the information, the Information Assurance Accreditation Package (IAAP) that contains the approved configuration and deployment guide must be requested directly from the Unified Capabilities Certification Office (UCCO), e-mail: disa.meade.ns.list.unified-capabilities-certification-office@mail.mil. All associated information is available on the DISA UCCO website located at <http://www.disa.mil/Services/Network-Services/UCCO>.

6. The JITC point of contact is Mr. Dale Fulton, DSN 879-0507, commercial (520) 538-0507, FAX DSN 879-4347, or e-mail to dale.h.fulton.civ@mail.mil. JITC's mailing address is P.O. Box 12798, Fort Huachuca, AZ 85670-2798. The UCCO tracking number for the SUTs are 1034102 and 1034105.

FOR THE COMMANDER:



for RICHARD A. MEADOR
Chief
Battlespace Communications Portfolio

Enclosure a/s

Distribution (electronic mail):

DoD CIO
Joint Staff J-6, JCS
USD(AT&L)
ISG Secretariat, DISA, JTA
U.S. Strategic Command, J665
US Navy, OPNAV N2/N6FP12
US Army, DA-OSA, CIO/G-6 ASA(ALT), SAIS-IOQ
US Air Force, A3CNN/A6CNN
US Marine Corps, MARCORSYSCOM, SIAT, A&CE Division
US Coast Guard, CG-64
DISA/TEMC
DIA, Office of the Acquisition Executive
NSG Interoperability Assessment Team
DOT&E, Netcentric Systems and Naval Warfare
Medical Health Systems, JMIS IV&V
HQUSAISEC, AMSEL-IE-IS
UCCO

ADDITIONAL REFERENCES

- (c) Office of the Assistant Secretary of Defense, "Department of Defense Unified Capabilities Requirements 2008, Change 1," 22 January 2010
- (d) Joint Interoperability Test Command, "Defense Switched Network Generic Switch Test Plan (GSTP), Change 2," 2 October 2006
- (e) Joint Interoperability Test Command, Memo, JTE, "Special Interoperability Test Certification of selected models from the Polycom High Definition Experience (HDX) family for the 9000 Series, 8000 High Definition (HD) Series, 7000 Series, 6000 HD, and 4000 HD Series using Software Release 2.7.0_J," 26 July 2011
- (f) Joint Interoperability Test Command, "Information Assurance (IA) Assessment of Polycom High Definition Experience (HDX) Release (Rel.) 2.7.0_J (Tracking Number 1034102)," 7 October 2011
- (g) Joint Interoperability Test Command, "Information Assurance (IA) Assessment of Polycom Converged Management Application (CMA) 5000 Family Release (Rel.) 5.2.0_J (Tracking Number 1034105)," 3 October 2011