



DEFENSE INFORMATION SYSTEMS AGENCY

P. O. BOX 549
FORT MEADE, MARYLAND 20755-0549

IN REPLY REFER TO: Joint Interoperability Test Command (JTE)

9 April 2020

MEMORANDUM FOR DISTRIBUTION

SUBJECT: Extension of the Joint Interoperability Certification of the Dell EMC Networking PowerSwitch Z9264F-ON and Z9332F-ON with Software Release SmartFabric Operating System (OS) 10.5

- References: (a) Department of Defense Instruction 8100.04, "DoD Unified Capabilities (UC)," 9 December 2010
(b) Office of the Department of Defense Chief Information Officer, "Department of Defense Unified Capabilities Requirements 2013, Change 2," September 2017
(c) through (e), see Enclosure 1

1. Certification Authority. Reference (a) establishes the Joint Interoperability Test Command (JITC) as the Joint Interoperability Certification Authority (CA) for the Department of Defense Information Network (DoDIN) products, Reference (b).

2. Conditions of Certification. The Dell EMC Networking PowerSwitch Z9264F-ON and Z9332F-ON with Software Release SmartFabric Operating System (OS) 10.5 is hereinafter referred to as the System Under Test (SUT). The SUT meets the critical requirements of the Unified Capabilities Requirements (UCR), Reference (b), as an Assured Services Local Area Network (ASLAN) Core, Distribution, and Access switch and is certified for joint use with the conditions described in Table 1. This certification expires upon changes that affect interoperability, but no later than the expiration date specified in the DoDIN Approved Products List (APL) memorandum.

This extension of the certification is for Desktop Review (DTR) 1. DTR 1 was requested to add the Z9332F-ON switch 400 Gigabit Ethernet (GbE) interface data rate to this certification. See Table 4 for a list of components and Paragraph 4 for the test details.

Table 1. Conditions

Table with 3 columns: Description, Operational Impact, Remarks. Row 1: UCR Waivers. Row 2: None.

JITC Memo, JTE, Joint Interoperability Certification of the Dell EMC Networking PowerSwitch Z9264F-ON and Z9332F-ON with Software Release SmartFabric Operating System (OS) 10.5

Table 1. Conditions (continued)

Description		Operational Impact	Remarks
TDR#	Conditions of Fielding		
DEL-0731-001	EDG-000080: Per ASLAN testing and vendor documentation, the SUT does not support PoE IAW either 802.3af-2003 or 802.3at-2009. CoF: The SUT is certified for only data and VVoIP endpoints that do not require PoE, such as CCA, UCCS, and Soft Clients.	Minor with CoF	On 29 October 2019, DISA adjudicated this discrepancy as minor with vendor POA&M and CoF.
DEL-0731-003	IP6-000490: Per Dell Letter of Compliance, Stateless Address Autoconfiguration and Manual Address Assignment, IAW IP6-000490: Non-Comply - User must select desired flag values when enabling router advertisements. CoF: Managed Address Configuration flags must be set to desired value when implemented by the user. Vendor to include configuration in deployment guide.	Minor with CoF	On 29 October 2019, DISA adjudicated this discrepancy as minor with CoF.
DEL-0731-004	EDG-000210: Per IO-3 ASLAN testing, SUT generates VRRP v3 checksums for IPv4 traffic in a different manner than other heterogeneous vendors. CoF: SUT must be configured with VRRPv2 to support Distribution switch failover in less than 5 seconds within an IPv4 infrastructure.	Minor with CoF and POA&M	On 29 October 2019, DISA adjudicated this discrepancy as minor with vendor POA&M.
DEL-0731-004	EDG-000210: Per IO-3 ASLAN testing, SUT recovery time exceeds 5 seconds. CoF: For failback recovery, site required to schedule ASI.	Minor with CoF	On 29 October 2019, DISA adjudicated this discrepancy as minor with CoF.
TDR#	Open Test Discrepancies		
DEL-0731-002	IP6-000390: Per Dell Letter of Compliance, Router Advertisement inconsistencies are not logged.	Minor with POA&M	On 29 October 2019, DISA adjudicated this discrepancy as minor with vendor POA&M.
DEL-0731-006	EDG-000010: Per IO-18 ASLAN testing, packet loss is measured in downstream Low Priority Scavenging traffic when upstream traffic is oversubscribed (testing with 6 queues).	Information Only	On 13 February 2020, DISA adjudicated this discrepancy as Information Only.
DEL-0731-007	EDG-000010: Per IO-19 ASLAN testing, packet loss is measured in downstream Low Priority Scavenging traffic when upstream traffic is oversubscribed (testing with 6 queues).	Information Only	On 13 February 2020, DISA adjudicated this discrepancy as Information Only.
LEGEND:			
802.3af-2003	Power over Ethernet up to 15.4 Watts	IPv4	Internet Protocol version 4
802.3at-2003	Power over Ethernet up to 25.5 Watts	IP6	Internet Protocol version 6
ASI	Authorized Service Interruption	POA&M	Plan Of Action and Milestones
ASLAN	Assured Services Local Area Network	PoE	Power Over Ethernet
CCA	Call Connection Agent	SUT	System Under Test
CoF	Condition of Fielding	TDR	Test Discrepancy Report
DEL	Dell	UCCS	Unified Capabilities Conference System
DISA	Defense Information Systems Agency	UCR	Unified Capabilities Requirements
EDG	Edge	v3	Version 3
IAW	In Accordance With	VRRP	Virtual Router Redundancy Protocol
IO	Interoperability	VVoIP	Voice and Video over Internet Protocol

3. Interoperability Status. Table 2 provides the SUT interface interoperability status, Table 3 provides the Capability Requirements and Functional Requirements status, and Table 4 provides a DoDIN APL Product Summary, to include all subsequent DTR updates.

Table 2. Interface Status

Interface (See note 1.)	Applicability			Status	Remarks
	Co	D	A		
Network Management Interfaces					
IEEE 802.3i (10BaseT UTP)	C	C	C	Met	
IEEE 802.3u (100BaseT UTP)	C	C	C	Met	
IEEE 802.3ab (1000BaseT UTP)	C	C	C	Met	
Access (User) Interfaces (See note 2.)					
IEEE 802.3i (10BaseT UTP)	C	C	C	Not Tested	See note 3.
IEEE 802.3u (100BaseT UTP)	C	C	C	Not Tested	See note 3.
IEEE 802.3u (100BaseFX)	C	C	C	Not Tested	See note 3.
IEEE 802.3ab (1000BaseT UTP)	C	C	C	Not Tested	See note 3.
IEEE 802.3z (1000BaseX Fiber)	C	C	C	Met	See note 4.
IEEE 802.3bz (2.5/5GBaseX)	O	O	O	Not Tested	See note 3.
IEEE 802.3ae (10GBaseX)	C	C	C	Met	
IEEE 802.3by (25GBaseX)	O	O	O	Met	
IEEE 802.3ba (40GBaseX)	O	O	O	Met	
IEEE 802.3cd (50GBaseX)	O	O	O	Met	
IEEE 802.3ba (100GBaseX)	O	O	O	Met	
IEEE 802.3bs (400GBaseX)	O	O	O	Met	See note 5.
Uplink (Trunk) Interfaces (See note 2.)					
IEEE 802.3u (100BaseT UTP)	O	O	O	Not Tested	See note 3.
IEEE 802.3u (100BaseFX)	O	O	O	Not Tested	See note 3.
IEEE 802.3ab (1000BaseT UTP)	O	O	O	Not Tested	See note 3.
IEEE 802.3z (1000BaseX Fiber)	C	C	C	Met	See note 4.
IEEE 802.3bz (2.5/5GBaseX)	O	O	O	Not Tested	See note 3.
IEEE 802.3ae (10GBaseX)	C	C	C	Met	
IEEE 802.3by (25GBaseX)	O	O	O	Met	
IEEE 802.3ba (40GBaseX)	C	C	C	Met	
IEEE 802.3cd (50GBaseX)	O	O	O	Met	
IEEE 802.3ba (100GBaseX)	C	C	C	Met	
IEEE 802.3bs (400GBaseX)	O	O	O	Met	See note 5.
NOTE(S):					
1. The SUT high-level requirements are depicted in Table 3. These high-level requirements refer to a more detailed list of requirements provided in Enclosure 3, Table 3-2.					
2. Core, Distribution, and Access products must minimally support one of the interfaces listed in this table as conditional for the given role. Other rates and standards may be provided as optional interfaces.					
3. The SUT does not support this (conditional or optional) interface.					
4. USAISEC-TIC tested the 10/25/40/50/100 GBaseX interfaces with the Z9264F, but not the 1GBaseX interface. Analysis determined the 1GBaseX interface is certified based on the vendor's Letters of Compliance to the IEEE 802.3 standards and the testing data collected at all other data rates.					
5. With DTR 1, the IEEE 802.3bs 400GBaseX interface was added to this certification based on testing of the Z9332F-ON switch that was conducted at USAISEC-TIC during an MVTE 13-31 January 2020					

JITC Memo, JTE, Joint Interoperability Certification of the Dell EMC Networking PowerSwitch Z9264F-ON and Z9332F-ON with Software Release SmartFabric Operating System (OS) 10.5

Table 2. Interface Status (continued)

LEGEND:			
802.3ab	1000BaseT Gbps Ethernet over Twisted Pair	C	Conditional
802.3ae	10 Gbps Ethernet over Fiber	Co	Core
802.3ba	40 and 100 Gigabit Ethernet over Twisted pair and Fiber	DTR	Desktop Review
802.3bs	400GbE over optical physical media	D	Distribution
802.3by	25 Gbps Ethernet over Multi-Mode Fiber	GBaseX	Gigabit Ethernet over Fiber or Copper
802.3bz	2.5/5 Gbps Ethernet over balanced Twisted Pair	Gbps	Gigabits per second
802.3cd	50 Gigabit Ethernet Standard	IEEE	Institute of Electrical and Electronics Engineers
802.3i	10BaseT 10 Mbps Ethernet over Twisted Pair	Mbps	Megabits per second
802.3u	Fast Ethernet at 100 Mbps, copper and Fiber	MVTE	Multi-Vendor Test Event
802.3z	Gigabit Ethernet over Fiber	O	Optional
A	Access	SUT	System Under Test
BaseFX	Megabit Ethernet over Fiber	TIC	Technology Integration Center
BaseT	Megabit (Baseband Operation, Twisted Pair) Ethernet	USAISEC	U.S. Army Information Systems Engineering Command
BaseX	Megabit Ethernet over Fiber or Copper	UTP	Unshielded Twisted Pair

Table 3. Capability Requirements and Functional Requirements Status

CR/FR ID	UCR Requirement (High-Level) (See note 1.)	UCR 2013 Change 2 Reference	Status
1	General LAN Switch and Router Product Requirements (R)	7.2.1	Met
2	LAN Switch and Router Redundancy Requirements (R)	7.2.2	Partially Met (See note 2.)
3	LAN Product Requirements Summary (R)	7.2.3	Partially Met (See notes 2 and 3.)
4	Multiprotocol Label Switching (O)	7.2.4	Not Tested (See note 4.)
5	IPv6	5.2	Partially Met (See note 2.)

NOTE(S):

- The annotation of “required” refers to a high-level requirement category. Enclosure 3 addresses the applicability of each sub-requirement.
- Reference Table 1 for conditions.
- A USAISEC-TIC-led Cybersecurity test team conducted Security testing and published the results in a separate report, Reference (d).
- The SUT does not support this optional requirement.

LEGEND:

CR	Capability Requirement	R	Required
FR	Functional Requirement	SUT	System Under Test
ID	Identification	TIC	Technology Integration Center
IPv6	Internet Protocol version 6	UCR	Unified Capabilities Requirements
LAN	Local Area Network	USAISEC	U.S. Army Information Systems Engineering Command
O	Optional		

Table 4. DoDIN APL Product Summary

Product Identification			
Product Name	Dell EMC Networking PowerSwitch Z9264F-ON and Z9332F-ON (See note 1.)		
Software Release	SmartFabric OS 10.5		
UCR Product Type(s)	ASLAN Core/Distribution/Access Switch		
Product Description	The Dell EMC Networking PowerSwitch Z9264F-ON and Z9332F-ON delivers voice-class availability, 1/10/25/40/50/100/400 GbE SFP+/QSFP+/QSFP28/QSFP56-DD for switching VoIP, video, and data traffic.		
DoDIN Certified Function	Component/Sub-component Name (See notes 2, 3 and 54.)	Tested Version	Remarks
ASLAN Core/Distribution/Access	Z9264F-ON	SmartFabric OS 10.5	Redundant power modules

Table 4. DoDIN APL Product Summary (continued)

Component/Sub-Component added with DTR 1 (See note 3.)																																				
Component	Sub-Component	Function (See note 4.)	Blocking Factor (See note 5.)																																	
			C/D	A																																
<u>Z9332F-ON</u>	N/A	<u>32x 100GbE (QSFP-DD) w/ 2x10G SFP+</u> or - 128x100GbE (QSFP56-DD to 4xQSFP28 breakout) w/ 2x10G SFP+ or - 32x100 GbE (QFSP28) – with breakout capability for 10/25/50 that includes 144 ports (QFSP28) of 10/25/50 GbE using breakout cables [Note: When 16 ports are configured in 8x mode (at 10G, 25G, 50G per lane), the other 16 ports will be in 1x mode. Hence 8*16 + 16*1 = 144.] or - 64x40GbE using QSFP28 to 2xQSFP+ breakout with 2x10G SFP+	<u>Met</u>	<u>Met</u>																																
<p>NOTE(S):</p> <ol style="list-style-type: none"> With DTR 1, the SUT Product Name was updated from Dell EMC Networking PowerSwitch Z9264F-ON to Dell EMC Networking PowerSwitch Z9264F-ON and Z9332F-ON with the addition of the Z9332F-ON switch. Table 3-3 of Enclosure 3 provides the detailed component and subcomponent descriptions. Components bolded and underlined were tested by USAISEC-TIC. The Z9332F-ON 10, 25, 40, 50, and 100 GbE interfaces are approved based on similarity to the same data rate interfaces that were tested on the Z9264-ON switch. With DTR 1, the Z9332F-ON switch was added to this certification with the 400 GbE interface data rate based on an MVTE conducted at USAISEC-TIC 13-31 January 2020. <p>LEGEND:</p> <table> <tr> <td>APL</td> <td>Approved Products List</td> <td>QSFP+</td> <td>Quad Small Form-factor Pluggable Plus</td> </tr> <tr> <td>ASLAN</td> <td>Assured Services Local Area Network</td> <td>QSFP28</td> <td>28Mbps Signaled Quad Small Form-factor Pluggable</td> </tr> <tr> <td>DoDIN</td> <td>Department of Defense Information Network</td> <td>SFP+</td> <td>Small Form-factor Pluggable Plus</td> </tr> <tr> <td>EMC</td> <td>Egan, Marino & Curly</td> <td>TIC</td> <td>Technology Integration Center</td> </tr> <tr> <td>GbE</td> <td>Gigabit Ethernet</td> <td>UCR</td> <td>Unified Capabilities Requirements</td> </tr> <tr> <td>MVTE</td> <td>Multi-Vendor Test Event</td> <td>USAISEC</td> <td>U.S. Army Information Systems Engineering Command</td> </tr> <tr> <td>OS</td> <td>Operating System</td> <td>VoIP</td> <td>Voice over Internet Protocol</td> </tr> <tr> <td>QSFP-DD</td> <td>Quad Small Form-factor Pluggable Double Density</td> <td></td> <td></td> </tr> </table>					APL	Approved Products List	QSFP+	Quad Small Form-factor Pluggable Plus	ASLAN	Assured Services Local Area Network	QSFP28	28Mbps Signaled Quad Small Form-factor Pluggable	DoDIN	Department of Defense Information Network	SFP+	Small Form-factor Pluggable Plus	EMC	Egan, Marino & Curly	TIC	Technology Integration Center	GbE	Gigabit Ethernet	UCR	Unified Capabilities Requirements	MVTE	Multi-Vendor Test Event	USAISEC	U.S. Army Information Systems Engineering Command	OS	Operating System	VoIP	Voice over Internet Protocol	QSFP-DD	Quad Small Form-factor Pluggable Double Density		
APL	Approved Products List	QSFP+	Quad Small Form-factor Pluggable Plus																																	
ASLAN	Assured Services Local Area Network	QSFP28	28Mbps Signaled Quad Small Form-factor Pluggable																																	
DoDIN	Department of Defense Information Network	SFP+	Small Form-factor Pluggable Plus																																	
EMC	Egan, Marino & Curly	TIC	Technology Integration Center																																	
GbE	Gigabit Ethernet	UCR	Unified Capabilities Requirements																																	
MVTE	Multi-Vendor Test Event	USAISEC	U.S. Army Information Systems Engineering Command																																	
OS	Operating System	VoIP	Voice over Internet Protocol																																	
QSFP-DD	Quad Small Form-factor Pluggable Double Density																																			

4. Test Details. This extension of the certification is based on DTR 1. The original certification, documented in Reference (c), was based on interoperability (IO) testing, review of the vendor’s Letters of Compliance (LoC) and DISA adjudication of open IO Technical Discrepancy Reports (TDRs) for inclusion on the DoDIN APL. The United States Army Information Systems Engineering Command (USAISEC) – Mission Engineering Directorate (MED), Technology Integration Center (TIC), hereafter referred to as USAISEC-TIC, conducted initial testing at Fort Huachuca, Arizona, from 19 August through 20 September 2019 using test procedures derived from Reference (d). Review of the vendor’s LoC completed on 18 October 2019. DISA completed adjudication of outstanding TDRs on 29 October 2019. USAISEC-TIC-led Cybersecurity (CS) test teams conducted CS testing and published the results in a separate report, Reference (e). Enclosure 2 of Reference (c) documents the test results and describes the tested network and system configurations. Enclosure 2 of Reference (c) provides the detailed interface, capability, and functional requirements and test results.

This extension of the certification is for Desktop Review (DTR) 1. DTR 1 was requested to add the Z9332F-ON switch with the 400 GbE interface data rate to this certification.

JITC analysis, with input from USAISEC-TIC, determined IO testing with CS vulnerability scans was required. Analysis also determined there were no past due Vendor Plan of Actions and Milestones (POA&M) for CS findings or IO discrepancies. USAISEC-TIC conducted IO testing on Z9332F-ON switch during a Multi-Vendor Test Event from 13 January through 31 January 2020 using failover, jitter, latency, packet loss, blocking factor and queue-shaping test

JITC Memo, JTE, Joint Interoperability Certification of the Dell EMC Networking PowerSwitch Z9264F-ON and Z9332F-ON with Software Release SmartFabric Operating System (OS) 10.5

procedures derived from Reference (d). Testing demonstrated the Z9332F-ON switch meets current UCR ASLAN requirements at the 400 GbE interface data rate in accordance with Reference (b). In addition, two new oversubscription test discrepancies, documented in TDRs DEL-0731-006 and DEL-0731-007, were adjudicated by DISA as Information Only, as noted in Table 1. Based on the IO test results, JITC approves this DTR with the conditions and limitations noted in Table 1.

Additionally, the results from the CS vulnerability scans performed during the test event are documented in a separate report, Reference (e).

5. Additional Information. JITC distributes interoperability information via the JITC Electronic Report Distribution (ERD) system, which uses Sensitive but Unclassified IP Data (formerly known as NIPRNet) e-mail. Interoperability status information is available via the JITC System Tracking Program (STP). STP is accessible by .mil/.gov users at <https://stp.fhu.disa.mil/>. Test reports, lessons learned, and related testing documents and references are on the JITC Industry Toolkit (JIT) at <https://jit.fhu.disa.mil/>. Due to the sensitivity of the information, the CS Assessment Package (CAP) containing the approved configuration and deployment guide must be requested directly from the Approved Products Certification Office (APCO) via e-mail: disa.meade.ie.list.approved-products-certification-office@mail.mil. All associated information is available on the DISA APCO website located at <https://aplits.disa.mil/>.

6. Point of Contact (POC). USAISEC-TIC testing POC: Mr. James Hatch; commercial telephone (520) 533-2860; DSN telephone 821-2860; e-mail address: james.d.hatch12.civ@mail.mil. JITC certification POC: Ms. Lisa Esquivel; commercial telephone (520) 538-5531; DSN telephone 879-5531; DSN FAX: 879-4347; e-mail address: lisa.r.esquivel.civ@mail.mil; mailing address: Joint Interoperability Test Command, ATTN: JTE (Ms. Lisa Esquivel), P.O. Box 12798, Fort Huachuca, AZ 85670-2798. The APCO tracking number for the SUT is 1907701.

FOR THE COMMANDER:

Enclosure

for RIC HARRISON
Chief
Networks/Communications &
DoDIN Capabilities Division

JITC Memo, JTE, Joint Interoperability Certification of the Dell EMC Networking PowerSwitch Z9264F-ON and Z9332F-ON with Software Release SmartFabric Operating System (OS) 10.5

Distribution (electronic mail):

DoD CIO
Joint Staff J-6, JCS
USD (AT&L)
ISG Secretariat, DISA, JTA
U.S. Strategic Command, J665
US Navy, OPNAV N2/N6FP12
US Army, DA-OSA, CIO/G-6 ASA (ALT), SAIS-IOQ
US Air Force, A3CNN/A6CNN
US Marine Corps, MARCORSSYSCOM, SIAT, A&CE Division
US Coast Guard, CG-64
DISA/TEMC
DIA, Office of the Acquisition Executive
NSG Interoperability Assessment Team
DOT&E, Netcentric Systems and Naval Warfare
Medical Health Systems, JMIS IV&V
HQUSAISEC, ELIE-ISE-ME
APCO

ADDITIONAL REFERENCES

- (c) Joint Interoperability Certification of the Dell EMC Networking PowerSwitch Z9264F-ON with Software Release SmartFabric Operating System (OS) 10.5, December 2019
- (d) Joint Interoperability Test Command, “Assured Services Local Area Network (ASLAN) and Non-ASLAN Test Procedures Version 1.0 for Unified Capabilities Requirements (UCR) 2013 Change 2,” October 2017
- (e) Joint Interoperability Test Command, “Cybersecurity Assessment Report for Dell EMC Networking PowerSwitch Z-Series Switches Software Release Dell EMC Networking SmartFabric OS 10.5 (Tracking Number TN 1907701),” February 2020