



DEFENSE INFORMATION SYSTEMS AGENCY

P. O. BOX 549
FORT MEADE, MARYLAND 20755-0549

IN REPLY REFER TO: Joint Interoperability Test Command (JTE)

18 September 2019

MEMORANDUM FOR DISTRIBUTION

SUBJECT: Extension of the Joint Interoperability Certification of the Dell EMC Unity Family OE 5.0

- References: (a) Department of Defense Instruction 8100.04, "DoD Unified Capabilities (UC)," 9 December 2010
(b) Office of the Department of Defense Chief Information Officer, "Department of Defense Unified Capabilities Requirements 2013, Change 1," June 2016
(c) through (e), see Enclosure

1. Certification Authority. Reference establish the Joint Interoperability Test Command (JITC) as the Joint Interoperability Certification Authority for the Department of Defense Information Network (DoDIN) products, Reference (b).

2. Conditions of Certification. The Dell EMC Unity Family Operating Environment (OE) 5.0, hereinafter referred to as the System Under Test (SUT), meets the critical requirements of the Unified Capabilities Requirements, Reference (b), and is certified for joint use as a Data Storage Controller with the conditions described in Table 1. The Dell EMC Unity Flash 650 and Dell EMC Unity Hybrid 400 models were tested. The additional EMC Unity models listed in Table 4 are also certified with the conditions described in Table 1. These additional models utilize the same software and similar hardware. JITC analyses determined these systems to be functionally identical to the Unity Flash 650 and the Unity Hybrid 400; therefore, they are covered under this certification. This certification expires upon changes that affect interoperability, but no later than the expiration date listed in the DoDIN Approved Products List (APL) memorandum.

This extension of the certification is for Desktop Review (DTR) 3. DTR 3 was requested to update the SUT software version from OE 4.5 to OE 5.0 and to add the Dell EMC Unity 380, 380F, 480, 480F, 680, 680F, 880, and 880F hardware platforms to the certification by similarity. See Table 4 for a list of components and Paragraph 4 for additional details.

Table 1. Conditions

Table with 3 columns: Condition, Operational Impact, Remarks. Row 1: UCR Waivers. Row 2: None.

**Table 1. Conditions (continued)**

Condition	Operational Impact	Remarks																								
<b>Conditions of Fielding</b>																										
<b>TDR DMC-0669-001:</b> The SUT does not Support the GNS or single Name space functionality. The SUT supports only "in-band" (local) single namespace functionality. Not certified for "out-of-band" Global Namespace support.	Minor	See note 1.																								
<b>TDR DMC-0669-003:</b> The SUT does not support statically provisioned or dynamically adjusted large IP packet receive buffers for replication (mirroring) session traffic received on the Ethernet physical interfaces. Data must be sent across terrestrial networks.	Minor	See note 1.																								
<b>TDR DMC-0669-005:</b> Per the vendor LoC, the SUT does not support Rapid recovery from sensitive data spills, where the wrong data is accidentally written to the wrong place. Vendor is required to add the necessary steps to erase the data accidentally written to wrong place in the Military Unique Deployment Guide.	Minor	See note 1.																								
<b>TDR DMC-0669-006:</b> The SUT does not provide Class of Service and Quality of Service marking on egress traffic at layer 3 per Section 6, Network Infrastructure End-to-End Performance. The SUT must be deployed with a site provided switch listed on the Approved Products List.	Minor	See note 1.																								
<b>Open Test Discrepancies</b>																										
<b>TDR DMC-0669-002:</b> The SUT does not support a configurable MTU between 1280 bytes and 1540 bytes to ensure packets can transit type 1 encryptors. The system default MTU shall be 1540 bytes.	None	CLOSED (See note 2.)																								
<b>TDR DMC-0669-004:</b> The SUT does not support client-side load balancing.	None	See note 3.																								
<p><b>NOTE(S):</b></p> <p>1. DISA has accepted and approved the vendor's POA&amp;M and adjudicated this discrepancy as having a minor operational impact with a condition of fielding. The SUT does not support disparate and remote network based file systems because the GNS exists within a DSC cluster, which must be co-located in a campus type environment. The SUT supports only "in-band" (local) single namespace functionality. The SUT is not certified for "out-of-band" Global Namespace support.</p> <p>2. DISA has accepted and approved the vendor's POA&amp;M and adjudicated this discrepancy as having a minor operational impact. Under DTR 1, the SUT version was updated from OE 4.2 to OE 4.4. Under DTR 2, the SUT version was updated from OE 4.4 to OE 4.5. This update included the resolution of this TDR, allowing the capability of the SUT to configure a custom MTU size between 1280 and 9216. Based on JITC analysis, the vendor provided documentation is sufficient to close this TDR.</p> <p>3. DISA has accepted and approved the vendor's POA&amp;M and adjudicated this discrepancy as a change requirement having no operational impact. DISA stated the intent to change this requirement in the next version of the UCR.</p>																										
<p><b>LEGEND:</b></p> <table style="width: 100%; border: none;"> <tr> <td style="width: 33%;">DISA</td> <td style="width: 33%;">Defense Information Systems Agency</td> <td style="width: 33%;">LoC</td> <td style="width: 33%;">Letters of Compliance</td> </tr> <tr> <td>DSC</td> <td>Data Storage Controller</td> <td>MTU</td> <td>Maximum Transmission Unit</td> </tr> <tr> <td>DTR</td> <td>Desktop Review</td> <td>POA&amp;M</td> <td>Plan of Action and Milestones</td> </tr> <tr> <td>GNS</td> <td>Global Name Service</td> <td>SUT</td> <td>System Under Test</td> </tr> <tr> <td>IP</td> <td>Internet Protocol</td> <td>TDR</td> <td>Test Discrepancy Report</td> </tr> <tr> <td>JITC</td> <td>Joint Interoperability Test Command</td> <td>UCR</td> <td>Unified Capabilities Requirements</td> </tr> </table>			DISA	Defense Information Systems Agency	LoC	Letters of Compliance	DSC	Data Storage Controller	MTU	Maximum Transmission Unit	DTR	Desktop Review	POA&M	Plan of Action and Milestones	GNS	Global Name Service	SUT	System Under Test	IP	Internet Protocol	TDR	Test Discrepancy Report	JITC	Joint Interoperability Test Command	UCR	Unified Capabilities Requirements
DISA	Defense Information Systems Agency	LoC	Letters of Compliance																							
DSC	Data Storage Controller	MTU	Maximum Transmission Unit																							
DTR	Desktop Review	POA&M	Plan of Action and Milestones																							
GNS	Global Name Service	SUT	System Under Test																							
IP	Internet Protocol	TDR	Test Discrepancy Report																							
JITC	Joint Interoperability Test Command	UCR	Unified Capabilities Requirements																							

3. **Interoperability Status.** Table 2 provides the SUT interface interoperability status, Table 3 provides the Capability Requirements and Functional Requirements status, and Table 4 provides the DoDIN APL product summary, to include all subsequent DTR updates.

**Table 2. SUT Interface Status**

Interface	Threshold CR/FR Requirements (See Note)	Status	Remarks
<b>Network Attached Storage (NAS) Interfaces</b>			
1 GbE (Ethernet) (R)	1	Met	
10 GbE (Ethernet) (R)	1	Met	
<b>Storage Array Net (SAN) Interfaces</b>			
Fibre Channel (FC)	1	Met	
FC Protocol (FCP)	1	Met	

**Table 2. SUT Interface Status (continued)**

Interface	Threshold CR/FR Requirements (See Note)	Status	Remarks																												
<b>Out-of-band Management Interfaces</b>																															
10 Mbps Ethernet (R)	1	Met																													
100 Mbps Ethernet (R)	1	Met																													
1 GbE Ethernet (R)	1	Met																													
<b>Converged Network Adapter (CNA) Interfaces</b>																															
10 GbE (Ethernet) (O)	1	Not Tested	The SUT does not support this optional CNA interface.																												
<p><b>NOTE(S):</b> The UCR does not identify interface CR/FR applicability. The SUT high-level CR and FR ID numbers depicted in the Threshold CR/FR Requirements column are cross-referenced with Table 3.</p> <p><b>LEGEND:</b></p> <table style="width: 100%; border: none;"> <tr> <td style="width: 50%;">CNA</td> <td style="width: 50%;">Converged Network Adapter</td> <td style="width: 50%;">Mbps</td> <td style="width: 50%;">Megabits per second</td> </tr> <tr> <td>CR</td> <td>Capability Requirement</td> <td>NAS</td> <td>Network Attached Storage</td> </tr> <tr> <td>FC</td> <td>Fibre Channel</td> <td>O</td> <td>Optional</td> </tr> <tr> <td>FCP</td> <td>FFC Protocol</td> <td>R</td> <td>Required</td> </tr> <tr> <td>FR</td> <td>Functional Requirement</td> <td>SAN</td> <td>Storage Array Net</td> </tr> <tr> <td>GbE</td> <td>Gigabit Ethernet</td> <td>SUT</td> <td>System Under Test</td> </tr> <tr> <td>ID</td> <td>Identification</td> <td>UCR</td> <td>Unified Capabilities Requirements</td> </tr> </table>				CNA	Converged Network Adapter	Mbps	Megabits per second	CR	Capability Requirement	NAS	Network Attached Storage	FC	Fibre Channel	O	Optional	FCP	FFC Protocol	R	Required	FR	Functional Requirement	SAN	Storage Array Net	GbE	Gigabit Ethernet	SUT	System Under Test	ID	Identification	UCR	Unified Capabilities Requirements
CNA	Converged Network Adapter	Mbps	Megabits per second																												
CR	Capability Requirement	NAS	Network Attached Storage																												
FC	Fibre Channel	O	Optional																												
FCP	FFC Protocol	R	Required																												
FR	Functional Requirement	SAN	Storage Array Net																												
GbE	Gigabit Ethernet	SUT	System Under Test																												
ID	Identification	UCR	Unified Capabilities Requirements																												

**Table 3. SUT Capability Requirements and Functional Requirements Status**

CR/FR ID	UCR Requirement (High-Level) (See note 1.)	UCR 2013 Reference	Status																				
1	Data Storage Controller (DSC) (R)	Section 14	Partially Met (See notes 2 and 3.)																				
<p><b>NOTE(S):</b></p> <ol style="list-style-type: none"> <li>The annotation of 'required' refers to a high-level requirement category. Enclosure 3 of Reference (c) provides the applicability of each sub-requirement.</li> <li>The SUT met the requirements with the exceptions noted in Table 1. DISA adjudicated these exceptions as minor or as change requirements.</li> <li>A JITC-led Cybersecurity test team accomplished Security testing and published the results in a separate report, Reference (e).</li> </ol> <p><b>LEGEND:</b></p> <table style="width: 100%; border: none;"> <tr> <td style="width: 50%;">CR</td> <td style="width: 50%;">Capability Requirement</td> <td style="width: 50%;">JITC</td> <td style="width: 50%;">Joint Interoperability Test Command</td> </tr> <tr> <td>DISA</td> <td>Defense Information Systems Agency</td> <td>R</td> <td>Required</td> </tr> <tr> <td>DSC</td> <td>Data Storage Controller</td> <td>SUT</td> <td>System Under Test</td> </tr> <tr> <td>FR</td> <td>Functional Requirement</td> <td>UCR</td> <td>Unified Capabilities Requirements</td> </tr> <tr> <td>ID</td> <td>Identification</td> <td></td> <td></td> </tr> </table>				CR	Capability Requirement	JITC	Joint Interoperability Test Command	DISA	Defense Information Systems Agency	R	Required	DSC	Data Storage Controller	SUT	System Under Test	FR	Functional Requirement	UCR	Unified Capabilities Requirements	ID	Identification		
CR	Capability Requirement	JITC	Joint Interoperability Test Command																				
DISA	Defense Information Systems Agency	R	Required																				
DSC	Data Storage Controller	SUT	System Under Test																				
FR	Functional Requirement	UCR	Unified Capabilities Requirements																				
ID	Identification																						

**Table 4. DoDIN APL Product Summary**

<b>Product Identification</b>			
Product Name	Dell EMC Unity Family		
Software Release	OE 5.0 (See note 1.)		
DoDIN Product Type(s)	Data Storage Controller		
Product Description	The SUT performs data replication, mirroring, back-up, continuance of operation, and disaster recovery functions.		
<b>Product Components</b> (See note 2.)	<b>Component Name</b> (See note 3.)	<b>Version</b>	<b>Remarks</b>
Primary and Secondary Data Storage Controller (x2)	300, 300F, 350F, <b>400</b> , 400F, 450F, 500, 500F, 550F, 600, <b>650E</b> .	5.0 (See note 1.)	
Primary and Secondary Data Storage Controller (x2)	380, 380F, 480, 480F, 680, 680F, 880, 880F	5.0	See note 4.

**Table 4. DoDIN APL Product Summary (continued)**

<b>NOTE(S):</b>			
1. The software version was upgraded from OE 4.2 to OE 4.4 with DTR 1. DTR 2 updated the SUT software version from OE 4.4 to OE 4.5. DTR 3 updated the SUT software version from OE 4.5 to OE 5.0.			
2. Enclosure 3 of Reference (c) provides the detailed component and subcomponent list			
3. Components bolded and underlined were tested by JITC. The other components in the family series were not tested, but are also certified for joint use. JITC certifies those additional components because they utilize the same software and similar hardware and JITC analysis determined them to be functionally identical for interoperability certification purposes.			
4. DTR 3 added the 380, 380F, 480, 480F, 680, 680F, 880, and 880F Dell EMC Unity models based on analysis (no testing) because they are functionally identical for interoperability certification purposes to the currently certified SUT Unity models and they utilize the same OE software.			
<b>LEGEND:</b>			
APL	Approved Products List	JITC	Joint Interoperability Test Command
DoDIN	Department of Defense Information Network	OE	Operating Environment
DTR	Desktop Review	SUT	System Under Test
F	Flash		

**4. Test Details.** The extension of this certification is based upon DTR 3. The original certification, Reference (c), was based on interoperability (IO) testing, review of the vendor’s Letters of Compliance (LoC), the Defense Information Systems Agency (DISA) adjudication of open Test Discrepancy Reports (TDRs), and the DISA Certifying Authority Recommendation for inclusion on the DoDIN APL. Conducted testing at JITC’s Global Network Test Facility at Fort Huachuca, Arizona, from 30 October through 9 November 2017, using test procedures derived from Reference (d). Conducted a follow-on Verification and Validation IO test from 27 November to 1 December 2017, using test procedures derived from Reference (d). Completed review of the vendor’s LoC on 30 October 2017. DISA adjudicated outstanding TDRs on 30 January 2018. A JITC-led Cybersecurity (CS) test team conducted CS testing and published the results in a separate report, Reference (e).

DTR 3 was requested to update the SUT software version from OE 4.5 to OE 5.0 and to add the Dell EMC Unity 380, 380F, 480, 480F, 680, 680F, 880, and 880F hardware platforms to the certification by similarity. JITC analysis determined the software update included minor commercial enhancements and defect resolutions that did not affect the certified IO features and functions or the approved CS posture of the SUT. The new Unity models added with DTR 3 are functionally identical for IO certification purposes to the currently certified SUT Unity models and they utilize the same OE software; therefore, no further IO or CS testing was required. In addition, Reference (e) documents the approved CS posture of the SUT. With no change to the certified IO features and functions of the SUT, JITC approves this DTR.

**5. Additional Information.** JITC distributes interoperability information via the JITC Electronic Report Distribution system, which uses Sensitive but Unclassified Internet Protocol Data (formerly known as NIPRNet) e-mail. Interoperability status information is available via the JITC System Tracking Program (STP). STP is accessible by .mil/.gov users at <https://stp.fhu.disa.mil/>. Test reports, lessons learned, and related testing documents and references are on the JITC Industry Toolkit (JIT) at <https://jit.fhu.disa.mil/>. Due to the sensitivity of the information, the CS Assessment Package that contains the approved configuration and deployment guide must be requested directly from the Approved Products Certification Office (APCO), e-mail: [disa.meade.ie.list.approved-products-certification-office@mail.mil](mailto:disa.meade.ie.list.approved-products-certification-office@mail.mil). All associated information is available on the DISA APCO website located at

JITC Memo, JTE, Extension of the Joint Interoperability Certification of the Dell EMC Unity Family OE 5.0

<http://www.disa.mil/Services/Network-Services/UCCO>.

6. **Point of Contact (POC).** JITC POC: Ms. Sibylle Gonzales, commercial telephone (520) 538-5483, DSN telephone 879-5483, FAX DSN 879-4347; e-mail address: Sibylle.j.gonzales.civ@mail.mil; mailing address: Joint Interoperability Test Command, ATTN: JTE (Ms. Sibylle Gonzales), P.O. Box 12798, Fort Huachuca, AZ 85670-2798. The APCO tracking number for the SUT is 1709401.

FOR THE COMMANDER:

Enclosure a/s

for RIC HARRISON  
Chief  
Networks/Communications & DoDIN  
Capabilities Division

**Distribution (electronic mail):**

DoD CIO  
Joint Staff J-6, JCS  
USD (AT&L)  
ISG Secretariat, DISA, JT  
U.S. Strategic Command, J665  
US Navy, OPNAV N2/N6FP12  
US Army, DA-OSA, CIO/G-6 ASA (ALT), SAIS-IOQ  
US Air Force, SAF/CIO A6XA  
US Marine Corps, MARCORSSYSCOM, SIAT, A&CE Division  
US Coast Guard, CG-64  
DISA/ISG REP  
DIA, Office of the Acquisition Executive  
NSG Interoperability Assessment Team  
DOT&E, Netcentric Systems and Naval Warfare  
Medical Health Systems, JMIS PEO T&IVV  
HQUSAISEC, AMSEL-IE-IS  
APCO

## **ADDITIONAL REFERENCES**

- (c) Joint Interoperability Test Command (JITC) Memo, JTE, "Joint Interoperability Certification of the Dell EMC Unity Family OE 4.2," 2 February 2018
- (d) JITC, "Data Storage Controller (DSC) Test Procedures for Unified Capabilities Requirements (UCR) 2013 Change 1," August 2016
- (e) JITC, "Cybersecurity Assessment Report for Dell EMC Unity Family Operating Environment (OE) 5.0 Tracking Number (TN) 1709401)," September 2019